

REL. S.O.	FRAME	HP	TYPE	PHASE/ HERTZ	RPM	VOLTS
	364TC	60	P	3/60	1780	230/460
AMPS	DUTY	AMB °C/ INSUL.	S.F.	NEMA DESIGN	CODE LETTER	ENCL.
136/68	CONT	40/F	1.00	B	G	TEFC
E/S	ROTOR	TEST S.O.	TEST DATE	STATOR RES. @25 °C OHMS (BETWEEN LINES)		
492281	418141035YE	---	---	.0277/.110		

PERFORMANCE

LOAD	HP	AMPERES	RPM	% POWER FACTOR	% EFFICIENCY
NO LOAD	0	20.1	1800	4.67	0
1/4	15.0	25.8	1795	58.6	93.0
2/4	30.0	37.5	1791	78.7	95.2
3/4	45.0	51.9	1786	85.0	95.3
4/4	60.0	68.0	1781	87.0	95.0
5/4	75.0	85.1	1775	87.5	94.3

SPEED TORQUE

	RPM	TORQUE % FULL LOAD	TORQUE LB.-FT.	AMPERES
LOCKED ROTOR	0	181	320	430
PULL UP	720	161	285	395
BREAKDOWN	1703	251	445	244
FULL LOAD	1781	100	177	68.0

AMPERES SHOWN FOR 460. VOLT CONNECTION. IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE

REMARKS: TYPICAL DATA
 XE MOTOR-NEMA NOM. EFF. 95.0 %
 GUARANTEED MIN. EFF. 94.1%



DR. BY D. M. BYRD
 CK. BY J. P. TSAO
 APP. BY E. J. CHRISTIAN
 DATE 10/10/91


**A-C MOTOR
 PERFORMANCE A36WG0261-R007
 DATA** ISSUE DATE 05/21/19

REL S.O.
 FRAME 364TC
 HP 60
 TYPE P
 PHASE/HERTZ 3/60

RPM 1780
 VOLTS 230/460
 AMPS 136/68
 DUTY CONT
 AMB °C/INSUL 40/F

S.F. 1.00
 NEMA DESIGN B
 CODE LETTER G
 ENCLOSURE TEFC
 E/S 492281

ROTOR 418141035YE
 TEST S.O. TYPICAL DATA
 TEST DATE ---
 STATOR RES. @ 25 °C .0277/.110
 OHMS (BETWEEN LINES)



AMPERES SHOWN FOR 460 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.



DR. BY D. M. BYRD
 CK. BY J. P. TSAO
 APP. BY E. J. CHRISTIAN
 DATE 10/10/91


A-C MOTOR PERFORMANCE CURVES
 A36WG0261-R007
 ISSUE DATE 05/21/19

REL. S.O.
 FRAME 364TC
 HP 60
 TYPE P
 PHASE/HERTZ 3/60

RPM 1780
 VOLTS 230/460
 AMPS 136/68
 DUTY CONT
 AMB °C/INSUL 40/F

S.F. 1.00
 NEMA DESIGN B
 CODE LETTER G
 ENCLOSURE TEFC
 E/S 492281

ROTOR 418141035YE
 TEST S.O. TYPICAL DATA
 TEST DATE ---
 STATOR RES. @ 25 °C .0277/.110
 OHMS (BETWEEN LINES)



THERMAL LIMIT CURVE

REMARKS: XE MOTOR-NEMA NOM. EFF. 95.0 %
 GUARANTEED MIN. EFF. 94.1%

AMPERES SHOWN FOR 460 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.



DR. BY D. M. BYRD
 CK. BY J. P. TSAO
 APP. BY E.J. CHRISTIAN
 DATE 10/10/91

A-C MOTOR PERFORMANCE CURVES
A36WG0261-R007
 ISSUE DATE 05/21/19