

ABB BALDOR RELIANCE III

Customer information packet CEM2550T

100HP, 3540RPM, 3PH, 60HZ, 365TSC, OPSB, F1

Specifications

Enclosure	OPSB
Frame	365TSC
Frame Material	Steel
Frequency	60.00 Hz
Motor Letter Type	Three Phase
Output @ Frequency	100.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CURUSEEV NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	220.000 A @ 230.0 V 110.000 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.6 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Heater Indicator	No Heater
High Voltage Full Load Amps	110.0 a
Insulation Class	F
Inverter Code	Inverter Ready
IP Rating	NONE
KVA Code	G

Part Detail

Revision	D
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	42WGW937
Layout	42LY-000-021
Eff. date	02-12-2024
CD Diagram	CD0180
Poles	02
Leads	9#4
Proprietary	False
Created date	03-06-2020

Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	4266M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	27.81 IN
Power Factor	91
Product Family	General Purpose
Pulley Face Code	C-Face
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	3540 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate
NP2138L

CAT.NO.	CEM2550T		P/N			ENCLOSURE	OPSB						
SPEC.	42-0000-0075	CC	010A	FRAME	365TSC	S/N							
HP	100		CLASS	F	HZ	60							
RPM	3540		PH	3	DES	A							
VOLT	230/460				KVA-CODE	G	ODE BRG	6311	DE BRG	6313			
AMP	220/110												
RATING	40C AMB-CONT		GREASE	POLYREX EM									
NEMA-NOM-EFF	93.6	PF	91	SER.F.	1.15								
HTR-VOLTS		HTR-AMPS											

Parts List

Part number	Description	Quantity
SA379773	SA 42-0000-0075	1.000 ea
RA369796	RA 42-0000-0075	1.000 ea
LB1624	COMBINED WARNING LABEL, ISO/ANSI PICTOGR	1.000 ea
LC0181	CONNECTION LABEL	1.000 ea
NP2138L	ALUM SUPER-E UL PREM CC (300	1.000 ea
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	4.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
HA6360	LIFTING LUG FOR 42 FRAME MOTORS.	2.000 ea
MJ1000A02	GREASE, POLYREX EM EXXON	0.200 lb
HA3151A09	THRUBOLT STUD 1/2-13 X 22.000	4.000 ea
HW1001A50	LOCKWASHER 1/2, ZINC PLT, .879 OD, .509 I	8.000 ea
XY5013A12	NUT, 1/2-13, HEX, STEEL, ZINC PLATED	8.000 ea
42EP3200A01	FR ENDPLATE, MACH	1.000 ea
HW5100A13	W4627-047 WVY WSHER	1.000 ea
HA4051A00	PLASTIC CAP FOR GREASE FITTING	1.000 ea
HW4500A03	GREASE FITTING, .125 NPT 1610(ALEMITE) 8	1.000 ea
HW4500A20	1/8NPT SL PIPE PLUG	1.000 ea
42EP1400A01	PUEP MACH,	1.000 ea
10XN3816K52	3/8-16 X 3-1/4 HEX HEAD CAP SCREW GRD 5	4.000 ea
HW1001A38	LOCKWASHER 3/8, ZINC PLT .688 OD, .382 I	4.000 ea
HA4051A00	PLASTIC CAP FOR GREASE FITTING	1.000 ea
HW4500A03	GREASE FITTING, .125 NPT 1610(ALEMITE) 8	1.000 ea
HW4500A20	1/8NPT SL PIPE PLUG	1.000 ea
10CB1000A390	CONDUIT BOX, MACH	1.000 ea
19XW3118A12	.31-18 X .75 HEX WASHER HEAD TAPTITE II	4.000 ea
HW1001A31	LOCKWASHER 5/16, ZINC PLT .591 OD, .319 I	4.000 ea
WD1000B53	TERMINAL BURNDY KPA34	1.000 ea
10XN5013K10	1/2-13 X .625 HEX HD, GRADE 5	1.000 ea
HA6017	CAST ADAPTER, 40, 42 KOBX	1.000 ea
19XW3118A12	.31-18 X .75 HEX WASHER HEAD TAPTITE II	2.000 ea
HW1001A31	LOCKWASHER 5/16, ZINC PLT .591 OD, .319 I	2.000 ea

10CB1500	STANDARD 10 FRAME CONDUIT BOX LID, CAST	1.000 ea
10XN2520K16	1/4-20 X 1" HX HD SCRW GRADE 5, ZINC P	4.000 ea
HW1001A25	LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I	4.000 ea
42AD2001A01	BAFFLE PLATE 42 OPEN, SLOTTED BAND MTRS	1.000 ea
MG1050Y01	CELEROL BALDOR GOLD *5 GALLON BUCKET*	0.125 ga
42AD2001A01	BAFFLE PLATE 42 OPEN, SLOTTED BAND MTRS	1.000 ea
40PA1000	PACKAGING GROUP	1.000 ea
HW2501H18	KEY, 1/2 SQ X 2.000	1.000 ea

AC Induction Motor Performance Data

Record # 38382

Typical performance - not guaranteed values

Winding: 42WGW937-R001			Type: 4266M		Enclosure: OPSB	
Nameplate Data				460 V, 60 Hz: High Voltage Connection		
Rated Output (HP)		100		Full Load Torque		148 LB-FT
Volts		230/460		Start Configuration		direct on line
Full Load Amps		220/110		Breakdown Torque		483 LB-FT
R.P.M.		3540		Pull-up Torque		172 LB-FT
Hz	60	Phase	3	Locked-rotor Torque		245 LB-FT
NEMA Design Code		B	KVA Code	Starting Current		771 A
Service Factor (S.F.)		1.15		No-load Current		23.5 A
NEMA Nom. Eff.		93.6	Power Factor	Line-line Res. @ 25°C		0.0539 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		45°C
S.F. Amps				Temp. Rise @ S.F. Load		55°C
				Locked-rotor Power Factor		21
				Rotor inertia		5.16 LB-FT2

Load Characteristics 460 V, 60 Hz, 100 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	72	87	90	91	91	89	91
Efficiency	91.3	93.9	94	93.6	92.7	91.6	93
Speed	3584	3568	3552	3536	3518	3496	3525
Line amperes	36.1	57.7	82.8	110	138	169	127


ABB Motors and Mechanical Inc.

WINDING # 42WGW937

Typical performance - not guaranteed values.

100 HP 3 PH 60 HZ 3540 RPM 460 V 4266M

TORQUES (LB-FT): PO=483 PU=172 LR=245 LRA=771





CD0180


LOW VOLTAGE
(2D)

HIGH VOLTAGE
(1D)

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: -


BALDOR - RELIANCE®

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1

CD0180