ABB BALDOR RELIANCE

Customer information packet

CEWDM2402T

10HP, 880RPM, 3PH, 60HZ, 284TC, TEFC, F1
Class - None
Division - Not Applicable

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
11/1/2026 7:21:19 PM

Specifications

Enclosure	TEFC
Frame	284TC
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	10.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	900 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
	230.0 V @ 60 HZ
Agency Approvals	CSA
	CSA EEV
	NEMA PREMIUM
	UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	30.000 A @ 208.0 V
	29.200 A @ 230.0 V
	14.600 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Enclosure Modification	Severe Duty Features
Feedback Device	NO FEEDBACK

Part Detail

Revision	G
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	10WGZ392
Layout	10LYP093
Eff. date	02-21-2024
CD Diagram	CD0180
Poles	08
Leads	9#10
Proprietary	False
Created date	08-16-2019

Heater Indicator	No Heater
High Voltage Full Load Amps	14.6 a
Insulation Class	F
Inverter Code	Inverter Duty
IP Rating	IP55
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	1350 rpm
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1046M
Mounting Arrangement	F1
Number of Poles	8
Overall Length	27.56 IN
Power Factor	71
Product Family	Washdown Features
Pulley Face Code	C-Face
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	1.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	880 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1669L									
CAT.NO.	CEWDM2402T								
SPEC.	10-0000-1014								
HP	10								
VOLTS	230/460 10:1 CT/VT								
AMP	29.2/14.6								
RPM	880								
FRAME	284TC	**HZ**	60			**PH**	3		
SER.F.	1.00	**CODE**	H	**DES**	B	**CLASS**	F		
NEMA-NOM-EFF	89.5	**PF**	71						
RATING	40C AMB-CONT								
CC	010A								
DE	6311	**ODE**	6309						
ENCL	TEFC	**SN**							
BLANK	1.15SF ON SINEWAVE								

Parts List

Part number	Description	Quantity
SA373165	SA 10-0000-1014	1.000 ea
RA362949	RA 10-0000-1014	1.000 ea
LB1624	COMBINED WARNING LABEL, ISO/ANSI PICTOGR	1.000 ea
LC0181	CONNECTION LABEL	1.000 ea
NP1669L	SS WD SUPER-E UL PREM REV MTG	1.000 ea
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
10FH1007WP	FAN COVER, W/WHITE EPOXY, PRIMED CASTING	1.000 ea
HW1001S31	WASHER, 5/16 SPLT LK, STAINLESS STEEL	3.000 ea
10XN3118S24	5/16-18 X 1 1/2 HEX HD SS	3.000 ea
09FN3001C02	EXTERNAL FAN, PLASTIC (COMES W/SCREW FRO	1.000 ea
HW2500A25	WOODRUFF KEY USA #1008 #BLOW CARBON STEE	1.000 ea
MJ1000A02	GREASE, POLYREX EM EXXON	0.130 lb
WD4100A02	DP-1000 HEYCO PLUG OR 62MP1000 MICRO PL	1.000 ea
10EP1104A42WP	FREP, MACH W/O GRSRS & RET HLS W/WHITE E	1.000 ea
10XN3816S32	3/8-16 X 2 HEX HD CAP SCREW, STAINLE	4.000 ea
HW1001S38	WASHER, 3/8 SPLT LK, STAINLESS STEEL	4.000 ea
HW4600B67	V-RING SLINGER 1.770 X 2.170 X .28 VITON	1.000 ea
HW5100A11	W3917-042 WVY WSHR (WB)	1.000 ea
HA4054	SHORT T-DRAIN FITTING, .125" N.P.T.	1.000 ea
10EP1305A45P	PUEP, MACH - W/O GRSRS, W/SEAL, EPOXY PR	1.000 ea
10XN3816S28	3/8-16 X 1 3/4 HEX HD CAP SCREW, STAINLE	4.000 ea
HW4600B40	V-RING SLINGER 2.000 X 2.680 X .28 VITON	1.000 ea
HW4600A53	SEAL 2.00 X 3.00 X 0.313 SINGLE LIP	1.000 ea
10XN3118S40	5/16-18X2 1/2 HEX HD SS	4.000 ea
HA4054	SHORT T-DRAIN FITTING, .125" N.P.T.	1.000 ea
10CB3000A05P	SPL CO BOX MACH. W/2" PIPE TAP, EPOXY PR	1.000 ea
09GS1010	GASKET, DWG, LEADWIRE SEPERATOR	1.000 ea
10XN3118K12	5/16-18 X .75 GRADE 5, ZINC PLATED	4.000 ea
HW1001A31	LOCKWASHER 5/16, ZINC PLT.591 OD, .319 I	4.000 ea
WD1000B25	GND LUG, BURNDY L125HP OR T&B L125HP-BB	1.000 ea

19XW3118G08	.31-18X.50,HEX WSHR HD,TAPTITE 2,GREEN	1.000 ea
10CB3500P	CONDUIT BOX LID, CAST - EPOXY PRIMED	1.000 ea
10GS1000A01	CONDUIT BOX LID GASKET NEOPRENE	1.000 ea
19XT2520S12	1/4-20X3/4 HWH NO SLOT TY.23 18-8 S.S.	4.000 ea
HW1001S25	WASHER, 1/4 SPLT LK, STAINLESS STEEL	4.000 ea
MG1025W01	WILKOFAST, 781.01, SIGNAL WHITE #9003	0.125 ga
MJ5001A27	32220KN GRAY SEALER *MIN BUY 4 QTS=1GAL	0.031 qt
MJ5002A01	SILICON RUBBER SEALANT, 732CL 10.3 OZ TU	0.033 ea
MJ5002A01	SILICON RUBBER SEALANT, 732CL 10.3 OZ TU	0.025 ea
10PA1000	PACKAGING GROUP COMBINED PRINT PK1023A07	1.000 ea
HW2502H28	#303 SS,SQ KEY 1/2 X 3.250	1.000 ea
51XB1214S20	12-14X1.25 HXWSSLD SERTYB, SS	1.000 ea

AC Induction Motor Performance Data
Record # 65626
Typical performance - not guaranteed values

Winding: 10WGZ392-R011	**Type:** 1046M	**Enclosure:** TEFC

Nameplate Data				**460 V, 60 Hz: High Voltage Connection**	
Rated Output (HP)			10	**Full Load Torque**	59.3 LB-FT
Volts			230/460	**Start Configuration**	direct on line
Full Load Amps			29.2/14.6	**Breakdown Torque**	169 LB-FT
R.P.M.			880	**Pull-up Torque**	76.4 LB-FT
Hz	60	**Phase**	3	**Locked-rotor Torque**	137 LB-FT
NEMA Design Code	B	**KVA Code**	H	**Starting Current**	80 A
Service Factor (S.F.)			1	**No-load Current**	8.76 A
NEMA Nom. Eff.	89.5	**Power Factor**	71	**Line-line Res. @ 25ºC**	0.956 Ω
Rating - Duty			40C AMB-CONT	**Temp. Rise @ Rated Load**	65°C
				Locked-rotor Power Factor	30.5
				Rotor inertia	5.67 LB-FT2

Load Characteristics 460 V, 60 Hz, 10 HP

% of Rated Load	**25**	**50**	**75**	**100**	**125**	**150**
Power Factor	32	51	64	71	75	77
Efficiency	81	87.8	89.5	89.8	89.6	88.7
Speed	896	893	890	886	881	876
Line amperes	9.23	10.6	12.3	14.6	17.4	20.4


ABB Motors and Mechanical Inc.


WINDING # 10WGZ392

10 HP 3 PH 60 HZ 880 RPM 460 V 1046M


Typical performance - not guaranteed values.


TORQUES(LB-FT): PO=169 PU=76.4 LR=137 LRA=80




10LYP093
(1024-1080) = 27.63
12.75
4.38
.25
.50 KEY
3.25 LONG
Ø15.31
11.16
Ø 10.500
10.497
Ø 1.875
1.874
SLINGER
(EA. END)
8 HOLES
Ø.53
9.50
.92
9.50
4.75
11.00
12.84
15.72
13.33
7.80
45°
45°
4 HOLES
.50-13 TAP
.88 DEE
Ø9.00 B.C.
2.50
14.64
7.00 +.00 -.06
LEAD HOLE
Ø2.00 NPT
AUTO DRAIN
(EA END)
5.50
5.50
10.66
6.38
12.75
HW4600A53
HW4600B40
DRIVE END SEAL DETAIL
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION
REV. DESC: CONVERT AUTOCAD DRW TO SWD
REV: L
VERSION: 08
REVISED: 11:06:08 06/28/2023
TDR: 000001211833
MODEL NO. 10LYP093
REF: -
BY: ENALEM0
B
BALDOR - RELICANCE®
HORZ TEFC 284-6TC WD FEATURES W/PU LIP SEAL
10LYP093

CD0180





NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0180

REV. DESC: ADD CLASS CONN00000007		
REV. LTR: D	VERSION: 01	TDR: 000001099922
FILE: \AAA\00005\148	REVISED: 10:25:29 02/19/2019	BY: ENBRIR0
MTL: –		

BALDOR - RELIANCE®

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1