

ABB BALDOR RELIANCE III

Customer information packet

CFM3156A

1 AIR-OVERHP, 1170RPM, 3PH, 60HZ, 56YZ, 3522M

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	56YZ
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	1.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	208.0 V @ 60 HZ 230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	C UR US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	1.700 A @ 460.0 V 3.400 A @ 230.0 V 3.500 A @ 208.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	78.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	1.7 a

Part Detail

Revision	D
Type	AC
Mech. spec.	35K306
Base	
Status	PRD/A
Elec. spec.	35WGG339
Layout	35LYK306
Eff. date	07-25-2024
CD Diagram	CD0007
Poles	06
Leads	12#18
Proprietary	False
Created date	12-19-2022

Insulation Class	F
Inverter Code	Not Inverter
IP Rating	NONE
KVA Code	H
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	12 @ 18 AWG
Motor Lead Termination	None
Motor Standards	NEMA
Motor Type	3522M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	16.30 IN
Power Factor	69
Product Family	General Purpose
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	Other
Pulley Shaft Indicator	Key And Flat
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1170 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Do Not Use Eve-Not Valid
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Automatic Thermal Overload
Winding Thermal 1 Location	ES
Winding Thermal 2	None

Nameplate

NP1257L											
CAT.NO.	CFM3156A										
SPEC.	35K306G339G1										
HP	1 AIR-OVER										
VOLTS	208-230/460										
AMP	3.5-3.4/1.7										
RPM	1170										
FRAME	56YZ				HZ		60		PH		3
SER.F.	1.15	CODE		H	DES		B	CL		F	
NEMA-NOM-EFF	78.5	PF		69							
RATING	40C AMB-CONT										
CC											
DE	6203	ODE		6205							
ENCL	OPEN	SN									
	SFA 3.9-3.8/1.9										

Parts List

Part number	Description	Quantity
SA409933	SA 35K306G339G1	1.000 ea
RA401509	RA 35K306G339G1	1.000 ea
TPMYJ56WM	THERMAL 3PH 0.75 AUT 135C	1.000 ea
RM1001A01	GROMMET "MIDSTATES"	1.000 ea
11XW0832G06	#8-32 X 3/8, TAPTITE II, HEX WSHR SLTD	1.000 ea
HA6001A01	THERMAL RETAINER (PLATED)	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 ea
MG1050G01	CELEROL MEDIUM CHARCOAL METALLIC GRAY	0.017 ga
35EP3210B00	MASTER DE,205 BRG,1.000SH	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 ea
MJ5004A05	#242-21 LOCTITE GENERAL PURPOSE MED. STR	0.010 ea
HW5100A03	WAVY WASHER (W1543-017)	1.000 ea
35EP3102B42	PUEP SH THRU HOLE .50 NPT, 2 #26 DRILL F	1.000 ea
XY1032A02	10-32 HEX NUT DIRECTIONAL SERRATION	4.000 ea
35CB4500	TERMINAL BOX LID STAMPED	1.000 ea
HA1041A01	CUPPED SLINGER KENCO	1.000 ea
HW2501D40	KEY, 3/16 SQ X 4.750	1.000 ea
HA7000A04	KEY RETAINER 0.625 DIA SHAFTS	1.000 ea
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
10XN2520A06	1/4 20X3/8 HX HD CAP	3.000 ea
MJ1000A02	GREASE, POLYREX EM EXXON	0.050 lb
35GS1002A02	GASKET,1/16 THICK NEOPRE.FT.SMITH MADE	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 ea
SP5079A02	MODEL 35 3PH TERM PANEL CONN 12LD DUAL V	1.000 ea
WD1000A16	2-520128-2 AMP FLAG TERMINAL(4M/RL)	12.000 ea
HA3100A19	THRUBOLT 10-32 X 9.625	4.000 ea
LB1118	LABEL,WARNING (ROLL LABEL)	1.000 ea
LC0007A01	CONN LABEL TYPE M,DV,REV,12LD 2Y/1Y TERM	1.000 ea
NP1257L	ALUM UL CC THERMAL REV MTG	1.000 ea
36PA1000	PKG GRP, PRINT PK1016A08	1.000 ea
PK3085X	FOAM SHAFT SUPPORT PRECUT 4-1/4 X 6-3/4	1.000 ea

PK3082	STYROFOAM CRADLE	1.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
FE-0000001	ZRTG FE ASSEMBLY	1.000 ea


ABB Motors and Mechanical Inc.


WINDING # 35WGG339

Typical performance - not guaranteed values.



1 HP 3 PH 60 HZ 1170 RPM 460 V 3522M

TORQUES (LB-FT): PO=11.4 PU=8.02 LR=8.81 LRA=8.29





CD0007



- NOTES:
1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 2. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
 3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: ADDED "CK" PLANT CODE			
REV. LTR: E	BY: EAH	REVISED: 05/06/99 17:1	TDR: 0181040
L00000		FILE: AAA00008370	MDL: -
		MTL: -	

BALDOR ELECTRIC Co.

3PH, DV, THERMAL, 12 LEADS

CD0007