

ABB BALDOR RELIANCE III

Customer information packet

CJL1303A

.5HP, 3450RPM, 1PH, 60HZ, 56J, 3420L, OPEN, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	56J
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Induction Run
Output @ Frequency	.500 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 115.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	7.400 A @ 115.0 V 3.700 A @ 230.0 V
Design Code	N
Drip Cover	Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	66.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Drip Cover Mounting
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	3.7 a

Part Detail

Revision	AE
Type	AC
Mech. spec.	34F492
Base	
Status	PRD/A
Elec. spec.	34WG2413
Layout	34LYF492
Eff. date	10-25-2024
CD Diagram	CD0307
Poles	02
Leads	5#18,1#16 #1TH
Proprietary	False
Created date	01-01-0001

Insulation Class	B
Inverter Code	Not Inverter
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Terminal Panel Or Lead Hole
Motor Lead Quantity/Wire Size	5 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3420L
Mounting Arrangement	F1
Number of Poles	2
Overall Length	12.51 IN
Power Factor	67
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Ext Thread
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.60
Shaft Diameter	0.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Fixed Opposite Standard
Shaft Slinger Indicator	No Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Automatic Thermal Overload
Winding Thermal 1 Location	SB

Winding Thermal 2

None

Nameplate

NP1257L											
CAT.NO.	CJL1303A										
SPEC.	34F492-2413G1										
HP	.5										
VOLTS	115/230										
AMP	7.4/3.7										
RPM	3450										
FRAME	56J			HZ		60		PH		1	
SER.F.	1.60		CODE	L	DES		N	CL	B		
NEMA-NOM-EFF	66		PF	67							
RATING	40C AMB-CONT										
CC											
DE	6203		ODE		6203						
ENCL	OPEN	SN									
	SFA 9.4/4.7										

Parts List

Part number	Description	Quantity
SA010331	SA 34F492-2413G1	1.000 ea
RA006719	RA 34F492-2413G1	1.000 ea
TPMRJ30RX	THERMAL 1PH 0.75 AUT 120C	1.000 ea
EC1189A02SP	61B2D120189NNBA ELEC CAP, 189-227MFD, 12	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	3.000 ea
11XW0832G06	#8-32 X 3/8, TAPTITE II, HEX WSHR SLTD	1.000 ea
WD4100A01	DP-875 HEYCO PLUG OR 62MP0875 MICRO PLAS	1.000 ea
NS2500A01	INSULATOR, AUTO THER PROT	1.000 ea
34CB4800SP	CAPACITOR COVER, STAMPED PRIMED	1.000 ea
51XB1016A05	10-16X5/16HX WA SL SR TYB (F/S)	2.000 ea
HW5100A03	WAVY WASHER (W1543-017)	1.000 ea
34EP3401A01SP	PU ENDPLATE, MACH	1.000 ea
34AD2000	BAFFLE PLATE, STAMPED	1.000 ea
60XW0632A06	6-32 X 3/8 TORX HEAD SCREW TAPTITE II	4.000 ea
51XN1032A20	10-32 X 1 1/4 HX WS SL SR	2.000 ea
34FH4500A02P	DRIPCOVER, MODEL 34	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 ea
34CB4501SP	TERMINAL BOX LID, STAMPED X (PLATED)	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 ea
RM1010A01	35-968-1 VINYL CLS	1.000 ea
WD1000A16	2-520128-2 AMP FLAG TERMINAL(4M/RL)	7.000 ea
34EP3202A02	FR ENDPLATE, MACH	1.000 ea
HA6001A03	THERMAL RETAINER (PLATED)	1.000 ea
51XT0632A06	6-32X3/8 TY23 HXWS SLDSR	2.000 ea
MG1050G01	CELEROL MEDIUM CHARCOAL METALLIC GRAY	0.014 ga
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
LB1009N	LABEL,ROTATION DIRECTION (ON ROLLS)	1.000 ea
SP5086A01	34 TERM PANEL SWITCH W/E-BLK & 8-RED	1.000 ea
HA3100A37	THRUBOLT 10-32 X 8.500	4.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
LB1118	LABEL,WARNING (ROLL LABEL)	1.000 ea

LC0307	1PH, DV, FIX, W & W/O THERM, TERM PLATE,	1.000 ea
NP1257L	ALUM UL CC THERMAL REV MTG	1.000 ea
35PA1066	PKG GRP, PRINT PK1008A07	1.000 ea


ABB Motors and Mechanical Inc.

WINDING # 34WG2413

Typical performance - not guaranteed values.


0.5 HP 1 PH 60 HZ 3450 RPM 230 V 3420L

TORQUES (LB-FT) : PO=2.3 PU=1.9 LR=2 LRA=20



8/6/2026 ACPERF, record # 6647

34LYF492



CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION

REV. DESC: LOAD TO SOLIDWORKS - REV A

REV: B

VERSION: 02

REVISED: 11:38:57 12/29/2022

TDR: 000001201165

BALDOR - RELIANCE®

34LYF492

MODEL NO. 34LYF492


BY: ENFRAJ0

REF: -

SPL HORZ 34L NEMA 56J OPEN W/DRIPCOVER, THERM IN T.P. EP

34LYF492

CD0307



REV. DESC: REMOVE OPTIONAL THERMAL CONNECTION		
REV. LTR: F	VERSION: 01	TDR: 000000373039
CD0307	FILE: \AAA\00007\308	REVISED: 11:45:00 08/11/2005
	MTL: -	BY: ENJOEPO

BALDOR ELECTRIC Co.

TYPE L, DV, FIX ROT, THERMAL, TERMINAL PLATE (OPP STD)

CD0307