

ABB BALDOR RELIANCE III

Customer information packet

CPX18346T

3//2HP, 1755//1465RPM, 3PH, 60//50HZ, 182T, X

Class - CLI GP C,D; CLII GP E,F,G

Division - Division I

Specifications

Enclosure	XPFC
Frame	182T
Frame Material	Iron
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	CLI GP C,D; CLII GP E,F,G
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	2.000 HP @ 50 HZ 3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 190.0 V @ 50 HZ 460.0 V @ 60 HZ 380.0 V @ 50 HZ
Agency Approvals	UL CSA EEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	6
Current @ Voltage	8.200 A @ 230.0 V 7.000 A @ 190.0 V 4.100 A @ 460.0 V 3.500 A @ 380.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT

Part Detail

Revision	M
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	06WGX181
Layout	06LYJ961
Eff. date	04-16-2026
CD Diagram	CD0005
Poles	04
Leads	9#16
Proprietary	False
Created date	02-05-2019

Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Enclosure Modification	Severe Duty Features
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	3.5 a
Insulation Class	F
Inverter Code	Inverter Duty
IP Rating	IP55
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	2700 rpm
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0632M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	17.59 IN
Power Factor	77
Product Family	Super-E Chemical Processing
Pulley Face Code	Standard
Rodent Screen	None
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	1755 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat

Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP2033XPSLEV												
NO.							CC	010A				
S/N							TEMP CODE	T3C				
SPEC.	06-0000-0019						INV.TYPE	PWM				
CAT.NO.	CPX18346T						C HP FR	60	C HP TO	90		
HP	3//2						CT HZ FROM	6	CT HZ TO	60		
VOLTS	230/460//190/380						VT HZ FROM	6	VT HZ TO	60		
AMPS	8.2/4.1//7/3.5						MAG CUR	4.2/2.1				
RPM	1755//1465						MX RPM	2700				
HZ	60//50	PH	3	CL	F	NOM.EFF.	89.5					
SER.F.	1.00	DES	B	SL HZ	1.5	WK2	0.3					
FRAME	182T	RATING	40C AMB-CONT									
BLANK	55C AMB AT 1.00 SF SINEWAVE											
	NEMA MG-1 PART 5, IP55						1.15 SF SINEWAVE					

Parts List

Part number	Description	Quantity
SA365815	SA 06-0000-0019	1.000 ea
RA355222	RA 06-0000-0019	1.000 ea
LB1624	COMBINED WARNING LABEL, ISO/ANSI PICTOGR	1.000 ea
LC0145B01	CONNECTION LABEL	1.000 ea
NP2033XPSLEV	SS XP INV UL CSA-EEV CC CL-I GP-C&D	1.000 ea
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	4.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
LB1081F	ALUM XP CAUTION LABEL (FS PLANT ONLY-	1.000 ea
HW3201A05	3/8-16 EYEBOLT	1.000 ea
06FH1003A06G	FAN COVER, X-PROOF--MACHINING W/GRAY EPO	1.000 ea
51XN1032A14	10-32 X 0.875 HX WS SL SR	4.000 ea
34FN3002A02	EXTERNAL FAN, PLASTIC, .905/.907 HUB W/	1.000 ea
MJ1000A02	GREASE, POLYREX EM EXXON	0.050 lb
06EP1709A10	FREP X06M - XPFC FOR GROUP C&E W/GREASER	1.000 ea
10XN3118K20	5/16-18 X 1 1/4 GRADE 5 STEEL ZC PLATED	4.000 ea
HA2009A46	SLINGER FOR GROUP E MTRS - 205 BRG.	1.000 ea
80XN0632J10	6-32 X 5/8 SET SCREW, HEX SOC, CUP PT	2.000 ea
HW5100A05	WVY WSHR F/205 & 304 BRGS	1.000 ea
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 ea
HW4500A19	1/4-28X1/4 SLOTTED PLUG F/S	1.000 ea
HW4506A02	BREATHING/DRAIN-EXP PROOF-.125-27 NPTF AI	1.000 ea
06EP1711A01	PU ENDPLATE, MACH	1.000 ea
HW1001A31	LOCKWASHER 5/16, ZINC PLT.591 OD, .319 I	4.000 ea
10XN3118K20	5/16-18 X 1 1/4 GRADE 5 STEEL ZC PLATED	4.000 ea
HA2009A57	SLINGER, FOR GROUP E MOTORS - 306 BRG.	1.000 ea
80XN0632J10	6-32 X 5/8 SET SCREW, HEX SOC, CUP PT	2.000 ea
51XN1032A28	10-32 X 1 3/4 HX WS SL SR	4.000 ea
HW4001A02	3/8 HX SOC PIPE PLUG W/.75" TAPER (F/S)	2.000 ea
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 ea
HW4500A19	1/4-28X1/4 SLOTTED PLUG F/S	1.000 ea

HW4506A02	BREATHER/DRAIN-EXP PROOF-.125-27 NPTF AI	1.000 ea
HW3022E05	.125 DIA X .500 ROLLED SPRING PIN	1.000 ea
07CB1000A02G	CONDUIT BOX, MODEL 306,EXP. PROOF,W/MG10	1.000 ea
10XN2520A14	1/4 20X7/8 HX HD CAP	4.000 ea
WD1000B17	T&B CX35TN OR L35P TERMINAL LUG	1.000 ea
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 ea
07CB1502A01G	CONDUIT BOX LID MACH (DUCTILE IRON) GRAY	1.000 ea
84XN2520J16	1/4-20 X 1 SOC HD CAP SCREW	4.000 ea
HW1001A25	LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I	4.000 ea
MG1500Y02	WILKOPON PRIMER YELLOW	0.001 ga
MG1025G29	WILKOFAS, 789.229, DARK CHARCOAL GRAY	0.022 ga
37PA1074	PALLET PACK GRP, PRINT BOX PK1026A06	1.000 ea
HW2501E18	KEY, 1/4 SQ X 2.000	1.000 ea
HA7000A02	KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA	1.000 ea
MJ5001A27	32220KN GRAY SEALER *MIN BUY 4 QTS=1GAL	0.001 qt

AC Induction Motor Performance Data

Record # 72220

Typical performance - not guaranteed values

Winding: 06WGX181-R087			Type: 0632M		Enclosure: XPFC		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		3//2	Full Load Torque		9.08 LB-FT		
Volts		230/460//190/380	Start Configuration		direct on line		
Full Load Amps		8.2/4.1//7/3.5	Breakdown Torque		33.1 LB-FT		
R.P.M.		1755//1465	Pull-up Torque		18.2 LB-FT		
Hz		60//50	Phase		3	Locked-rotor Torque	20.4 LB-FT
NEMA Design Code		B	KVA Code		J	Starting Current	29.8 A
Service Factor (S.F.)		1	No-load Current		2.14 A		
NEMA Nom. Eff.		89.5	Power Factor		77	Line-line Res. @ 25°C	3.93 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		35°C	
S.F. Amps				Temp. Rise @ S.F. Load		42°C	
				Locked-rotor Power Factor		41.4	
				Rotor inertia		0.298 LB-FT2	

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	38	58	70	77	81	83
Efficiency	83.5	88.9	90	89.8	89.1	87.7
Speed	1790	1779	1769	1757	1744	1730
Line amperes	2.34	2.79	3.39	4.1	4.91	5.86


ABB Motors and Mechanical Inc.

WINDING # 06WGX181

Typical performance - not guaranteed values.

3 HP 3 PH 60 HZ 1757 RPM 460 V 0632M

TORQUES (LB-FT): PO=33.1 PU=18.2 LR=20.4 LRA=29.8



AC Induction Motor Performance Data

Record # 72221

Typical performance - not guaranteed values

Winding: 06WGX181-R087				Type: 0632M		Enclosure: XPFC	
Nameplate Data				380 V, 50 Hz: High Voltage Connection			
Rated Output (HP)		3//2		Full Load Torque		7.25 LB-FT	
Volts		230/460//190/380		Start Configuration		direct on line	
Full Load Amps		8.2/4.1//7/3.5		Breakdown Torque		31.25 LB-FT	
R.P.M.		1755//1465		Pull-up Torque		18.55 LB-FT	
Hz	60//50	Phase	3	Locked-rotor Torque		20.79 LB-FT	
NEMA Design Code		B	KVA Code	J	Starting Current		28.72 A
Service Factor (S.F.)		1		No-load Current		2.11 A	
NEMA Nom. Eff.		89.5	Power Factor	77	Line-line Res. @ 25°C		3.93 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		28°C	
S.F. Amps				Temp. Rise @ S.F. Load		32°C	
				Locked-rotor Power Factor		46.1	
				Rotor inertia		0.298 LB-FT2	

Load Characteristics 380 V, 50 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	33	52	65	73	78	81
Efficiency	79.7	86.5	88.4	88.7	88.4	87.1
Speed	1491	1483	1474	1465	1455	1443
Line amperes	2.25	2.57	3.01	3.53	4.14	4.87

ABB Motors and Mechanical Inc.

WINDING # 06WGX181

Typical performance - not guaranteed values.

2 HP 3 PH 50 HZ 1465 RPM 380 V 0632M

TORQUES (LB-FT) : PO=31.25 PU=18.55 LR=20.79 LRA=28.72

