

ABB BALDOR RELIANCE III

Customer information packet D2005P

5HP, 1750RPM, 240V, DKPG, L186AT

Specifications

Armature Voltage	240 V
Base Speed	1750 rpm
Enclosure	DPFG
Field Voltage	150 V
	300 V
Output Power	5.000 HP
Agency Approvals	CSA
Ambient Temperature	40 °C
Armature Current	17.7 a
Drip Cover	No Drip Cover
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Field Winding Type	STR. SHUNT
Heater Indicator	No Heater
Insulation Class	F
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	F3
Overall Length	20.87 IN
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Slinger Indicator	No Slinger
Thermal Device - Bearing	None

Part Detail

Revision	-
Type	DC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	K0007A A
Layout	875
Eff. date	12-27-2019
CD Diagram	15209
Poles	00
Leads	
Proprietary	False
Created date	12-26-2019

Nameplate

NP1734									
CAT.NO.	D2005P			MODEL	T18S8005				
HP	5	RPM	1750/2300		FRAME	L 0186AT			
ARM V	240		ARM A	17.70	WOUND	STR. SHUNT			
FLD V	150/300		FLD A	.74-.36/.37-.18					
CONN			OHMS	555.		CL	F		
ENCL	DPFG		DUTY	CONT		MX AMB	40		
P CODE	D		CTSR			SER.F.	1.0		
S/N				E/S	K0007A A				
O.D.E. BRG.	6205	D.E. BRG.	6206	BRUSH		18044-4		QTY	2

Parts List

Part number	Description	Quantity
SA377441	SA T18S8005	1.000 ea
AA018257	AA T18S8005	1.000 ea
036170004DA	DRSCW METRIC NAMEPLATE	4.000 ea
NP1734	NPL,BALDOR DC MTR ALUMINUM	1.000 ea
ME3002A06	COMMUTATOR ISOLATOR FOR 18043 COMM	1.000 ea
032018004AK	HHCS 1/4-20X1/2 PLATED	2.000 ea
034017012AB	LCKW 1/4 STD. PLATED 034017012AF	2.000 ea
034000012AB	WSHR 1/4 STD. PLATED	2.000 ea
18006	BRUSH ROCKER ASSY FRAME 180SERIES	1.000 ea
18044-4	BRUSH, (2PC SET) GR.E41,210 SER.SGL	2.000 ea
18082-1	BRACKET 18081	1.000 ea
18032	FE BRKT MACH FR 180 STD AT	1.000 ea
032130008BA	5/16-18 X 1.0 HSHCS	4.000 ea
032130024BA	HSHCS	4.000 ea
HW5100A05	WVY WSHR F/205 & 304 BRGS	1.000 ea
15490	LIFTING LUG,180 FRAME	2.000 ea
150449-25	T BOX GRD STUD ARG 1/4 20 DIA. STUD	1.000 ea
WD4100A34	CAPLUG IN T-SERIES T12	1.000 ea
032018006DK	HHCS 1/2-13X3/4 PLATED	4.000 ea
18026	GASKET,T BOX COVER,FR.1803/32 THK CORK/N	1.000 ea
18027	GASKET,ACCESS CVR,FR.180 3/32 THK DC205(	2.000 ea
032018004AK	HHCS 1/4-20X1/2 PLATED	6.000 ea
032018004AK	HHCS 1/4-20X1/2 PLATED	6.000 ea
18034	FAN VENT GUARD-SIDE FR 18 SERIES,	2.000 ea
18033	FAN VENT GARD-BOTTOM FR 18 SERIES,	1.000 ea
18019	TERMINAL BOX COVER FRAME 180	1.000 ea
18020	BRUSH VENT COVER FR 18 SERIES #18 GA ST	1.000 ea
18020	BRUSH VENT COVER FR 18 SERIES #18 GA ST	1.000 ea
15209	LABEL CONNECTIONS & TERMINAL MARKIN	1.000 ea
15021-1	ACCESSORY FACE COVER FRAME 180-500 SERIE	1.000 ea
034180011DA	1/4 SQ X 1.375 KEY	1.000 ea

004824007BTW

SPECIAL PAINT4824-3BVZ

0.100 ea

Accessories

Part number	Description	Multiplier
90EP5000A02	C-FACE CONVERSION KIT FOR STOCK MTR,FR 1	

CUSTOMER NAME		MODEL NO.			MTG.		REMARKS:	
CUSTOMER P.O.		FRAME	R.P.M.	VOLTS	PHASE		INSUL	
CERTIFIED BY		H.P.	TYPE	ENCL	FREQ.		AMB.	

UNITS: INCH	SCALE: NONE	PROPORTION: NONE	PART NUMBER	875	DWG. SIZE A
----------------	----------------	---------------------	----------------	-----	----------------

1/2-13UNC-2B THD X .75 DEEP
4-HOLES EQ. SPACED AT 90°
ON A 7.250 DIA. B.C.

3/8-16UNC-2B THD
X .88 DEEP IN SHAFT
END.

45°

ACCESSORY MTG. FACE

STANDARD COMM END
FOR SINGLE SHAFT EXTENSION

.40
.063
.061
.700
.695 DIA.
.9846
.9841 DIA.


FRAME	FOOT MOUNTING					D.E. SHAFT EXTENSION					DRIVE KEY		ACC SHAFT EXTENSION			ACC KEY		FRAME								ARM APPROX. WK ² LBS.FT. ²	APPROXIMATE WEIGHT
	BA	E	2F	G	H	J	N	N-W	U	V	W	KEY-SQ.	KEY-LONG	FN	FU	FV	KEY-SQ.	KEY-LONG	A	B	C	FC	D	O	P		
L182AT	2.75	3.75	4.50	.38	.406	1.50	2.90	2.77	1.125	2.50 ³	.13	.250	1.38	2.28	.875	2.03	.188	1.38	8.81	5.75	15.81	17.37	4.50 ²	8.94	8.88	.28	84 ⁵
L186AT	2.75	3.75	7.00	.38	.406	1.50	2.90	2.77	1.125	2.50 ³	.13	.250	1.38	2.28	.875	2.03	.188	1.38	8.81	8.25	19.31	20.87	4.50 ²	8.94	8.88	.67	159 ⁵
L1810AT	2.75	3.75	11.00	.38	.406	1.50	2.90	2.77	1.125	2.50 ³	.13	.250	1.38	2.28	.875	2.03	.188	1.38	8.81	12.25	22.21	23.78	4.50 ²	9.00	9.00	1.0	195 ⁵

- 1) SHAFT DIAMETERS TO 1.500 TOLERANCE +.0000 - .0005
SHAFT DIAMETERS ABOVE 1.500 TOLERANCE +.0000 - .0010
SHAFT DIAMETERS TO 1.625 RUNOUT .002 T.I.R. MAX.
SHAFT DIAMETERS ABOVE 1.625 RUNOUT .003 T.I.R. MAX.
- 2) 'D' DIMENSION TOLERANCE +.000 - .030
- 3) 'V' DIMENSION IS MAX. HUB LENGTH ON SHAFT
- 4) CONDUIT BOX CAN BE ROTATED IN 90° STEPS ON ITS OWN AXIS.
- 5) TOTAL WEIGHT OF MOTOR.
- 6) ALL DIMENSIONS NOT NOTED ARE NOMINAL DIMENSIONS CONSULT FACTORY FOR TOLERANCES.

FOR F1 OR F2 CONDUIT BOX
LOCATION SEE SALES ORDER

DESIGNER CSL 7-19-91		BALDOR		TITLE: DIMENSION SHEET DPFG, STD AT	
ENGINEER RFL 7-19-91					
ENGINEER DAG 7-19-91		MANUF. RWT 7-19-91		PART NUMBER 875	
REV. ECO.		DESCRIPTION		BY DATE	

15209



NOTE:
MATERIAL .005 MINIMUM FULL HARD ALUMINUM DULL FINISH.
TEMP. RANGE -20°C TO +125°C MAXIMUM.
FOR INDOOR AND OUTDOOR MOUNTING BACK.
METAL, PRESSURE SENSITIVE BACK. MUST MEET CSA STANDARD.
THE CSA IDENTIFYING MARK OF THE LABEL MANUFACTURER MUST APPEAR IN THE UPPER RIGHT HAND CORNER AS INDICATED.

MATL: NOTED			
REV:	G	CHANGE ALL "NAMEPLATE" TEXT TO "LABEL"	
60Z91		SCALE: —	BY: BKW
		FILE: CHB00002485	REVISED: 02/19/97
		TDR: 0115147	

BALDOR ELECTRIC Co.

LABEL, CONNECTIONS AND TERMINAL MARKINGS DC

15209