

ABB BALDOR RELIANCE III

Customer information packet D2015R

15 1750 SC2113ATZ DPG 240V

Specifications

Enclosure	DP
Frame	SC2113ATZ
Frame Material	Steel
Output Power	15.000 HP
Agency Approvals	CCSA US
Ambient Temperature	40 °C
Bearing Grease Type	Polyrex EM (-20F +300F)
Drip Cover	No Drip Cover
Feedback Device	NO FEEDBACK
Field Winding Type	STAB SHUNT
Frame Prefix	SC
Heater Indicator	No Heater
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	F1
Overall Length	28.38 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Slinger Indicator	No Slinger

Part Detail

Revision	-
Type	DC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	G6067A A
Layout	609950-001
Eff. date	04-13-2015
CD Diagram	406770-001
Poles	00
Leads	
Proprietary	False
Created date	04-09-2015

Nameplate

000613006HP									
CAT.NO.	D2015R	SPEC NO.		T21S1330					
FR	SC 2113ATZ	HP	15		DUTY		CONT		
ENCL.	DP	RPM	1750/ 2300			S.F.	1.0		
ENCL MOD	GUARDED	VOLTS	240			INSUL		F	
MAX SAFE SPEED	4500	AMPS	56.00			AMB.	40		
FIELD DATA		SER.NO.							
WINDING	STAB SHUNT	POWER CODE		C					
VOLTS	150	D.E. BRG.		50BC03J30X					
MAX AMPS @ 25 C	4.12	O.D.E. BRG.		45BC02J30X					
HOT AMPS	2.85/ 1.92	MIN. AMB.		0		TYPE		TR	
BRUSH:419904051AD									

Parts List

Part number	Description	Quantity
SA297157	SA T21S1330	1.000 ea
AA016175	AA T21S1330	1.000 ea
000613006HP	NAMEPLATE - RPM III D-C MOTOR W/CSA LOGO	1.000 ea
000692000FP	NP, WARNING LIFT INSTRUCTIONS	1.000 ea
000692000FS	WARNING LABEL	1.000 ea
033775004EA	DRSCR #6-1/4 304 S.S.	6.000 ea
406770001	C/D TAG (STAB SHUNT)	1.000 ea
034182010GA	KEY 1/2 X 3/8 X 1.25"	1.000 ea
036000012HB	HHCS M6X12MM LONG PLATED	4.000 ea
036000020KB	MHHCS M10-1.5X20MM PLTD.	4.000 ea
036501008AB	KPNUT M6-1.0 ZINCPLTED	8.000 ea
036610010AB	MHSLW M10 PLATED	4.000 ea
419904-51AD	BRUSH C	4.000 ea
419905003A	FLAT WASHER ROCKER RPM III RGG	4.000 ea
419905008A	HARDWARE	8.000 ea
706364051RBA	BRHLD METRIC SPRING CHG.	4.000 ea
706372001B	ROCKR METRIC	1.000 ea
034693001AB	PPLG - G508- use 034692001AB	1.000 ea
034693001AB	PPLG - G508- use 034692001AB	1.000 ea
035000001A	ALFTG 1/8" 1610-BL	1.000 ea
035000001BB	GREASE FTG,GRS.IN	1.000 ea
036000055JB	HHCS,DE CAP	2.000 ea
036000060KB	HHCS,DE CAP	3.000 ea
036500010AB	METRIC NUT M10-1.5PLTD400	4.000 ea
036500010AB	METRIC NUT M10-1.5PLTD400	4.000 ea
406055001B	GRFTG	1.000 ea
400638001H	SPRING WASHER (Customer number 43699)	1.000 ea
418150003A	GREASE FITTING CAP	2.000 ea
609830005M	TBOLT METRIC RP609830-	4.000 ea
801924102A	BRKT,ODE,C210	1.000 ea
801925102A	BRKT,DE,C210	1.000 ea


032018004CK	HHCS 3/8-16X1/2L PLATED	4.000 ea
036000012HB	HHCS M6X12MM LONG PLATED	2.000 ea
036000045JB	M8-1.25 X 45MM HXHCS	4.000 ea
036620009AB	M8 EXTERNAL LK WASHER	1.000 ea
065564000B	GASK 250-280	1.000 ea
075453000A	CBOXC, PAINTED 250-280	1.000 ea
417733001D	GASKT	2.000 ea
418010006A	CAST,MPLATE,180-280,EX1,7BY	1.000 ea
418018074A	GROUND LABEL G100 METRIC 160 D.C.	1.000 ea
422919001	CVRKT BE SOLID C210	1.000 ea
422919003	HHCVR KIT,C210,DE,LOUVERED	1.000 ea
422919003	HHCVR KIT,C210,DE,LOUVERED	1.000 ea
422919012	HHCVR KIT,C210,ODE,SOLID	1.000 ea
422919014	HHCVR KIT,C210,ODE,LOUVERED	1.000 ea
422919014	HHCVR KIT,C210,ODE,LOUVERED	1.000 ea
706305026A	GUARD,SHAFT	1.000 ea
706320005A	CONDUIT BOX	1.000 ea
000640000P	TAG WINDING THERMOST	1.000 ea
000692000NG	LABEL ;NP 4POLE METRIC LABEL	1.000 ea
034180020GA	KEY 1/2X1/2X2-1/2 L	1.000 ea

609950-001

INDUSTRIAL DIRECT CURRENT MOTORS
AND GENERATORS - RPM III

ENCLOSURE: DRIP-PROOF FULLY-GUARDED, COOLING: SELF-VENTILATED
SPLASHPROOF, TOTALLY ENCLOSED NON-VENTILATED
MOUNTING: FOOT ACCESSORIES: PROVISION FOR
METHOD OF DRIVE: COUPLED OR BELTED TACHOMETER MOUNTING
ONLY WHEN SPECIFIED

FRAMES SC2113ATZ THRU LC2812ATZ



DIMENSIONS ARE IN INCHES; SEE 609950-1M FOR DIMENSIONS IN MILLIMETERS

FRAME	A	X(1)	E	G	H	HG	J	D	P	T	BA	K	FK	BK
SC2113ATZ-LC2113ATZ	10.25	5.25	4.25	44	44	1.38	1.75	10.44	10.31	2.56	3.50	5.19	6.81	2.38
SC2512ATZ-LC2512ATZ	12.31	6.25	5.00	50	56	1.62	2.00	12.50	12.44	3.06	4.25	6.06	8.00	3.00
MC2812ATZ-LC2812ATZ	13.78	7.00	5.50	62	56	1.88	2.75	14.00	13.94	3.38	4.75	6.75	9.19	3.50

FRAME	D(7)	B	BS	2F	N	N-W	UK(2)	V	R(3)	SQ	LGTH.	FN	FN-FW	FK(2)	FV	FR(3)	SV	LGTH.	WT.
SC2113ATZ	28.38	22.50	11.38	18.00	4.00	3.75	1.875	3.50	1.591	.500	2.50	3.50	3.25	1.625	3.00	1.416	.375	2.25	315
LC2113ATZ	29.62	23.75	12.62	18.00	4.00	3.75	1.875	3.50	1.591	.500	2.50	3.50	3.25	1.625	3.00	1.416	.375	2.25	340
SC2512ATZ	31.69	25.06	13.56	20.00	4.50	4.25	2.125	4.00	1.845	.500	3.00	4.00	3.75	1.875	3.50	1.591	.500	2.50	505
MC2512ATZ	33.19	26.56	15.06	20.00	4.50	4.25	2.125	4.00	1.845	.500	3.00	4.00	3.75	1.875	3.50	1.591	.500	2.50	540
LC2512ATZ	34.69	28.06	16.56	20.00	5.00	4.75	2.375	4.50	2.021	.625	3.50	4.50	4.25	2.125	4.00	1.845	.500	3.00	775
MC2812ATZ	37.38	29.94	18.45	22.00	5.00	4.75	2.375	4.50	2.021	.625	3.50	4.50	4.25	2.125	4.00	1.845	.500	3.00	850

- (1) "D" DIMENSION WILL NOT BE EXCEEDED. SHIMS UP TO .03 INCHES IN THICKNESS ARE USUALLY REQUIRED FOR COUPLED OR GEARED MACHINES.
(2) "U" AND "FV" VARY-----+ .000 - .005
(3) "R" AND "FR" VARY-----+ .000 - .015
(4) TERMINAL BOX VARIES WITH H.P. FOR DIMENSIONS "AA", "AB", "AC", "AF", "X" AND "Y". REFER TO BOX D/S. (STD. 609959-1, "X/P" 609959-2, MILL. 609959-3)
(5) OPPOSITE DRIVE END SHFT SUPPLIED ONLY WHEN SPECIFIED.
(6) MOTOR SHFT TAPPED FOR 3/8"-16 IN STUB SHFT.
(7) WHEN THE MOTOR APPLICATION DOES NOT REQUIRE THE USE OF DFP, DRIVE END, ADD .25 TO "C" DIM FOR BRACKET COVER.
TERMINAL BOX CAN BE ROTATED FOR LEAD OUTLET AT TOP, SIDES OR BOTTOM. TERMINAL BOX LOCATED ON OPPOSITE SIDE WHEN F-2, V-1, V-4, V-5, W-7, OR C-1 MOUNTING IS SPECIFIED. BOX LOCATED ON TOP WHEN SPECIFIED. MOTOR WEIGHT MAY VARY 15% FOR NON-STANDARD RATINGS AND/OR ACCESSORIES. IF MOUNTING CLEARANCE DETAILS ARE REQUIRED, CONSULT FACTORY.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: LOADED TO BUS	VERSION: 00	TDR: 000000577407
REV. LTR: -	REVISED: 10:21:19 01/26/2011	BY: RGGBG
FILE: \RGG\00015\543		
MTL: -		


BALDOR
DIMENSION DRAWING, SC2113ATZ - LC2812ATZ, DPP, TENV, FOOT MTG
SH 1 of 1

609950-001

609959-001

INDUSTRIAL DIRECT CURRENT MOTORS
AND GENERATORS - RPM III
TERMINAL BOX DIMENSIONS
STANDARD SIZE AND ONE SIZE LARGER
FRAMES C2113ATZ THRU C2815ATZ

DIMENSIONS ARE IN INCHES



FRAME SIZE	MAX. AMPS	STANDARD SIZE						STEEL TERMINAL BOX DIMENSIONS						ONE SIZE LARGER						PART NUMBER		
		AA(1)	AB	AC	AF	X	Y	PART NUMBER	AA(1)	AB	AC	AF	X	Y	PART NUMBER							
C2113ATZ	40	3/4 & 1"	8.97	7.47	1.94	4.38	5.00	705028-1-R	1-1/4 & 1-1/2	10.03	8.03	2.50	5.50	6.12	705029-1-R	1-1/4 & 1-1/2	10.03	8.03	2.50	5.50	6.12	705029-1-R
C2115ATZ	96	1-1/4 & 1-1/2	10.03	8.03	2.50	5.50	6.12	705029-1-R	2" & 2-1/2	11.16	8.41	3.19	7.00	7.62	705030-1-R	2" & 2-1/2	11.16	8.41	3.19	7.00	7.62	705030-1-R
(2)	208	2" & 2-1/2	11.16	8.41	3.19	7.00	7.62	705030-1-R	2" & 2-1/2	11.16	8.41	3.19	7.00	7.62	705030-1-R	2" & 2-1/2	11.16	8.41	3.19	7.00	7.62	705030-1-R
C2516ATZ	40	3/4 & 1"	10.03	8.53	1.94	4.38	5.00	705028-1-R	1-1/4 & 1-1/2	11.09	9.09	2.50	5.50	6.12	705029-1-R	1-1/4 & 1-1/2	11.09	9.09	2.50	5.50	6.12	705029-1-R
C2514ATZ	96	1-1/4 & 1-1/2	11.09	9.09	2.50	5.50	6.12	705029-1-R	2" & 2-1/2	12.22	9.47	3.19	7.00	7.62	705030-1-R	2" & 2-1/2	12.22	9.47	3.19	7.00	7.62	705030-1-R
(2)	208	2" & 2-1/2	12.22	9.47	3.19	7.00	7.62	705030-1-R	2" & 2-1/2	12.22	9.47	3.19	7.00	7.62	705030-1-R	2" & 2-1/2	12.22	9.47	3.19	7.00	7.62	705030-1-R
C2816ATZ	128	2"	14.03	10.53	4.25	8.44	7.25	74874-R	3"	14.47	11.22	4.25	8.44	7.25	74874-R	3"	14.47	11.22	4.25	8.44	7.25	74874-R
C2815ATZ	195	3"	14.47	11.22	4.25	8.44	7.25	74874-R	4"	15.91	11.84	5.38	10.56	9.00	706308-3-R	4"	15.91	11.84	5.38	10.56	9.00	706308-3-R
(2)	269	4"	15.91	11.84	5.38	10.56	9.00	706308-3-R	5" (4)	18.72	13.47	7.00	12.75	15.00	706589-1-C	5" (4)	18.72	13.47	7.00	12.75	15.00	706589-1-C

CAST IRON TERMINAL BOX DIMENSIONS															
FRAME SIZE	MAX. AMPS	STANDARD SIZE						ONE SIZE LARGER							
		AB	AC	AF	X	Y	NUMBER	AB	AC	AF	X	Y	NUMBER		
C2113ATZ	18	3/4	10.03	8.03	2.50	5.00	5.75	705028-2-S	1"	10.03	8.03	2.50	5.00	5.75	705028-2-T
C2113ATZ	40	1"	10.03	8.03	2.50	5.00	5.75	705028-2-T	1-1/2	10.97	8.53	3.00	6.00	7.00	705029-2-R
C2115ATZ	96	1-1/2	10.97	8.53	3.00	6.00	7.00	705029-2-R	2"	10.97	8.53	3.00	6.00	7.00	705029-2-S
C2516ATZ	208	2"	10.97	8.53	3.00	6.00	7.00	705029-2-S	2-1/2	12.66	8.91	3.62	7.88	9.25	705030-2-R
C2516ATZ	18	3/4	11.09	9.09	2.50	5.00	5.75	705028-2-S	1"	11.09	9.09	2.50	5.00	5.75	705028-2-T
C2516ATZ	40	1"	11.09	9.09	2.50	5.00	5.75	705028-2-T	1-1/2	12.03	9.59	3.00	6.00	7.00	705029-2-R
C2514ATZ	96	1-1/2	12.03	9.59	3.00	6.00	7.00	705029-2-R	2"	12.03	9.59	3.00	6.00	7.00	705029-2-S
C2515ATZ	208	2"	12.03	9.59	3.00	6.00	7.00	705029-2-S	2-1/2	13.72	9.97	3.62	7.88	9.25	705030-2-R
C2816ATZ	128	2"	12.78	10.34	3.00	6.00	7.00	75460-T	3"	14.47	10.72	3.62	7.88	9.25	76700-R
C2816ATZ	195	3"	14.47	10.72	3.62	7.88	9.25	76700-R	4"	15.78	11.59	4.12	9.50	10.50	76700-R
C2815ATZ	269	4"	15.78	11.59	4.12	9.50	10.50	76700-R	5" (4)	18.59	13.34	7.00	12.75	15.00	76870-S

CONDUIT BOX DIMENSIONS WITH TERMINAL BOARDS (IEC TYPE BOX)

CONDUIT: RUA DIMENSIONS WITH TOLERANCE, DIMENSIONS (INCH, LIFT, DIA.)												
STANDARD SIZE												
FRAME SIZE	AMPS	AB	AC	AF	X	AA	Y	PART NUMBER		PART NUMBER		
C210	100	10.71	8.98	2.72	7.48	---	7.48	706310-56-A		706310-225-R		
	200	11.66	9.25	3.35	8.82	---	8.82	706310-56-B		706310-225-R		
	100	11.30	9.57	2.72	7.48	---	7.48	706310-56-A		706310-225-R		
	200	11.85	9.84	3.35	8.82	---	8.82	706310-56-B		706310-225-R		
C250	400	17.48	12.75	6.20	14.39	---	14.39	706310-63-B & 706310-63G		706310-63-B & 706310-63G		
	800	17.48	12.75	6.20	14.39	---	14.39	706310-63-B & 706310-63G		706310-63-B & 706310-63G		
	200	12.60	10.59	3.76	8.82	---	8.82	706310-56-B		706310-225-R		
	400	18.27	13.54	6.20	14.39	---	14.39	706310-63-B & 706310-63G		706310-63-B & 706310-63G		
C280	800	18.27	13.54	6.20	14.39	---	14.39	706310-63-B & 706310-63G		706310-63-B & 706310-63G		
	1600	18.27	13.54	7.68	15.35	---	15.35	706310-63-C		706310-63-C		

OPTIONAL AUXILIARY CONDUIT BOX DIMENSIONS (MAXIMUM)

FRAME SIZE	XAB	XY	PART NUMBER	FRAME SIZE	XAB	XY	PART NUMBER
C210	7.38	4.25	602007-26-A	C210	10.88	8.00	706310-3-B
C250	8.44	4.25	602007-26-A	C250	11.88	8.00	706310-3-B
C280	9.12	4.25	602007-26-A	C280	12.62	8.00	706310-3-B

(1) 1/4" CONDUIT.
(2) RACES PROVIDED WITH DOUBLE KNUCKLE.
(3) 1/4" PIPE LAP.(4) TERMINAL BOX 76870-S AND 76870-98 EXTENDS BELOW MOTOR FEET.
TERMINAL BOX 76870-S AND 76870-98 EXTENDS BELOW MOTOR FEET.
DR - C-1 MOUNTING IS SPECIFIED. BOX LOCATED ON TOP WHEN SPECIFIED.
FOR "X"/"Y" TERMINAL BOX DIMENSIONS SEE 609959-2.
FOR MILL TYPE TERMINAL BOX DIMENSIONS SEE 609959-3.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: ADD 706310-63G C/BOX TO C250 AND C280 FRAMES

REV. LTR: A

VERSION: 01

TDR: 000000816512

FILE: \RGG\00021\153

REVISED: 03: 09: 09 09/06/2013

MTL: -

BY: RGGWT

BALDOR

DIMENSION SHEET

SH 1 of 1

609959-001

