

ABB BALDOR RELIANCE III

Customer information packet

D2015R-BV

15HP, 1750RPM, DC, 2113ATZ, DPG-FV,

Specifications

Enclosure	DP
Frame	SC2113ATZ
Frame Material	Steel
Output Power	15.000 HP
Agency Approvals	CCSA US
Ambient Temperature	40 °C
Bearing Grease Type	Polyrex EM (-20F +300F)
Drip Cover	No Drip Cover
Feedback Device	NO FEEDBACK
Field Winding Type	STR SHUNT
Frame Prefix	SC
Heater Indicator	No Heater
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	F1
Overall Length	28.38 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Slinger Indicator	No Slinger

Part Detail

Revision	-
Type	DC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	G6207C B
Layout	616002-001
Eff. date	04-13-2015
CD Diagram	406770-006
Poles	00
Leads	
Proprietary	False
Created date	04-09-2015

Nameplate


000613006HP									
CAT.NO.		SPEC NO.	T21T1359						
FR	SC 2113ATZ	HP	15	DUTY		CONT			
ENCL.	DP	RPM	1750/ 2300		S.F.	1.0			
ENCL MOD	FORCE VENT	VOLTS	240		INSUL		F		
MAX SAFE SPEED	4500	AMPS	56.00		AMB.		40		
FIELD DATA		SER.NO.							
WINDING	STR SHUNT	POWER CODE	D						
VOLTS	150	D.E. BRG.	50BC03J30X						
MAX AMPS @ 25 C	4.73	O.D.E. BRG.	45BC02J30X						
HOT AMPS	3.41/ 2.24	MIN. AMB.	0		TYPE		TR		
BRUSH:419904051AD									

Parts List

Part number	Description	Quantity
SA297129	SA T21T1359	1.000 ea
AA016161	AA T21T1359	1.000 ea
000613006HP	NAMEPLATE - RPM III D-C MOTOR W/CSA LOGO	1.000 ea
000692000FP	NP, WARNING LIFT INSTRUCTIONS	1.000 ea
000692000FS	WARNING LABEL	1.000 ea
033775004EA	DRSCR #6-1/4 304 S.S.	6.000 ea
406770006	C/D TAG STRAIGHT SHUNT	1.000 ea
036000012HB	HHCS M6X12MM LONG PLATED	4.000 ea
036000020KB	MHHCS M10-1.5X20MM PLTD.	4.000 ea
036501008AB	KPNUT M6-1.0 ZINCPLTED	8.000 ea
036610010AB	MHSLW M10 PLATED	4.000 ea
419904-51AD	BRUSH C	4.000 ea
419905003A	FLAT WASHER ROCKER RPM III RGG	4.000 ea
419905008A	HARDWARE	8.000 ea
706364051RBA	BRHLD METRIC SPRING CHG.	4.000 ea
706372001B	ROCKR METRIC	1.000 ea
034693001AB	PPLG - G508- use 034692001AB	1.000 ea
034693001AB	PPLG - G508- use 034692001AB	1.000 ea
035000001A	ALFTG 1/8" 1610-BL	1.000 ea
035000001BB	GREASE FTG,GRS.IN	1.000 ea
036000055JB	HHCS,DE CAP	2.000 ea
036000060KB	HHCS,DE CAP	3.000 ea
036500010AB	METRIC NUT M10-1.5PLTD400	4.000 ea
036500010AB	METRIC NUT M10-1.5PLTD400	4.000 ea
406055001B	GRFTG	1.000 ea
400638001H	SPRING WASHER (Customer number 43699)	1.000 ea
418150003A	GREASE FITTING CAP	2.000 ea
609830005M	TBOLT METRIC RP609830-	4.000 ea
801924102A	BRKT,ODE,C210	1.000 ea
801925102A	BRKT,DE,C210	1.000 ea
000613006NT	NAME PLATE IEC	1.000 ea

032018004CK	HHCS 3/8-16X1/2L PLATED	4.000 ea
032018006CK	HHCS 3/8-16X3/4L PLATED 411409	4.000 ea
034017014AB	LCKW 3/8 STD. PLATED	4.000 ea
036000012HB	HHCS M6X12MM LONG PLATED	2.000 ea
036000012JB	M8-1.25 X 12MM HXHDC	3.000 ea
036000020JB	HHCS M8-1.25X20L PLTD-250	4.000 ea
036000045JB	M8-1.25 X 45MM HXHCS	4.000 ea
036600009AB	METRIC FLWASH M8 PLATED	3.000 ea
036620009AB	M8 EXTERNAL LK WASHER	1.000 ea
065564000B	GASK 250-280	1.000 ea
075453000A	CBOXC, PAINTED 250-280	1.000 ea
410978010C	FLANGE, INLET BLOWER HSG.	1.000 ea
410978019A	SCREEN, INLET FLANGE	1.000 ea
417733001D	GASKT	2.000 ea
418010006A	CAST,MPLATE,180-280,EX1,7BY	1.000 ea
418018074A	GROUND LABEL G100 METRIC 160 D.C.	1.000 ea
422919001	CVRKT BE SOLID C210	1.000 ea
422919003	HHCVR KIT,C210,DE,LOUVERED	1.000 ea
422919003	HHCVR KIT,C210,DE,LOUVERED	1.000 ea
422919012	HHCVR KIT,C210,ODE,SOLID	1.000 ea
422919012	HHCVR KIT,C210,ODE,SOLID	1.000 ea
422919012	HHCVR KIT,C210,ODE,SOLID	1.000 ea
610490001AH	.75HP,3450//2850RPM,3PH,60//50HZ,56C,351	1.000 ea
611917002A	GASKT	1.000 ea
611965001A	WHEEL, BLOWER	1.000 ea
706305026A	GUARD,SHAFT	1.000 ea
706320005A	CONDUIT BOX	1.000 ea
708528004G	HOUSING, BLOWER	1.000 ea
000640000P	TAG WINDING THERMOST	1.000 ea
000692000NG	LABEL ;NP 4POLE METRIC LABEL	1.000 ea
034180020GA	KEY 1/2X1/2X2-1/2 L	1.000 ea
418018116	WARNING PLATE	1.000 ea

ACCESSORIES: PROVISION FOR
TACHOMETER MOUNTING
ONLY WHEN SPECIFIED




CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. LTR: -	VERSION: 00	TDR: 000000578087
FILE: \RGG\00015\944	REVISED: 08:22:49 01/28/2011	BY: CONNAS
MTL: -		

BALDOR
 DIMENSION DRAWING,SC2113ATZ - LC2115ATZ,DPP,FOOT MTG
 SH 1 of 1

609959-001

INDUSTRIAL DIRECT CURRENT MOTORS
AND GENERATORS - RPM III
TERMINAL BOX DIMENSIONS
STANDARD SIZE AND ONE SIZE LARGER
FRAMES C2113ATZ THRU C2815ATZ

DIMENSIONS ARE IN INCHES

STEEL TERMINAL BOX DIMENSIONS															
FRAME SIZE	MAX. AMPS	STANDARD SIZE					ONE SIZE LARGER					PART NUMBER			
		AA(1)	AB	AC	AF	Y	AA(1)	AB	AC	AF	Y				
C2113ATZ	40	3/4 & 1"	8.97	7.47	1.94	4.38	5.00	7.05028-1-R	1-1/4 & 1-1/2	10.03	8.03	2.50	5.50	6.12	7.05029-1-R
C2115ATZ	96	1-1/4 & 1-1/2	10.03	8.03	2.50	5.50	6.12	7.05029-1-R	2" & 2-1/2	11.16	8.41	3.19	7.00	7.62	7.05030-1-R
(2)	208	2" & 2-1/2	11.16	8.41	3.19	7.00	7.62	7.05028-1-R	2" & 2-1/2	11.16	8.41	3.19	7.00	7.62	7.05030-1-R
C2514ATZ	40	3/4 & 1"	10.03	8.53	1.94	4.38	5.00	7.05028-1-R	1-1/4 & 1-1/2	11.09	9.09	2.50	5.50	6.12	7.05029-1-R
C2514ATZ	96	1-1/4 & 1-1/2	11.09	9.09	2.50	5.50	6.12	7.05029-1-R	2" & 2-1/2	12.22	9.47	3.19	7.00	7.62	7.05030-1-R
(2)	208	2" & 2-1/2	12.22	9.47	3.19	7.00	7.62	7.05030-1-R	2" & 2-1/2	12.22	9.47	3.19	7.00	7.62	7.05030-1-R
C2815ATZ	188	2"	14.03	10.53	4.23	8.44	7.23	7.05030-1-R	2"	14.47	11.22	4.23	8.44	7.23	7.05030-1-R
C2815ATZ	188	3"	14.47	11.22	4.23	8.44	7.23	7.05030-1-R	3"	15.91	11.84	5.38	10.56	9.00	7.05030-3-R
(2)	269	4"	15.91	11.84	5.38	10.56	9.00	7.05030-3-R	5" (4)	18.72	13.47	7.00	12.73	15.00	7.06550-1-C

CAST IRON TERMINAL BOX DIMENSIONS															
FRAME SIZE	MAX. AMPS	STANDARD SIZE					ONE SIZE LARGER								
		AK(3)	AB	AC	AF	X	Y	NUMBER	AK(3)	AB	AC	AF	X	Y	NUMBER
C2113ATZ	18	3/4	10.03	8.03	2.50	5.00	5.75	7.05028-2-S	1"	10.03	8.03	2.50	5.00	5.75	7.05028-2-R
C2115ATZ	40	1"	10.03	8.03	2.50	5.00	5.75	7.05028-2-T	1-1/2	10.97	8.53	3.00	6.00	7.00	7.05029-2-R
C25115ATZ	96	1-1/2	10.97	8.53	3.00	6.00	7.00	7.05029-2-S	2"	10.97	8.53	3.00	6.00	7.00	7.05029-2-R
C2512ATZ	18	3/4	11.09	9.09	2.50	5.00	5.75	7.05028-2-S	1"	11.09	9.09	2.50	5.00	5.75	7.05028-2-T
C2514ATZ	40	1"	11.09	9.09	2.50	5.00	5.75	7.05028-2-T	1-1/2	12.03	9.59	3.00	6.00	7.00	7.05029-2-R
C2514ATZ	96	1-1/2	12.03	9.59	3.00	6.00	7.00	7.05029-2-S	2"	12.03	9.59	3.00	6.00	7.00	7.05029-2-R
C2813ATZ	188	2"	12.03	9.59	3.00	6.00	7.00	7.05029-2-S	2-1/2	13.72	9.97	3.62	7.88	9.25	7.05030-2-R
C2813ATZ	188	3"	12.78	10.34	3.62	7.88	9.25	7.05030-2-R	3"	14.47	10.72	3.62	7.88	9.25	7.05030-2-R
C2815ATZ	269	4"	14.47	10.72	3.62	7.88	9.25	7.05030-2-R	5" (4)	15.78	11.59	4.12	9.50	10.50	7.05030-2-R

CONDUIT BOX DIMENSIONS WITH TERMINAL BOARDS (IEC TYPE BOX)

STANDARD SIZE									
FRAME SIZE	AMPS	AB	AC	AF	X	AA	Y	PART NUMBER	PART NUMBER
C210	100	10.71	8.98	2.72	7.48	---	7.48	706310-56-A	706310-225-R
	200	11.66	9.23	3.33	8.82	---	8.82	706310-56-B	706310-225-R
	100	11.30	9.57	2.72	7.48	---	7.48	706310-56-A	706310-225-R
C250	200	11.85	9.84	3.35	8.82	---	8.82	706310-56-B	706310-225-R
	400	17.48	12.75	6.20	14.39	---	14.39	706310-63-B & 706310-63G	706310-63-B & 706310-63G
	800	17.48	12.75	6.20	14.39	---	14.39	706310-63-B & 706310-63G	706310-63-B & 706310-63G
C280	200	12.60	10.59	3.76	8.82	---	8.82	706310-56-B	706310-225-R
	400	18.27	13.54	6.20	14.39	---	14.39	706310-63-B & 706310-63G	706310-63-B & 706310-63G
	800	18.27	13.54	6.20	14.39	---	14.39	706310-63-B & 706310-63G	706310-63-B & 706310-63G
	1600	18.27	13.54	7.68	15.35	---	15.35	706310-63-C	706310-63-C

OPTIONAL AUXILIARY CONDUIT BOX DIMENSIONS (MAXIMUM)										
FRAME SIZE	XAB	XY	PART NUMBER	FRAME SIZE	XAB	XY	PART NUMBER	FRAME SIZE	PART NUMBER	
C210	7.38	4.25	6.02007-26-A	C210	10.88	8.00	7.06310-3-B	C250	11.88	8.00
C250	8.44	4.25	6.02007-26-A	C250	11.88	8.00	7.06310-3-B	C280	12.62	8.00
C280	9.12	4.25	6.02007-26-A	C280	12.62	8.00	7.06310-3-B			

(1) 1/4" CONDUIT.
(2) RACEWAYS PROVIDED WITH DOUBLE KNUCKLE.
(3) 1/4" PIPE LAP.(4) TERMINAL BOX 76870-S AND 76870-98 EXTENDS BELOW MOTOR FEET.
TERMINAL BOX 76870-S AND 76870-98 EXTENDS BELOW MOTOR FEET.
DR - C-1 MOUNTING IS SPECIFIED. BOX LOCATED IN TOP WHEN SPECIFIED.
FOR "X"/P/TERMINAL BOX DIMENSIONS SEE 609959-2.
FOR MILL TYPE TERMINAL BOX DIMENSIONS SEE 609959-3.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: ADD 706310-63G C/BOX TO C250 AND C280 FRAMES	VERSION: 01	TDR: 000000816512
REV. LTR: A		
FILE: \RGG\00021\153		REVISED: 03: 09: 09 09/06/2013
MTL: -		BY: RGGWT

BALDOR

DIMENSION SHEET

SH 1 of 1

609959-001

406770-006			406770-006	
CONNECTION DIAGRAM D-C MOTOR - STRAIGHT SHUNT W1 <NOTE 6> H1 H2 SHUNT FIELD INTER-COIL ARMATURE F1 A1 A2 F2 <NOTE 3> <CAUTION-SEE NOTE 1> P1 P2 <NOTE 4> TD1 TD2 TD3 TD <NOTE 5> THREE WIRE RTD ARMATURE AND FIELD EXTERNAL CONNECTIONS WARNING- SEE NOTE 7 FOR GROUNDING INSTRUCTIONS A1 A2 F1 F2 - + - - CCW ROTATION ROTATION FACING COMMUTATOR END A1 A2 F1 F2 - + + - CW ROTATION 1. CAUTION — ARMATURE MAY HAVE MULTIPLE LEADS. CONNECT ALL LUGS WITH THE SAME MARKING TOGETHER. 2. OPTIONAL CONTROL SIGNAL LEAD IS MARKED AX2. ALWAYS TAKE INTERPOLE DROP BETWEEN A2 AND AX2. NOTE: NEMA DESIGNATION FOR AX2 IS LETTER C. 3. SPACE HEATERS, WHEN PROVIDED, WILL HAVE LEADS MARKED H1 AND H2, H3, H4, ETC. 4. THERMAL PROTECTOR, WHEN PROVIDED, WILL HAVE LEADS MARKED P1 AND P2, P3, P4, ETC. 5. WINDING RTD'S, WHEN PROVIDED, WILL HAVE LEADS MARKED TD1, TD2, & TD3. 6. BRUSH WEAR SENSOR, WHEN PROVIDED, WILL HAVE LEAD MARKED W1. 7. WARNING — MOTOR MUST BE GROUNDED TO PREVENT SERIOUS INJURIES TO PERSONNEL. GROUND THE MOTOR PER IEC, NATIONAL ELECTRICAL CODE AND ANY APPLICABLE LOCAL ELECTRICAL CODES. A TAPPED HOLE IS PROVIDED IN THE CONDUIT BOX, ON THE FOOT. FRAME BRACE OR OPPOSITE OPPOSITE DRIVE END BRACKET, ADJACENT TO THE TERMINAL BOX FOR MOTOR GROUNDING. GROUND LEAD, WHEN PROVIDED, WILL BE GREEN. CUSTOMER _____ CUSTOMER ORDER NO. _____ RELIANCE S.D. NO. _____				
REV. DESC: UPDATE LOGO AND TITLEBLOCK: LOADED TO BUS		BALDOR D-C MOTOR CONNECTION DIAGRAM, STRAIGHT SHUNT SH 1 of 1		
REV. LTR: -	VERSION: 00	TDR: 000000781086		
FILE: \RSN\00026\515		REVISED: 02: 41:08 02/01/2013		
MTL: -		BY: MGHPC		