

ABB BALDOR RELIANCE III

Customer information packet

D50200RR-BV

200HP, 1750RPM, DC, 3214ATZ, DPG-FV,

Specifications

Enclosure	DP
Frame	UC3214ATZ
Frame Material	Steel
Output Power	200.000 HP
Agency Approvals	CCSA US
Ambient Temperature	40 °C
Bearing Grease Type	Polyrex EM (-20F +300F)
Drip Cover	No Drip Cover
Feedback Device	NO FEEDBACK
Field Winding Type	STR. SHUNT
Frame Prefix	UC
Heater Indicator	No Heater
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	F2
Overall Length	46.75 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Slinger Indicator	No Slinger

Part Detail

Revision	A
Type	DC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	G8032B F
Layout	616032-001
Eff. date	06-28-2021
CD Diagram	406770-006
Poles	00
Leads	
Proprietary	False
Created date	04-09-2015

Nameplate

000613006HP									
CAT.NO.	D50200RR-BV	SPEC NO.	T32T1322						
FR	UC 3214ATZ	HP	200		DUTY	CONT			
ENCL.	DP	RPM	1750/2100			S.F.	1.0		
ENCL MOD	FORCE VENT	VOLTS	500			INSUL	F		
MAX SAFE SPEED	03600	AMPS	322.00			AMB.	40		
FIELD DATA		SER.NO.							
WINDING	STR. SHUNT	POWER CODE	C						
VOLTS	300	D.E. BRG.	85RU02M30X						
MAX AMPS @ 25 C	8.37	O.D.E. BRG.	65BC02J30X						
HOT AMPS	5.88/4.75	MIN. AMB.	0			TYPE	TR		
	BRUSH:419904052AF								

Parts List

Part number	Description	Quantity
SA297029	SA T32T1322	1.000 ea
AA016080	AA T32T1322	1.000 ea
000613006HP	NAMEPLATE - RPM III D-C MOTOR W/CSA LOGO	1.000 ea
000692000FP	NP, WARNING LIFT INSTRUCTIONS	1.000 ea
000692000FS	WARNING LABEL	1.000 ea
033775004EA	DRSCR #6-1/4 304 S.S.	8.000 ea
406770006	C/D TAG STRAIGHT SHUNT	1.000 ea
036000014JB	M8 X 1.25X14MM HXHDCS	4.000 ea
036000020KB	MHHCS M10-1.5X20MM PLTD.	4.000 ea
036501009AB	M8-1.25 X 9MM HEX NUTS	8.000 ea
036600009AB	METRIC FLWASH M8 PLATED	4.000 ea
036610010AB	MHSLW M10 PLATED	4.000 ea
419904-52AF	BRUSH EXTRUDER DUTY	8.000 ea
419905003A	FLAT WASHER ROCKER RPM III RGG	4.000 ea
419905004A	HARDWARE	8.000 ea
706364052E	BRHLD METRIC SPRING CHG.	4.000 ea
706372012RA	ROCKR METRIC	1.000 ea
034693001AB	PPLG - G508- use 034692001AB	1.000 ea
034693001AB	PPLG - G508- use 034692001AB	1.000 ea
035000001A	ALFTG 1/8" 1610-BL	1.000 ea
035000001BB	GREASE FTG,GRS.IN	1.000 ea
036000060KB	HHCS,DE CAP	3.000 ea
036100060JA	M8-1.25 X 60MM HXSOCHDCS	3.000 ea
036500013AB	M16 X 2.0 HX NUT,ODE BRKT 304589	4.000 ea
036500013AB	M16 X 2.0 HX NUT,ODE BRKT 304589	4.000 ea
418150003A	GREASE FITTING CAP	2.000 ea
609830005AAZ	TBOLT METRIC	4.000 ea
801930102A	BRKT,ODE,C320	1.000 ea
801931102B	BRKT,DE,C320	1.000 ea
004824015A	GREASE POLYREX EM	0.400 lb
000613006NT	NAME PLATE IEC	1.000 ea

036000016KB	HHCSM10-1.5X16MM PLTD-280	2.000 ea
032018004CK	HHCS 3/8-16X1/2L PLATED	4.000 ea
032018006CK	HHCS 3/8-16X3/4L PLATED 411409	4.000 ea
034017014AB	LCKW 3/8 STD. PLATED	4.000 ea
036000012JB	M8-1.25 X 12MM HXHDC	3.000 ea
036000020JB	HHCS M8-1.25X20L PLTD-250	6.000 ea
036010020HB	SEMS SCR,BRHLDR	8.000 ea
036000025KB	HHCS,BRACE C/BOX M10X25 HXHDCS 304528	4.000 ea
036100035JA	M8-1.25 X 35MM HXSOCHDCS	4.000 ea
036600009AB	METRIC FLWASH M8 PLATED	3.000 ea
418018074A	GROUND LABEL G100 METRIC 160 D.C.	3.000 ea
036620009AB	M8 EXTERNAL LK WASHER	1.000 ea
036620010AB	M10 EXT. TOOTH LK WASHER	2.000 ea
410978010E	INLET FLGE	1.000 ea
410978019A	SCREEN, INLET FLANGE	1.000 ea
417733004F	GASKT	1.000 ea
418014011A	ADAPT 603582011C	1.000 ea
418153001A	GASK 440	1.000 ea
422919079	HHCVR KIT, C320, DE, SOLID	1.000 ea
422919081	HHCVR KIT, C320, DE, LOUVER	1.000 ea
422919081	HHCVR KIT, C320, DE, LOUVER	1.000 ea
422919090	HHCVR KIT,C320,ODE,SOLID	1.000 ea
422919090	HHCVR KIT,C320,ODE,SOLID	1.000 ea
603529001L	GASKT	1.000 ea
610490001DG	2HP,3450//2890RPM,3PH,60//50HZ,56C,3532M	1.000 ea
415000103F	TLUG	1.000 ea
611917002G	GASKT	1.000 ea
611965001A	WHEEL, BLOWER	1.000 ea
702658001C	CONDUIT BOX, STEEL, E440 5" LEAD OUTLET	1.000 ea
702658002A	+C/BOX CVR, PAINTED 440	1.000 ea
706305026A	GUARD,SHAFT	1.000 ea
708528004E	BLOWER HOUSING	1.000 ea
000640000P	TAG WINDING THERMOST	1.000 ea
000692000NG	LABEL ;NP 4POLE METRIC LABEL	1.000 ea

032018024DK	HHCS 1/2-13X3L PLATED	1.000 ea
034001016AB	WSHR .562ID 1.375OD .109	1.000 ea
004824007K	SPECIAL PAINT	0.200 ea
034180034JA	KEY 3/4X3/4X4-1/4 L	1.000 ea
418018116	WARNING PLATE	1.000 ea

616032-001


INDUSTRIAL DIRECT CURRENT MOTORS
AND GENERATORS - RPM III

ENCLOSURE: DRIP-PROOF FULLY-GUARDED
SPLASHPROOF
MOUNTING: FOOT

COOLING: FORCE VENTILATED
WITH INTEGRAL
BLOWER AND MOTOR

ACCESSORIES: PROVISION FOR
TACHOMETER MOUNTING
ONLY WHEN SPECIFIED

FRAMES SC3210ATZ THRU ULC3214ATZ



DIMENSIONS ARE IN INCHES

FRAME	XAC	XC	XE	XF	XO
SC3210ATZ-ULC3214ATZ	6.75	3.25	8.50	19.25	28.00

FRAME	A	D(1)	E	G	H	HG	J	O	P	T	BA	K	FK	STD.	LG.(8)	BK
SC3210ATZ-ULC3214ATZ	15.50	8.00	6.25	.75	.69	2.25	3.00	15.81	15.62	3.54	5.25	6.75	7.94	10.44	4.00	

FRAME	METHOD OF DRIVE	C(7)				BS	2F	DRIVE END SHAFT AND KEY				OPPOSITE DRIVE END SHAFT AND KEY				WT.						
		STD.	LG.(8)	STD.	LG.(8)			N	N-W	U(2)	V	R(3)	ISO	LGTH.	FN		FN-FW	FU(2)	FV	FR(3)	ISO	LGTH.
SC3210ATZ-ULC3210ATZ	COUPLED	36.25	38.75	28.31	30.81	13.38	20.00	5.50	5.25	2.625	5.00	2.275	.625	4.00	4.75	4.50	2.250	4.25	1.972	5.00	3.25	1115
USC3210ATZ-ULC3210ATZ	BELTED	36.75	39.25	28.31	30.81	13.38	20.00	6.00	5.75	2.875	5.50	2.450	.750	4.25	4.75	4.50	2.250	4.25	1.972	5.00	3.25	1120
MC3212ATZ-ULC3212ATZ	COUPLED	39.25	41.75	31.31	33.81	16.38	25.00	5.50	5.25	2.625	5.00	2.275	.625	4.00	4.75	4.50	2.250	4.25	1.972	5.00	3.25	1210
UMC3212ATZ-ULC3212ATZ	BELTED	39.75	42.25	31.31	33.81	16.38	25.00	6.00	5.75	2.875	5.50	2.450	.750	4.25	4.75	4.50	2.250	4.25	1.972	5.00	3.25	1215
LC3212ATZ-ULC3212ATZ	COUPLED	41.25	43.75	33.31	35.81	18.38	25.00	5.50	5.25	2.625	5.00	2.275	.625	4.00	4.75	4.50	2.250	4.25	1.972	5.00	3.25	1290
ULC3212ATZ-ULC3212ATZ	BELTED	41.75	44.25	33.31	35.81	18.38	25.00	6.00	5.75	2.875	5.50	2.450	.750	4.25	4.75	4.50	2.250	4.25	1.972	5.00	3.25	1295
C3214ATZ-ULC3214ATZ	COUPLED	46.25	48.75	38.31	40.81	23.38	32.00	5.50	5.25	2.625	5.00	2.275	.625	4.00	4.75	4.50	2.250	4.25	1.972	5.00	3.25	1470
UC3214ATZ-ULC3214ATZ	BELTED	46.75	49.25	38.31	40.81	23.38	32.00	6.00	5.75	2.875	5.50	2.450	.750	4.25	4.75	4.50	2.250	4.25	1.972	5.00	3.25	1475

- (1) "D" DIMENSION WILL NOT BE EXCEEDED. SHIMS UP TO .06 INCHES IN THICKNESS ARE USUALLY REQUIRED FOR COUPLED OR GEARED MACHINES.
(2) "U" AND "FU" VARY-----+.000 - .001
(3) "R" AND "FR" VARY-----+.000 - .015
(4) TERMINAL BOX VARIES WITH H.P. FOR DIMENSIONS "AA", "AB", "AC", "AF", "X" AND "Y". REFER TO BOX D/S. (STD. 609979-1, "X/P" 609979-2, MILL 609979-3)
(5) OPPOSITE DRIVE END SHAFT SUPPLIED ONLY WHEN SPECIFIED.
(6) MOTOR SHAFT TAPPED FOR SCREW IN STUB SHAFT.
(7) WHEN THE MOTOR APPLICATION DOES NOT REQUIRE THE USE OF DPP DRIVE END, ADD .25 TO "C" DIM FOR BRACKET COVER.
(8) DIMENSION FOR FRAMES WITH PREFIX LSC, LMC, LLC, LC, ULSC, ULMC, ULLC OR ULC.
(9) "XC" DIMENSION IS NOT APPLICABLE TO "C3214ATZ" FRAMES (BLOWER MOTOR IS CENTERED ON SHAFT C/L).

TERMINAL BOX CAN BE ROTATED FOR LEAD OUTLET AT TOP, SIDES OR BOTTOM.
TERMINAL BOX LOCATED ON OPPOSITE SIDE WHEN F-2, W-1, W-4, W-5, W-7, OR C-1 MOUNTING IS SPECIFIED.
BOX LOCATED ON TOP WHEN SPECIFIED.
BLOWER ASSEMBLY CAN BE LOCATED AT POSITIONS 1, 2, OR 4, EXCEPT BLOWER ASSEMBLY AND TERMINAL BOX CAN NOT BE LOCATED AT THE SAME POSITION.
MOTOR WEIGHT MAY VARY 15% FOR NON-STANDARD RATINGS AND/OR ACCESSORIES.
IF MOUNTING CLEARANCE DETAILS ARE REQUIRED, CONSULT FACTORY.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.


REV. DESC: LOADED TO BUS	VERSION: 00	TDR: 000000578087
REV. LTR: -	REVISED: 03:36:51 01/28/2011	BY: CONNAS
FILE: \RGG\00016\040		
MTL: -		

BALDOR
DIMENSION DRAWING, SC3210ATZ - ULC3214ATZ, DPP, FOOT MTG
SH 1 of 1

616032-001

INDUSTRIAL DIRECT CURRENT MOTORS
AND GENERATORS – RPM III

STEEL AND CAST IRON TERMINAL BOX DIMENSIONS
STANDARD SIZE AND ONE SIZE LARGER
FRAMES C3210ATZ THRU C3613ATZ



STEEL TERMINAL BOX DIMENSIONS

FRAME SIZE	MAX AMPS	AA(1)	AB	AC	AF	X	Y	PART NUMBER	AA(1)	AB	AC	AF	X	Y	PART NUMBER
C3210ATZ	185	2	14.88	11.38	4.25	8.44	7.25	74874-R	3	15.31	12.06	4.25	8.44	7.25	74874-24-R
C3212ATZ	269	4	16.75	12.69	5.38	10.56	9.00	700308-3-R	4	16.75	12.69	5.38	10.56	9.00	700308-3-R
C3214ATZ	500	5	21.00	15.88	6.50	12.10	14.62	702658-1-C	5	21.00	15.88	6.50	12.10	14.62	702658-1-C
C3612ATZ	185	3	16.31	13.06	4.25	8.44	7.25	74874-24-R	3	16.31	13.06	4.25	8.44	7.25	74874-24-R
C3613ATZ	269	4	17.75	13.69	5.38	10.56	9.00	700308-3-R	4	17.75	13.69	5.38	10.56	9.00	700308-3-R
	500	5	22.00	15.88	6.50	12.10	14.62	702658-1-C	5	22.00	15.88	6.50	12.10	14.62	702658-1-C

CAST IRON TERMINAL BOX DIMENSIONS

FRAME SIZE	MAX AMPS	AA(2)	AB	AC	AF	X	Y	PART NUMBER	AA(2)	AB	AC	AF	X	Y	PART NUMBER
C3210ATZ	185	1-1/2	13.62	11.19	3.00	6.00	7.00	75460-R	3	15.31	11.56	3.62	7.88	9.25	76700-RB
C3212ATZ	269	4	15.31	11.56	3.62	7.88	9.25	76700-RB	4	16.62	12.44	4.12	9.50	10.50	76708-RR
C3214ATZ	500	5	19.44	14.19	7.00	12.75	15.00	76870-S	5	19.44	14.19	7.00	12.75	15.00	76870-S
C3612ATZ	185	1-1/2	14.62	12.19	3.00	6.00	7.00	75460-R	3	16.31	12.56	3.62	7.88	9.25	76700-RB
C3613ATZ	269	4	17.62	13.44	4.12	9.50	10.50	76708-RR	4	17.62	13.44	4.12	9.50	10.50	76708-RR
	500	5	20.44	15.19	7.00	12.75	15.00	76870-S	6	20.44	15.19	7.00	12.75	15.00	76870-S

CONDUIT BOX DIMENSIONS WITH TERMINAL BOARDS (IEC TYPE BOX)

FRAME SIZE	MAX AMPS	AB	AC	AF	X	AA (3)	Y	PART NUMBER
C320	400	19.02	15.28	6.20	14.39	---	14.39	706310-63-B
	800	19.02	15.28	6.20	14.39	---	14.39	706310-63-B
	1600	19.02	15.28	7.68	15.35	---	15.35	706310-63-C
C360	400	20.00	15.28	6.20	14.39	---	14.39	706310-63-B
	800	20.00	15.28	6.20	14.39	---	14.39	706310-63-B
	1600	20.00	15.28	7.68	15.35	---	15.35	706310-63-C

OPTIONAL AUXILIARY CONDUIT BOX DIMENSIONS (MAXIMUM)

FRAME SIZE	XAB	XX	XY	PART NUMBER	FRAME SIZE	XAB	XX	XY	PART NUMBER
C320	10.00	4.25	4.25	602007-26-A	C320	13.50	8.00	8.00	706310-3-B
C360	11.00	4.25	4.25	602007-26-A	C360	14.50	8.00	8.00	706310-3-B

- (1) "AA" CONDUIT.
- (2) "AA" PIPE TAP.
- (3) CUSTOMER TO PROVIDE HOLE FOR CONDUIT.
- TERMINAL BOX LOCATED ON OPPOSITE SIDE WHEN F-2, V-1, V-4, V-5, W-7, OR C-1 MOUNTING IS SPECIFIED. BOX LOCATED ON TOP WHEN SPECIFIED.
- FOR "X/P" TERMINAL BOX DIMENSIONS SEE 609979-2.
- FOR MILL TYPE TERMINAL BOX DIMENSIONS SEE 609979-3.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: LOAD TO BUS	VERSION: 00	TDR: 000000958110
REV. LTR: -	REVISED: 08:37:45 12/17/2015	BY: RGGWT
FILE: \RGG\00026\318		
MTL: -		



DIM SHT,C3210ATZ THRU C3613ATZ,W/AUX C/BOX

SH 1 of 1

