

ABB BALDOR RELIANCE III

Customer information packet

D5075RS-1BV

MC3212ATZ, 75HP, 1750RPM, 500, 300, , F2

Specifications

Armature Voltage	500 V
Base Speed	1750 rpm
Enclosure	DPG-FV
Field Voltage	300 V
Frame	MC3212ATZ
Output Power	75.000 HP
Ambient Temperature	40 °C
Armature Current	122.0 a
Bearing Grease Type	Polyrex EM (-20F +300F)
Drip Cover	No Drip Cover
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Field Winding Type	STAB SHUNT
Frame Prefix	MC
Heater Indicator	No Heater
Insulation Class	F
IP Rating	IP23
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	F1
Overall Length	39.25 IN
Service Factor	1.00
Shaft Diameter	2.624 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Slinger Indicator	No Slinger

Part Detail

Revision	C
Type	DC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	G6295A A
Layout	609972-368
Eff. date	09-25-2024
CD Diagram	406770-001
Poles	00
Leads	
Proprietary	False
Created date	01-24-2019

Nameplate

000613006LP									
CAT.NO.	D5075RS-1BV	SPEC NO.		D32-A000-0075					
FR	MC3212ATZ	HP	75		DUTY		CONT		
ENCL.	DPG-FV	RPM	1750/2100			S.F.	1.00		
ENCL MOD		VOLTS	500			INSUL		F	
MAX SAFE SPEED	3600	AMPS	122.00			AMB.	40		
FIELD DATA		SER.NO.							
WINDING	STAB SHUNT	POWER CODE		C					
VOLTS	300	D.E. BRG.		70BC03J30X					
MAX AMPS @ 25 C	3.56	O.D.E. BRG.		60BC02J30X					
HOT AMPS	2.50/1.84	MIN. AMB.		0		TYPE		TR	
	BRUSH:419904052AJ								
	AIR BAFFLED								

Parts List

Part number	Description	Quantity
SA365375	SA D32-A000-0075	1.000 ea
AA017949	AA D32-A000-0075	1.000 ea
000692000FP	NP, WARNING LIFT INSTRUCTIONS	1.000 ea
000692000FS	WARNING LABEL	1.000 ea
033775004EA	DRSCR #6-1/4 304 S.S.	8.000 ea
000613006LP	EXTRUDER DUTY D-C MOTOR W/CSA	1.000 ea
419905004A	HARDWARE	8.000 ea
036000020KB	MHHCS M10-1.5X20MM PLTD.	4.000 ea
036610010AB	MHSLW M10 PLATED	4.000 ea
036501009AB	M8-1.25 X 9MM HEX NUTS	8.000 ea
419905003A	FLAT WASHER ROCKER RPM III RGG	4.000 ea
036000014JB	M8 X 1.25X14MM HXHDCS	4.000 ea
036600009AB	METRIC FLWASH M8 PLATED	4.000 ea
419904-52AJ	BRUSH	4.000 ea
706372012RB	ROCKR METRIC	1.000 ea
706364052B	BRHLD METRIC SPRING CHG.	4.000 ea
801930052A	BRKT,ODE,C320	1.000 ea
801931060A	BRKT,DE,C320	1.000 ea
412118001B	3/8-16 X 3/4 DRAIN SSTL.	1.000 ea
004824015A	GREASE POLYREX EM	0.400 lb
036000080KB	HHCSM10-1.5X80MMPLTD-360	3.000 ea
406055001C	GRFTG	1.000 ea
706311001X	BAFLE	1.000 ea
706311001E	BAFFLE PLATE	1.000 ea
706311001F	BAFFLE INSULATOR	1.000 ea
036310012FB	PHMS M4 X 12MM M2	8.000 ea
036501006AB	KPNUT M4 ZINC	8.000 ea
049730000L	BPLUG	4.000 ea
400638001AF	WWSHR OS-H-KK-2	1.000 ea
418150003A	GREASE FITTING CAP	2.000 ea
035000001A	ALFTG 1/8" 1610-BL	1.000 ea

035000001BB	GREASE FTG,GRS.IN	1.000 ea
036100065KA	M10-1.5 X 65MM HXSOCHDCS	3.000 ea
034693001AB	PPLG - G508- use 034692001AB	1.000 ea
034693001AB	PPLG - G508- use 034692001AB	1.000 ea
036500013AB	M16 X 2.0 HX NUT,ODE BRKT 304589	4.000 ea
418057013A	GROMT	3.000 ea
036500013AB	M16 X 2.0 HX NUT,ODE BRKT 304589	4.000 ea
609830005Y	TBOLT METRIC RP609830-	4.000 ea
610490001DG	2HP,3450//2890RPM,3PH,60//50HZ,56C,3532M	1.000 ea
415000103G	TLUG	1.000 ea
036000012JB	M8-1.25 X 12MM HXHDC	3.000 ea
611965001A	WHEEL, BLOWER	1.000 ea
417733004D	GASKET CONDUIT BOX	2.000 ea
611917001H	GASKT	1.000 ea
611917002H	GASKT	1.000 ea
036000020JB	HHCS M8-1.25X20L PLTD-250	6.000 ea
417077121	FILTER KIT	1.000 ea
032018006CK	HHCS 3/8-16X3/4L PLATED 411409	4.000 ea
706303021B	GUARD	2.000 ea
705034036A	BAFFL	1.000 ea
706303021A	GUARD	2.000 ea
000613006NT	NAME PLATE IEC	1.000 ea
418018070A	TAG "WARNING THERMOSTA	1.000 ea
036000016KB	HHCSM10-1.5X16MM PLTD-280	2.000 ea
036600009AB	METRIC FLWASH M8 PLATED	3.000 ea
418018074A	GROUND LABEL G100 METRIC 160 D.C.	3.000 ea
708528004F	HOUSING, BLOWER	1.000 ea
410978010E	INLET FLGE	1.000 ea
410978019A	SCREEN, INLET FLANGE	1.000 ea
036620009AB	M8 EXTERNAL LK WASHER	1.000 ea
036620010AB	M10 EXT. TOOTH LK WASHER	2.000 ea
036000045HB	MHHCS M6X45MM PLATED	3.000 ea
036010012GB	M5-.8 X 12 HXWHD SCREW	6.000 ea
036000012JB	M8-1.25 X 12MM HXHDC	6.000 ea

034017014AB	LCKW 3/8 STD. PLATED	4.000 ea
418014004A	609185004cDPT/BOX	1.000 ea
610409044A	ADAPT	1.000 ea
036000020JB	HHCS M8-1.25X20L PLTD-250	4.000 ea
032018004CK	HHCS 3/8-16X1/2L PLATED	4.000 ea
422919079	HHCVR KIT, C320, DE, SOLID	1.000 ea
422919079	HHCVR KIT, C320, DE, SOLID	1.000 ea
422919090	HHCVR KIT,C320,ODE,SOLID	1.000 ea
422919101	HHCVR KIT,C320,ODE, LEXAN	1.000 ea
422919090	HHCVR KIT,C320,ODE,SOLID	1.000 ea
706320009A	CB, 2.00 CONDUIT, METRIC, SHEET METAL	1.000 ea
074875000A	CONDUIT BOX COVER	1.000 ea
402731000A	GASK 320-400	1.000 ea
036000012HB	HHCS M6X12MM LONG PLATED	4.000 ea
036000045JB	M8-1.25 X 45MM HXHCS	4.000 ea
406770001	C/D TAG (STAB SHUNT)	1.000 ea
706305026A	GUARD,SHAFT	1.000 ea
034180032HA	KEY 5/8X5/8X4	1.000 ea
000640000P	TAG WINDING THERMOST	1.000 ea
000692000NG	LABEL ;NP 4POLE METRIC LABEL	1.000 ea
004824007K	SPECIAL PAINT	0.200 ea
418018116	WARNING PLATE	1.000 ea

609972-368


INDUSTRIAL DIRECT CURRENT MOTORS AND GENERATORS – RPM III

ENCLOSURE: DRIP-PROOF FULLY-GUARDED,
SPLASHPROOF
MOUNTING: FOOT

COOLING: FORCE VENTILATED WITH
INTEGRAL BLOWER AND
MOTOR AIR FILTERED-
SPECIAL BAFFLE

ACCESSORIES: PROVISION FOR
TACHOMETER MOUNTING
ONLY WHEN SPECIFIED

FRAME MC3212ATZ



- 1) SHAFT ROUNDT .003 MAX. T.I.R.
- 2) WHEN THE MOTOR APPLICATION DOES NOT REQUIRE THE USE OF OPPOSITE DRIVE END, ADD .25 TO THIS DIMENSION.
- 3) MOTOR TAPPED FOR SCREW-IN STUB SHAFT AT ODE END.
- 4) TERMINAL BOX CAN BE ROTATED WITH LEAD OUTLET AT TOP, SIDES OR BOTTOM. BOX IS RATED 128 A.
- 5) MOTOR WEIGHT APPROX. 1150 LBS.
- 6) HORIZONTAL APPLICATIONS ONLY.

IF MOUNTING CLEARANCE DETAILS ARE REQUIRED, CONSULT FACTORY.

REF. 5075RS-1BV (SPEC. D32-A000-0075)

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: REVISE DRAWING	VERSION: 01	TDR: 000001241447
REV. LTR: A	FILE: \RGG\00033\332	BY: USNISC2
MTL: -	REVISED: 03:42:52 09/23/2024	


BALDOR - RELIANCE®

DIM DRAWING, MC3212ATZ, DPP. FOOT MTG, BAFFLED, AIR FILTER
SH 1 of 1

609972-368

INDUSTRIAL DIRECT CURRENT MOTORS
AND GENERATORS – RPM III

STEEL AND CAST IRON TERMINAL BOX DIMENSIONS
STANDARD SIZE AND ONE SIZE LARGER
FRAMES C3210ATZ THRU C3613ATZ



STEEL TERMINAL BOX DIMENSIONS

FRAME SIZE	MAX AMPS	AA(1)	AB	AC	AF	X	Y	PART NUMBER	AA(2)	AB	AC	AF	X	Y	PART NUMBER
C3210ATZ	185	2	14.88	11.38	4.25	8.44	7.25	74874-R	3	15.31	12.06	4.25	8.44	7.25	74874-24-R
C3212ATZ	269	4	16.75	12.69	5.38	10.56	9.00	700308-3-R	5	16.75	12.69	5.38	10.56	9.00	700308-3-R
C3214ATZ	500	5	21.00	15.88	6.50	12.10	14.62	702658-1-C	5	21.00	15.88	6.50	12.10	14.62	702658-1-C
C3612ATZ	185	2	15.88	12.38	4.25	8.44	7.25	74874-R	3	16.31	13.06	4.25	8.44	7.25	74874-24-R
C3613ATZ	269	4	17.75	13.69	5.38	10.56	9.00	700308-3-R	5	17.75	13.69	5.38	10.56	9.00	700308-3-R
	500	5	22.00	15.88	6.50	12.10	14.62	702658-1-C	5	22.00	15.88	6.50	12.10	14.62	702658-1-C

CAST IRON TERMINAL BOX DIMENSIONS

FRAME SIZE	MAX AMPS	AA(2)	AB	AC	AF	X	Y	PART NUMBER	AA(2)	AB	AC	AF	X	Y	PART NUMBER
C3210ATZ	185	1-1/2	13.62	11.19	3.00	6.00	7.00	75460-R	3	15.31	11.56	3.62	7.88	9.25	76700-RB
C3212ATZ	269	4	15.31	11.56	3.62	7.88	9.25	76700-RB	4	16.62	12.44	4.12	9.50	10.50	76708-RR
C3214ATZ	500	5	19.44	14.19	7.00	12.75	15.00	76870-S	5	19.44	14.19	7.00	12.75	15.00	76870-S
C3612ATZ	185	1-1/2	14.62	12.19	3.00	6.00	7.00	75460-R	3	16.31	12.56	3.62	7.88	9.25	76700-RB
C3613ATZ	269	4	17.62	13.44	4.12	9.50	10.50	76708-RR	5	20.44	15.19	7.00	12.75	15.00	76870-S
	500	5	20.44	15.19	7.00	12.75	15.00	76870-S	6	20.44	15.19	7.00	12.75	15.00	76870-R

CONDUIT BOX DIMENSIONS WITH TERMINAL BOARDS (IEC TYPE BOX)

FRAME SIZE	MAX AMPS	AB	AC	AF	X	AA (3)	Y	PART NUMBER
C320	400	19.02	15.28	6.20	14.39	---	14.39	706310-63-B
	800	19.02	15.28	6.20	14.39	---	14.39	706310-63-B
	1600	19.02	15.28	7.68	15.35	---	15.35	706310-63-C
C360	400	20.00	15.28	6.20	14.39	---	14.39	706310-63-B
	800	20.00	15.28	6.20	14.39	---	14.39	706310-63-B
	1600	20.00	15.28	7.68	15.35	---	15.35	706310-63-C

OPTIONAL AUXILIARY CONDUIT BOX DIMENSIONS (MAXIMUM)

FRAME SIZE	XAB	XX	XY	PART NUMBER	FRAME SIZE	XAB	XX	XY	PART NUMBER
C320	10.00	4.25	4.25	602007-26-A	C320	13.50	8.00	8.00	706310-3-B
C360	11.00	4.25	4.25	602007-26-A	C360	14.50	8.00	8.00	706310-3-B

- (1) 'AA' CONDUIT.
- (2) 'AA' PIPE TAP.
- (3) CUSTOMER TO PROVIDE HOLE FOR CONDUIT.
- TERMINAL BOX LOCATED ON OPPOSITE SIDE WHEN F-2, V-1, V-4, V-5, W-7, OR C-1 MOUNTING IS SPECIFIED. BOX LOCATED ON TOP WHEN SPECIFIED.
- FOR 'X/P' TERMINAL BOX DIMENSIONS SEE 609979-2.
- FOR MILL TYPE TERMINAL BOX DIMENSIONS SEE 609979-3.


CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: LOAD TO BUS	VERSION: 00	TDR: 000000958110
REV. LTR: -	REVISED: 08:37:45 12/17/2015	BY: RGGWT
FILE: \RGG\00026\318		
MTL: -		



DIM SHT,C3210ATZ THRU C3613ATZ,W/AUX C/BOX

065564-004



SYM	MAKE FROM	a	b	c	REMARKS
A	X	1/8	5/8	24*	TERMBX & CVR 180AT-250AT
B	X	1/8	5/8	37 1/2*	TERMBX & CVR 280AT-320AT
C	Y	1/4	5/8	44 1/2Δ	FILTER TO HOUSING GASKET
D	X	1/8	5/8	170"	TEAO HEAT EXCH.
E	Y	1/4	5/8	72"Δ	TERMBX & CVR

SYM	MAT'L SPEC	a	b	c
X	46024-XV	1/8	5/8	* 50' ROLL; WET ADHESIVE ON ONE SIDE
Y	46024-XV	1/4	5/8	* 50' ROLL; WET ADHESIVE ON ONE SIDE

Δ RELIANCE WILL CUT AND MOUNT ON FILTER HOUSING PER
ASSEMBLY DRAWING 603989-2.

* PROD. NOTE: WHEN ORDERING THRU PURCHASING
ORDER AS 50 FT. ROLLS, WET ADHESIVE ON ONE
SIDE. RELIANCE WILL CUT AND MOUNT ON COVER.
PER INSTRUCTIONS ON COVER DRAWINGS.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: CHANGE DESCRIPTION ON TITLE BLOCK		
REV. LTR: C	VERSION: 03	TDR: 000000571980
FILE: \RGG\00000\220	REVISED: 10:54:04 12/16/2010	BY: RGGWT
MTL: -		

BALDOR
GASKET,STRIP,CLOSED CELL NEOPRENE
SH 1 of 1

065564-004

