ABB BALDOR RELIANCE

Customer information packet

ECP4102T-5

20HP, 1180RPM, 3PH, 60HZ, 286T, 1062M, TEFC, F1
Class - CLI GP A,B,C,D
Division - Division II

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
11/1/2026 6:39:50 PM

Specifications

Enclosure	TEFC
Frame	286T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	20.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Agency Approvals	CSA EEV
	NEMA PREMIUM
	NEMA_PREMIUM
	UR
	CCSA US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	1.0
Current @ Voltage	20.600 A @ 575.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None

Part Detail

Revision	AH
Type	AC
Mech. spec.	10H292
Base	
Status	PRD/A
Elec. spec.	10WGY161
Layout	10LYH292
Eff. date	09-29-2025
CD Diagram	CD0006
Poles	06
Leads	3#10
Proprietary	False
Created date	01-09-2013

Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	20.6 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	1800 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	3 @ 10 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1062M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	28.00 IN
Power Factor	78
Product Family	Super-E Chemical Processing
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.15
Shaft Diameter	1.875 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1180 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None

Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3241

CAT.NO.	ECP4102T-5		**P/N**				**ENCLOSURE**	TEFC				
SPEC.	10H292Y161G1	**CC**	010A	**FRAME**	286T		**S/N**					
HP	20		**CLASS**	F	**HZ**	60	**DES**	A				
RPM	1180		**RPM MAX**	1800	**PH**	3	**KVA-CODE**	H				
VOLT	575		**MOTOR WEIGHT**	478								
AMP	20.6		**SER.F.**	1.15	**PF**	78	**ODE BRG**	6311	**DE BRG**	6311		
RATING	40C AMB-CONT		**NEMA-NOM-EFF**	93			**GREASE**	POLYREX EM				
					INV.TYPE	PWM						
TEMP CODE	T3C	**INVERTER-TEMP-CODE**	180									
TEMP =	160	**C HP FR**	60	**C HP TO**	90							
CT HZ FROM	1.0	**CT HZ TO**	60									
HTR-VOLTS		**HTR-AMPS**		**HTR-WATTS**		**MAX. SPACE HEATER TEMP.**			**VT HZ FROM**	O	**VT HZ TO**	60

Parts List

Part number	Description	Quantity
SA256683	SA 10H292Y161G1	1.000 ea
RA243471	RA 10H292Y161G1	1.000 ea
09FN3001B02	EXTERNAL FAN, PLASTIC (COMES W/SCREW FRO	1.000 ea
10CB1000A09P	KOBX, MACH W/1.50 NPT & PRIMER	1.000 ea
09GS1010	GASKET, DWG, LEADWIRE SEPERATOR	1.000 ea
10XN3118K16	5/16-18 X 1' GRADE #5, STL, ZINC PLATE	4.000 ea
HW1001A31	LOCKWASHER 5/16, ZINC PLT.591 OD, .319 I	4.000 ea
10CB1503P	CONDUIT BOX LIPPED, CAST W/EPOXY PRIMER	1.000 ea
WD1000B16	T&B CX70TN OR L70P TERMINAL LUG	1.000 ea
59XW2520G07	.25-20X.44,HEX SER WSHR,TAPTITE 2,GREEN	1.000 ea
10XN3816K28	3/8-16 X 1.75 HEX HD CAP SCREW, GRADE 5	4.000 ea
HW1001A38	LOCKWASHER 3/8, ZINC PLT .688 OD, .382 I	4.000 ea
HA4017A11	1/8 X 2.75 GREASE EXT (F/S)	1.000 ea
HA4017A03	.125 X 1.75 GREASE EXT (F/S)	1.000 ea
HW4019A01	PIPE COUPLING 1/8 NPT,STEEL,ZINC COATING	1.000 ea
HW4600B40	V-RING SLINGER 2.000 X 2.680 X .28 VITON	1.000 ea
HW5100A13	W4627-047 WVY WSHER	1.000 ea
HW4500A20	1/8NPT SL PIPE PLUG	1.000 ea
10XN3118K40	5/16-18 X 2.50" HEX HD, GRADE 5	4.000 ea
10EP1110A47P	PU ENDPLATE, MACH W/PRIMER	1.000 ea
10FH1007P	FAN COVER, CAST W/EPOXY PRIMER	1.000 ea
10XN3816K28	3/8-16 X 1.75 HEX HD CAP SCREW, GRADE 5	4.000 ea
HW1001A38	LOCKWASHER 3/8, ZINC PLT .688 OD, .382 I	4.000 ea
HW4500A20	1/8NPT SL PIPE PLUG	1.000 ea
HW4600B40	V-RING SLINGER 2.000 X 2.680 X .28 VITON	1.000 ea
10XN3118K40	5/16-18 X 2.50" HEX HD, GRADE 5	4.000 ea
10XN3118K20	5/16-18 X 1 1/4 GRADE 5 STEEL ZC PLATED	3.000 ea
HW1001A31	LOCKWASHER 5/16, ZINC PLT.591 OD, .319 I	3.000 ea
14GS1003	GASKET CONDUIT BOX LID, NEOP	1.000 ea
10XN2520K16	1/4-20 X 1" HX HD SCRW GRADE 5, ZINC P	4.000 ea
HW1001A25	LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I	4.000 ea

HW2501H29	KEY, 1/2 SQ X 3.375	1.000 ea
MJ5001A27	32220KN GRAY SEALER *MIN BUY 4 QTS=1GAL	0.031 qt
MJ5002A01	SILICON RUBBER SEALANT, 732CL 10.3 OZ TU	0.033 ea
MJ5002A01	SILICON RUBBER SEALANT, 732CL 10.3 OZ TU	0.025 ea
10EP1110A44LP5	FREP, MACH W/PRIMER & MG1025L14	1.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
LB1002N	LABEL,MARINE DUTY (ON ROLLS)	1.000 ea
HA4051A00	PLASTIC CAP FOR GREASE FITTING	1.000 ea
HW4500A21	1618BALEMITE FITTING 825 UNIVERSAL	1.000 ea
HW4500A17	317400 ALEMITE GREASE RELIEF	1.000 ea
HA4054	SHORT T-DRAIN FITTING, .125" N.P.T.	1.000 ea
MJ1000A02	GREASE, POLYREX EM EXXON	0.130 lb
HA4051A00	PLASTIC CAP FOR GREASE FITTING	1.000 ea
HW4500A17	317400 ALEMITE GREASE RELIEF	1.000 ea
HW4500A03	GREASE FITTING, .125 NPT 1610(ALEMITE) 8	1.000 ea
HA4054	SHORT T-DRAIN FITTING, .125" N.P.T.	1.000 ea
HW2500A25	WOODRUFF KEY USA #1008 #BLOW CARBON STEE	1.000 ea
MG1025N19	WILKOFAST, 778.50, RELIANCE BLUE-GREEN 8	0.125 ga
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	4.000 ea
LB1624	COMBINED WARNING LABEL, ISO/ANSI PICTOGR	1.000 ea
LC0006	CONNECTION LABEL	1.000 ea
NP3241	SS SUPER-E INV UL CSA-EEV PREM CC	1.000 ea
LB1449	DIV-2/NEC WARNING LABEL	1.000 ea
10PA1000	PACKAGING GROUP COMBINED PRINT PK1023A07	1.000 ea

AC Induction Motor Performance Data
Record # 47253
Typical performance - not guaranteed values

Winding: 10WGY161-R004	**Type:** 1062M	**Enclosure:** TEFC

Nameplate Data			
Rated Output (HP)			20
Volts			575
Full Load Amps			20.6
R.P.M.			1180
Hz	60	**Phase**	3
NEMA Design Code	A	**KVA Code**	H
Service Factor (S.F.)			1.15
NEMA Nom. Eff.	93	**Power Factor**	78
Rating - Duty			40C AMB-CONT
S.F. Amps			

575 V, 60 Hz: Single Voltage Motor	
Full Load Torque	89 LB-FT
Start Configuration	direct on line
Breakdown Torque	281 LB-FT
Pull-up Torque	110 LB-FT
Locked-rotor Torque	156 LB-FT
Starting Current	135 A
No-load Current	9.64 A
Line-line Res. @ 25ºC	0.593 Ω
Temp. Rise @ Rated Load	48°C
Temp. Rise @ S.F. Load	58°C
Rotor inertia	7.59 LB-FT2

Load Characteristics 575 V, 60 Hz, 20 HP

% of Rated Load	**25**	**50**	**75**	**100**	**125**	**150**	**S.F.**
Power Factor	40	62	73	78	80	81	79
Efficiency	87.4	92.1	93.2	93.2	92.4	92	92.7
Speed	1195	1191	1187	1183	1178	1173	1180
Line amperes	10.7	13.4	16.7	20.6	25.1	30.2	23.3


ABB Motors and Mechanical Inc.


WINDING # 10WGY161

20 HP 3 PH 60 HZ 1180 RPM 575 V 1062M

Typical performance - not guaranteed values.


TORQUES(LB-FT): PO=281 PU=110 LR=156 LRA=135





10LYH292
[711]
(1028-1080) =28.00
[332]
13.07
[121]
4.75
[117]
4.63
.50 [13]KEY
3.38 [86] LONG
[47.61]
[47.59]
Ø 1.875
Ø 1.874
SLINGER
(EA. END)
DRAIN
FITTING
(EA. END)
.25-20 TAP
GRD LOC.
8 HOLES
Ø .53 [13]
[241]
9.50
[23]
.92
[241]
9.50
[121]
4.75
[279]
11.00
[326.14]
13
[399]
15.72
[324]
12.75
[198]
7.80
[69]
2.70
PLUG
(EA. END)
[367]
14.44
[178.0 -1]
7.000 +.000 -.060
[82]
3.25
[22]
.88
LEAD HOLE
1.50 NPT
[140]
5.50
[140]
5.50
[260]
10.25
[162]
6.38
[324]
12.75
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION
REV. DESC: ADD METRIC DIMS
REV: H
VERSION: 08
REVISED: 01:34:44 05/01/2023
TDR: 000001207975
MODEL NO. 10LYH292
REF: -
BY: ENNIND0
B
BALDOR
HORZ TEFC 284-6T ECP W/311 BRGS & PLS
10LYH292


CD0006

TYPICAL WYE–CONNECTED MOTOR





TYPICAL DELTA–CONNECTED MOTOR



NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007		
REV. LTR: E	VERSION: 01	TDR: 000001099922
FILE: \AAA\00005\141	REVISED: 10:24:49 02/19/2019	BY: ENBRIR0
MTL: –		

BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1