

ABB BALDOR RELIANCE III

Customer information packet

EM4348T

40HP, 890RPM, 3PH, 60HZ, 365T, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	365T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	40.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	900 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CURUSEEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Current @ Voltage	104.000 A @ 230.0 V 111.000 A @ 208.0 V 52.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.0 %
Feedback Device	NO FEEDBACK
Heater Indicator	No Heater
High Voltage Full Load Amps	52.0 a
Insulation Class	F
Inverter Code	Inverter Ready
IP Rating	NONE
KVA Code	G
Lifting Lugs	Standard Lifting Lugs

Part Detail

Revision	K
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A36WG1044
Layout	617428-077
Eff. date	11-16-2023
CD Diagram	416820-002
Poles	08
Leads	3#6,6#8
Proprietary	False
Created date	11-23-2015

Motor Lead Quantity/Wire Size	3 @ 6 AWG
Motor Standards	NEMA
Motor Type	A36062M
Mounting Arrangement	F1
Number of Poles	8
Overall Length	33.47 IN
Power Factor	77
Product Family	General Industrial
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.15
Shaft Diameter	2.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	890 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None

Nameplate

NP2496L	
MOBIL POLYREX EM	

NP2349L

SPEC NO.	A36-7200-1044			CAT.NO.	EM4348T				FRAME	365T				
HP	40	VOLTS	230/460		PHASE	3	DESIGN	B	TYPE	P				
RPM	890	AMPS	104/52		HZ	60	AMB	40	SF	1.15				
DRIVE END BEARING	65BC03J30X			DUTY	CONT		INSUL.CLASS		F					
OPP D.E. BEARING	65BC03J30X			ENCL	TEFC		CODE	G						
SER.NO.				POWER FACTOR		77		NEMA-NOM-EFFICIENCY				93		
						MAX CORR KVAR		15	GUARANTEED EFFICIENCY		91.7			
						NEMA NOM/CSA QUOTED EFF								
								MOTOR WEIGHT				875		

Parts List

Part number	Description	Quantity
SA310819	SA A36-7200-1044	1.000 ea
RA298217	RA A36-7200-1044	1.000 ea
421948032	LABEL, MYLAR	1.000 ea
NP2496L	MOTOR LUBE NAMEPLATE	1.000 ea
000613006PU	N/P (RELEASE QTY 10,000) UL CSA LABEL	1.000 ea
000692000VD	LABEL WARNING	1.000 ea
NP2349L	SUPER-E ,SS, CURUS EEV, CC, LASER	1.000 ea
085922073B	BRKT 360 085922072WCC KB	1.000 ea
415072001B	CLAMP	1.000 ea
078559001A	+FANCV - 360	1.000 ea
034180012DA	KEY 1X4X1/4X1-1/2 L	1.000 ea
078557001F	FAN KB 110/50 (60) 360	1.000 ea
004824015A	GREASE POLYREX EM	0.540 lb
032018012DK	HHCS 1/2-13X1-1/2 PLTD. 032018012DR	4.000 ea
032018008AK	HHCS 1/4-20X1 PLATED	4.000 ea
032018024CK	HHCS 3/8-16X3 PLTD.	3.000 ea
415096002A	CPLG 1/8 HEX TYPE	1.000 ea
410700004F	WSHR	1.000 ea
035000001G	GREASE RELIEF FITTING, ALEMITE 317400	1.000 ea
035000001G	GREASE RELIEF FITTING, ALEMITE 317400	1.000 ea
034530052AB	P/NIP 1/8X6-1/2 Zinc	1.000 ea
034600001AA	BUSH 1/4TO1/8 BLACK	1.000 ea
412118006A	DRAIN	1.000 ea
412118006A	DRAIN	1.000 ea
034600001AA	BUSH 1/4TO1/8 BLACK	1.000 ea
085922073B	BRKT 360 085922072WCC KB	1.000 ea
032018012DK	HHCS 1/2-13X1-1/2 PLTD. 032018012DR	4.000 ea
032018024CK	HHCS 3/8-16X3 PLTD.	3.000 ea
077176000L	C/BOX, PAINTED 440	1.000 ea
077176001A	CBOX Cover 360-400	1.000 ea
043292000AJ	GASK 320-400	1.000 ea

402731001A	GASK 360-440	1.000 ea
418150003A	GREASE FITTING CAP	1.000 ea
MG1025Y17	WILKOFEST, 789.701, SUPER E PEARL GOLD	0.250 ga
032018005DL	1/2-13 X 5/8 SILICON BRONZE HHCS	1.000 ea
032018005AK	HHCS 1/4-20X5/8 PLATED	4.000 ea
032018008CK	HHCS 3/8-16X1L PLATED	4.000 ea
035000001A	ALFTG 1/8" 1610-BL	1.000 ea
415000115H	T/LUG #2AWG-4/0AWG	1.000 ea
406099000A	PLUG - FAN COVER 320-440	1.000 ea
035000001A	ALFTG 1/8" 1610-BL	1.000 ea
418150003A	GREASE FITTING CAP	1.000 ea
033775004EA	DRSCR #6-1/4 304 S.S.	2.000 ea
034180034HA	KEY 5/8X5/8X4-1/4 L	1.000 ea
14PA1000	PACKAGING 314 GROUP COMBINED PRINT	1.000 ea
HW1000A32	5/16 FL WASHER WIDE,ID=.344,OD=1.125	3.000 ea
032509020C	CARRIAGE BOLT - 360	3.000 ea

REL. S.O.	FRAME	HP	TYPE	PHASE/ HERTZ	RPM	VOLTS
	365T	40	P	3/60	890	230/460
AMPS	DUTY	AMB °C/ INSUL.	S.F.	NEMA DESIGN	CODE LETTER	ENCL.
104/52	CONT	40/F	1.15	B	G	FCXE
E/S	ROTOR	TEST S.O.	TEST DATE	STATOR RES. @25 °C OHMS (BETWEEN LINES)		
492342	418141073EE	---	---	.0486/.194		
PERFORMANCE						
LOAD	HP	AMPERES	RPM	% POWER FACTOR	% EFFICIENCY	
NO LOAD	0	25.7	900	3.85	0	
1/4	10.0	28.1	897	37.3	89.5	
2/4	20.0	33.9	895	59.5	93.0	
3/4	30.0	42.2	892	71.2	93.4	
4/4	40.0	52.0	889	77.4	93.0	
5/4	50.0	63.3	885	80.2	92.2	
SPEED TORQUE						
	RPM	TORQUE % FULL LOAD	TORQUE LB.-FT.	AMPERES		
LOCKED ROTOR	0	140	330	282		
PULL UP	225	123	290	265		
BREAKDOWN	845	224	530	157		
FULL LOAD	889	100	236	52.0		
AMPERES SHOWN FOR 460. VOLT CONNECTION. IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE REMARKS: XE MOTOR-TYPICAL DATA-NEMA NOM. EFF. 93.0 PCT. GUARANTEED MIN. EFF. 92.4 PCT.						
		DR. BY <u>M.C. BENTON</u> CK. BY <u>K.W. KANOUFF</u> APP. BY <u>K.W. KANOUFF</u> DATE <u>03/09/93</u>				
		A-C MOTOR PERFORMANCE DATA				
		A36WG1044-R001 ISSUE DATE 03/09/93				

FRAME 365T

VOLTS 230/460

NEMA DESIGN B

TEST S.O. ---

HP 40

AMPS 104/52

CODE LETTER G

TEST DATE ---

TYPE P

DUTY CONT

ENCLOSURE FCXE


STATOR RES. @ 25 °C .0486/.194

PHASE/HERTZ 3/60

AMB °C/INSUL 40/F

E/S 492342

OHMS (BETWEEN LINES)




AMPERES SHOWN FOR 460 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.

BALDOR



DR. BY M.C. BENTON
CK. BY K.W. KANOUFF
APP. BY K.W. KANOUFF
DATE 03/09/93

**A-C MOTOR
PERFORMANCE CURVES** A36WG1044-R001
ISSUE DATE 03/09/93



416820-002

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 9 LEAD DELTA-CONNECTED



(N.P. 1575-B)

REV. DESC: FONT CHANGE FOR PDF SEARCHABLE		
REV. LTR: A	VERSION: 01	TDR: 000001009382
FILE: \MGA\00000\661	REVISED: 02:46:19 02/13/2020	BY: MGHMTT
MTL: —	⊗ ◻	

BALDOR - RELIANCE®

CONN DIAG — STANDARD 9 LEAD, DELTA-CONNECTED
SH 1 of 1

416820-002