

ABB BALDOR RELIANCE III

Customer information packet

GDL1607T

7.5HP, 1725RPM, 1PH, 60HZ, 215TZ, 3744LC, ODTF

Class - None

Division - Not Applicable

Specifications

Enclosure	ODTF
Frame	215TZ
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Cap Run
Output @ Frequency	7.500 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	32.000 A @ 230.0 V
Design Code	L
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	82.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	32.0 a
Insulation Class	F
Inverter Code	Not Inverter

Part Detail

Revision	K
Type	AC
Mech. spec.	37M320
Base	
Status	PRD/A
Elec. spec.	37WG1630
Layout	37LYM320
Eff. date	02-08-2024
CD Diagram	CD0086
Poles	04
Leads	2#8 A PH,2#14 B PH
Proprietary	False
Created date	02-09-2010

KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Cap Box
Motor Lead Quantity/Wire Size	2 @ 8 AWG, A PH
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3744LC
Mounting Arrangement	F1
Number of Poles	4
Overall Length	22.57 IN
Power Factor	90
Product Family	General Purpose
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	Included
Service Factor	1.15
Shaft Diameter	1.375 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1725 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L											
CAT.NO.	GDL1607T										
SPEC.	37M320-1630G1										
HP	7.5										
VOLTS	230										
AMP	32										
RPM	1725										
FRAME	215TZ		HZ	60				PH	1		
SER.F.	1.15		CODE	J	DES	L		CLASS	F		
NEMA-NOM-EFF	82.5		PF	90							
RATING	40C AMB-CONT										
CC											
DE	6307		ODE	6206							
ENCL	ODTF		SN								

Parts List

Part number	Description	Quantity
SA190810	SA 37M320-1630G1	1.000 ea
RA178475	RA 37M320-1630G1	1.000 ea
OC3060F10SP	CYL OIL CAP 60MFD/370V	1.000 ea
EC1216C06SP	ELEC CAP, 216-259 MFD, 250V, 2.06D X 4.	3.000 ea
HW3200A01	3/8-16X3/4 EYEBOLT WELDED F/S	1.000 ea
37CB5001A25	OPEN, A01 BOX W/LID, W/GASKETS - NO THRM	1.000 ea
37EP3203B00	MASTER,ODE,206 BRG,GREASER,DRIP COVER	1.000 ea
HW4500A19	1/4-28X1/4 SLOTTED PLUG F/S	1.000 ea
SP1008A01	BAFFLE, MODEL 36 & 37	1.000 ea
13XF0832A08	8-32 X.50 PAN HD,SLTD, TYPE F SCREW, ZIN	2.000 ea
HW5100A06	W2420-025 WVY WSHR (WB)	1.000 ea
37EP3400A08	EP PU OPEN 307 BRG W/GRSR, BAFFLE & SCRE	1.000 ea
37AD2000A01	BAFFLE PLATE, STAMPED PLATED	1.000 ea
60XW0632A06	6-32 X 3/8 TORX HEAD SCREW TAPTITE II	4.000 ea
HW4500A19	1/4-28X1/4 SLOTTED PLUG F/S	1.000 ea
HA1222	RODENT SCREEN - 37 C-FACE MOTORS	4.000 ea
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	4.000 ea
HW1000A10	#10 FLAT WASHER (SAE)	4.000 ea
XY3118A12	5/16-18 HEX NUT DIRECTIONAL SERRATION	4.000 ea
10XN2520A28	1/4-20X 1 3/4 HEX HD	4.000 ea
HW1001A25	LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I	4.000 ea
37FN3000A01SP	EXFN, PLASTIC, 8.50 OD, 1.175 ID	1.000 ea
10XN2520A24	1/4-20X 1 1/2 HEX HD X	1.000 ea
XY2520A11	254-20 SQUARE NUT	1.000 ea
37FH4000A05SP	DRIP COVER, W/ PRIMER	1.000 ea
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 ea
HA1005A07	SLINGER, OD 2.25, ID 1.344, 307 BRG	1.000 ea
HW2501F21	KEY, 5/16 SQ X 2.375	1.000 ea
HA7000A02	KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA	1.000 ea
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
MJ1000A02	GREASE, POLYREX EM EXXON	0.050 lb

WD1000A03	41531 AMP FLG.TERM,4M/REEL(2.5MIL)	10.000 ea
SP5172A03	37 TYPE L TORQ STAT SWITCH LEAD ASSEMBLY	1.000 ea
HA3104A24	THRUBOLT- 5/16-18 X14.375	4.000 ea
MG1025G29	WILKOFAST, 789.229, DARK CHARCOAL GRAY	0.028 ga
LC0086	CONNECTION LABEL	1.000 ea
LB1624	COMBINED WARNING LABEL, ISO/ANSI PICTOGR	1.000 ea
NP1256L	ALUM UL CC INDUSTRIAL MOTOR A60	1.000 ea
37PA1074	PALLET PACK GRP, PRINT BOX PK1026A06	1.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
FE-0000001	ZRTG FE ASSEMBLY	1.000 ea

Accessories

Part number	Description	Multiplier
37-1404	C FACE KIT	A8

AC Induction Motor Performance Data

Record # 37082

Typical performance - not guaranteed values

Winding: 37WG1630-R002			Type: 3744LC		Enclosure: ODTF			
Nameplate Data			230 V, 60 Hz: Single Voltage Motor					
Rated Output (HP)		7.5	Full Load Torque		22.3 LB-FT			
Volts		230	Start Configuration		direct on line			
Full Load Amps		32	Breakdown Torque		65 LB-FT			
R.P.M.		1725	Pull-up Torque		40 LB-FT			
Hz	60	Phase	1	Locked-rotor Torque		75 LB-FT		
NEMA Design Code		L	KVA Code	J	Starting Current		250 A	
Service Factor (S.F.)		1.15		No-load Current		10 A		
NEMA Nom. Eff.		82.5	Power Factor		90	Line-line Res. @ 25°C		0.187 Ω A Ph 1.18 Ω B Ph
Rating - Duty		40C		AMB-CONT		Temp. Rise @ Rated Load		69°C
S.F. Amps						Temp. Rise @ S.F. Load		77°C

Load Characteristics 230 V, 60 Hz, 7.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	74	87	91	91	90	87	90
Efficiency	66.3	78.9	82.6	83.6	83.2	80.5	83.4
Speed	1788	1778	1766	1751	1735	1708	1741
Line amperes	12.6	18.1	24.4	31.6	39.9	50	36.6


ABB Motors and Mechanical Inc.


WINDING # 37WG1630

Typical performance - not guaranteed values.


7.5 HP 1 PH 60 HZ 1725 RPM 230 V 3744LC

TORQUES (LB-FT) : PO=65 PU=40 LR=75 LRA=250





CD0086



	LINE A	LINE B
STD	1,8	4,5
OPP	1,5	4,8

- NOTES:
1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
 2. OPTIONAL THERMOSTAT IS PROVIDED WHEN SPECIFIED.
 3. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
 4. OPTIONAL OIL CAPACITOR IS PROVIDED WHEN SPECIFIED.
 5. CAPACITORS MAY BE SEPERATELY MOUNTED.
 6. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: ADDED CK TO PLANT CODE			
REV. LTR: F	BY: JD	REVISED: 16:01:12 01/07/2002	TDR: 259409
980000		FILE: AAA00026904	REF: CD0086
		MTL: -	

BALDOR ELECTRIC Co.

TYPE L OR LC, SV, REV, 4 LEADS, CAPS MAY BE SEP MTD

CD0086