

ABB BALDOR RELIANCE III

Customer information packet

HIC264A

.33HP, 1625RPM, 1PH, 60HZ, 48Z, 3414C, TEAO, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEAO
Frame	48Z
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Oil Capacitor Start and Run
Output @ Frequency	.330 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	115.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	1.900 A @ 230.0 V 3.800 A @ 115.0 V
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	64.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Terminal Panel
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	1.9 a
Insulation Class	F

Part Detail

Revision	L
Type	AC
Mech. spec.	34M259
Base	
Status	PRD/A
Elec. spec.	34WGR070
Layout	34LYM259
Eff. date	10-28-2024
CD Diagram	CD0804A01
Poles	04
Leads	9#18
Proprietary	False
Created date	06-04-2013

Inverter Code	Not Inverter
KVA Code	C
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Terminal Panel Or Lead Hole
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	None
Motor Standards	NEMA
Motor Type	3414C
Mounting Arrangement	F1
Number of Poles	4
Overall Length	10.09 IN
Power Factor	90
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Multiple Flats
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.00
Shaft Diameter	0.500 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible: Connected Standard
Shaft Slinger Indicator	Shaft Slinger
Speed	1625 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Automatic Thermal Overload
Winding Thermal 1 Location	WG
Winding Thermal 2	None

Nameplate

NP1257L									
CAT.NO.	HIC264A								
SPEC.	34M259R070G1								
HP	.33								
VOLTS	115/230								
AMP	3.8/1.9								
RPM	1625								
FRAME	48Z			HZ	60		PH	1	
SER.F.	1.00		CODE	C		DES	-	CL	F
NEMA-NOM-EFF	64		PF	90					
RATING	40C AMB-CONT								
CC									
DE	6203		ODE	6203					
ENCL	TEAO		SN						

Parts List

Part number	Description	Quantity
SA264225	SA 34M259R070G1	1.000 ea
RA250938	RA 34M259R070G1	1.000 ea
OC3020F12SP	CAPACITORS 20 MFD 370 VAC	1.000 ea
11XW0832G06	#8-32 X 3/8, TAPTITE II, HEX WSHR SLTD	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	3.000 ea
33CB4800A01	CAPACITOR COVER, STAMPED	1.000 ea
35GS3001A01	GASKET, CAPACITOR COVER	1.000 ea
34GS5003	FOAM SLEEVE, ID = 2 1/16" X 3 3/8"	1.000 ea
51XB1016A05	10-16X5/16HX WA SL SR TYB (F/S)	2.000 ea
WD4100A42	CAPLUG BPF-3/4, FOR 1/2" NPT OR 3/4 HOLE	1.000 ea
34EP3204D01	SPL FR ENDPLATE 34L - ENCL	1.000 ea
HW5100A03	WAVY WASHER (W1543-017)	1.000 ea
34EP3109D01	PU ENDPLATE, MACH ENCL, 5.125 B.C.	1.000 ea
XY0832A02	8-32 HEX NUT	8.000 ea
34CB4501SP	TERMINAL BOX LID, STAMPED X (PLATED)	1.000 ea
34GS1005	GASKET, TERM PLATE LID	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 ea
HA1005A05SP	SLINGER, OD 1.50, ID .659, 203 BRG	1.000 ea
MG1050G01	CELEROL MEDIUM CHARCOAL METALLIC GRAY	0.014 ga
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
ML14-8C18	18 AWG, 8,RED	31.000 in
WD1000A16	2-520128-2 AMP FLAG TERMINAL(4M/RL)	2.000 ea
WD1000A27	2-520263-4 AMP TRM 3.4/RL	1.000 ea
WD1000A28	SPADE TERM,18-22AWG.INSUL.(3./RL) AMP# 2	1.000 ea
WD1000A27	2-520263-4 AMP TRM 3.4/RL	1.000 ea
WD1000A28	SPADE TERM,18-22AWG.INSUL.(3./RL) AMP# 2	1.000 ea
ML14-6L18	18 AWG, 6,PURPLE	21.000 in
WD1000A16	2-520128-2 AMP FLAG TERMINAL(4M/RL)	1.000 ea
ML14-6L18	18 AWG, 6,PURPLE	21.000 in
WD1000A16	2-520128-2 AMP FLAG TERMINAL(4M/RL)	1.000 ea
WD1000A16	2-520128-2 AMP FLAG TERMINAL(4M/RL)	7.000 ea

SP5068A29	MODEL 34 TERM PANEL SWITCH "L"	1.000 ea
HA3169A07	THRUBOLT #8-32 THDS X 8.188" LONG	4.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
LB1118	LABEL,WARNING (ROLL LABEL)	1.000 ea
NP1257L	ALUM UL CC THERMAL REV MTG	1.000 ea
34PA1002	PKG GRP, PRINT PK1001A01	1.000 ea
PK3083	STYROFOAM PACKING CRADLE	1.000 ea
PK3088	MICROFOAM, 8"X"8 PERF. SHEETS	1.000 ea

AC Induction Motor Performance Data

Record # 42889

Typical performance - not guaranteed values

Winding: 34WGR070-R001			Type: 3414C		Enclosure: TEAO	
Nameplate Data				230 V, 60 Hz: High Voltage Connection		
Rated Output (HP)		.33 AIR OVER		Full Load Torque		1.06 LB-FT
Volts		115/230		Start Configuration		direct on line
Full Load Amps		3.8/1.9		Breakdown Torque		2.17 LB-FT
R.P.M.		1625		Pull-up Torque		0.709 LB-FT
Hz	60	Phase	1	Locked-rotor Torque		0.779 LB-FT
NEMA Design Code		- KVA Code		Starting Current		5.37 A
Service Factor (S.F.)		1		No-load Current		0.987 A
NEMA Nom. Eff.		64	Power Factor	90	Line-line Res. @ 25°C	
						11.488 Ω A Ph 9.5258 Ω B Ph
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		

Load Characteristics 230 V, 60 Hz, 0.33 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	75	83	88	90	92	93
Efficiency	34	52.1	61.3	64.6	63.9	59.8
Speed	1759.9	1728.4	1690.3	1642	1577	1489.7
Line amperes	1.11	1.31	1.56	1.85	2.22	2.67

ABB Motors and Mechanical Inc.

WINDING # 34WGR070

Typical performance - not guaranteed values.

0.33 HP 1 PH 60 HZ 1625 RPM 230 V 3414C

TORQUES (LB-FT): PO=2.17 PU=0.709 LR=0.779 LRA=5.37





