

ABB BALDOR RELIANCE III

Customer information packet

IDDRPM21404

40HP, 1750, 460V, RL2162, DPFV, F1

Specifications

Enclosure	DPFV
Frame	RL2162Z
Frame Material	Exposed Laminations
Frequency	60.00 Hz
Output @ Frequency	40.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CCSA US
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Current @ Voltage	52.000 A @ 460.0 V
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Frame Prefix	RL
Heater Indicator	No Heater
High Voltage Full Load Amps	52.0 a
Insulation Class	H
IP Rating	NONE
Motor Standards	NEMA
Mounting Arrangement	F1
Overall Length	23.12 IN
Product Family	General Industrial
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.00
Shaft Diameter	1.875 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Speed	1750 rpm
Starting Method	Full Voltage

Part Detail

Revision	D
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	L0231A
Layout	617202-051
Eff. date	05-21-2026
CD Diagram	422927-001
Poles	04
Leads	
Proprietary	False
Created date	10-21-2021

Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat

Nameplate

000613006MY									
	DUTY	HP	RPM	AMPS	VOLTS	HZ			
	CONT	40	1750		52	460		60	
	CONT	40	2000		52	460		69	
CAT.NO.	IDDRPM21404			SPEC. NO.	R21-A000-0368				
SER.NO				FR	RL2162Z	INSUL	H		
PH.	3	MAX SAFE SPEED			5000	AMB.	40	MIN. AMB.	-25
DESIGN NO.	L0231A	TYPE				ENCL.	DPG-FV		
S.F.	1.00	D.E. BRG.			50BC03JPP30A				
ENCL MOD				O.D.E. BRG.	45BC02JPP30A				
	IP23								

Parts List

Part number	Description	Quantity
WS392793	WS R21-A000-0368	1.000 ea
RA389324	RA R21-A000-0368	1.000 ea
000692000LD	NP	1.000 ea
033775004EA	DRSCR #6-1/4 304 S.S.	4.000 ea
000613006MY	NP-RPMAC INVERTER DUTY	1.000 ea
000692000XM	LABEL QR CODE	1.000 ea
LB1613	LABEL, QR CODE, ADHESIVE LABEL	1.000 ea
422927001	C/D LABEL	1.000 ea
004824007AB	PAINT,XT	0.100 ea
807527202DAE	BRKT,DE,RL210,DPFV	1.000 ea
BP5068BJ01	BRUSH, .187 X .187 X 1.00	1.000 ea
HA4054	SHORT T-DRAIN FITTING, .125" N.P.T.	1.000 ea
HA4054	SHORT T-DRAIN FITTING, .125" N.P.T.	1.000 ea
400638001AB	WASHER SPRING - 210	1.000 ea
036000016DB	HHCS	2.000 ea
036100080KA	M10-1.50X 80MM HXSOCHDCS	3.000 ea
036140001B	METRIC EYEBOLT	2.000 ea
036500010AB	METRIC NUT M10-1.5PLTD400	4.000 ea
036500010AB	METRIC NUT M10-1.5PLTD400	4.000 ea
609830005ACL	STUD FRAME .375X11.38	4.000 ea
BP5248	BP5248	1.000 ea
036600010AB	MFWSH M10 PLATED	8.000 ea
610490001A	16M 2P TENV VER 56C SUPER E, CE	1.000 ea
415000103D	T/LUG #4AWG-1/0AWG W/HOLE FOR .250 BOLT	1.000 ea
036000012JB	M8-1.25 X 12MM HXHDC	3.000 ea
418057256D	GROUND SCREW	1.000 ea
417744401J	GROUND WIRE	1.000 ea
611965001A	WHEEL, BLOWER	1.000 ea
417733004AC	GASK C/BOX	1.000 ea
706310640B	BACKPLATE GASKET C/BOX 706310-637	1.000 ea
609843001K	GASKET HANDHOLE COVER FE	1.000 ea

611917002AN	GASKT RL210 DPFV	1.000 ea
036000020HB	HHCS M6-1.0X20MM PLATED	8.000 ea
032018006CK	HHCS 3/8-16X3/4L PLATED 411409	4.000 ea
000613006NT	NAME PLATE IEC	1.000 ea
418057256F	HHCS M6 12MM ZINCPLAT	1.000 ea
036600009AB	METRIC FLWASH M8 PLATED	3.000 ea
032018004DK	HHCS,DRIP COVER	4.000 ea
418018074A	GROUND LABEL G100 METRIC 160 D.C.	1.000 ea
708528004G	HOUSING, BLOWER	1.000 ea
610409128A	ADAPTER, BLOWER	1.000 ea
410978010C	FLANGE, INLET BLOWER HSG.	1.000 ea
410978019A	SCREEN, INLET FLANGE	1.000 ea
036321020HB	HEXSOCKET FLAT SCREW M	4.000 ea
036620009AB	M8 EXTERNAL LK WASHER	1.000 ea
036620009AB	M8 EXTERNAL LK WASHER	1.000 ea
034017014AB	LCKW 3/8 STD. PLATED	4.000 ea
036000012JB	M8-1.25 X 12MM HXHDC	4.000 ea
706310638A	BACK PLATE FOR 706310-637 WITH 3.12" BOL	1.000 ea
422919192	HHCVR KIT,DC180,DE LOUVERED, S/P	1.000 ea
422919192	HHCVR KIT,DC180,DE LOUVERED, S/P	1.000 ea
423709011A	WASHER	8.000 ea
706310637A	C/BOX, MILL, RPMAC,9X9X4, 375IN^3	1.000 ea
706310641A	LIPPED CBOX LID FOR 706310-642	1.000 ea
706310640A	LID GASKET C/BOX 706310-637	1.000 ea
036010012HB	HHCS T/BOX BRACE	16.000 ea
036000012HB	HHCS M6X12MM LONG PLATED	4.000 ea
706305301A	GUARD, SHAFT	1.000 ea
034180020GA	KEY 1/2X1/2X2-1/2 L	1.000 ea
000640000P	TAG WINDING THERMOST	1.000 ea
004824007CQR	C2 PAINT SYSTEM MEDIUM GRAY CHARCOAL MET	0.100 ea
418018116	WARNING PLATE	1.000 ea
LB1549	LABEL, BLANK 1.375 X 2.250 IMPRINTABLE	1.000 ea
807527224CCB	BRKT,ODE,RL210,GROUND STRAP	1.000 ea

FRAME	RL2162	AMPS	49.26	MAX SAFE SPEED	5000		
HP	40	DUTY	CONT	IM (AMPS)	15.52	R1 .177	X1 .748
BASE SPEED	1750	S.F.	1.0	P.F. @NL / FL	.089/.872	R2 .113	X2 .717
PHASE/HZ	3/60	AMB.°C / INSUL	40/H	WK ² (Lb-Ft ²)	1.99		XM 17.6

RATED FULL LOAD DATA

	RPM	HP	TORQUE LB-FT	FUND VOLTS	FREQ-HZ	AMPS
BASE SPEED	1747	40.0	120	460	60	49.6
MAX SPEED	2007	40.0	105	460	69	48.9
MIN SPEED	0	0	120	26.7	1.78	49.6

LOAD PERFORMANCE AT BASE SPEED

	RPM	HP	TORQUE LB-FT	FUND VOLTS	FREQ-HZ	AMPS
NO LOAD	1800	0	0	460	60	15.3
1/4	1788	10.0	29	460	60	19.4
1/2	1776	20.0	59	460	60	27.6
3/4	1762	30.0	89	460	60	37.7
FULL LOAD	1747	40.0	120	460	60	49.6
0/L	1707	58.6	180	460	60	76.8

REMARKS:
TYPICAL DATA
CORRELATED DATA



DRAWN BY: B. GRANT
CHECKED BY: B. GRANT
APPROVED BY: T. EVON
DATE: 3-7-05


**AC MOTOR
PERFORMANCE
DATA**

L0231A

ISSUE DATE 3-7-05

FRAME	RL2162	AMPS	49.26	MAX SAFE SPEED	5000	(AT BASE RATING, 25°C)			
HP	40	DUTY	CONT	IM (AMPS)	15.52	R1	.177	X1	.748
BASE SPEED	1750	S.F.	1.0	P.F. @NL / FL	.089/.872	R2	.113	X2	.717
PHASE/HZ	3/60	AMB.°C / INSUL	40/H	WK ² (Lb-Ft ²)	1.99			XM	17.6

**CORRELATED DATA
VARIABLE SPEED AC MOTOR CURVES**



TYPICAL DATA, DATA VALID FOR NAMEPLATE SPEED RANGE ONLY




DRAWN BY: B. GRANT
 CHECKED BY: B. GRANT
 APPROVED BY: T. EVON
 DATE: 3-7-05

**AC MOTOR
PERFORMANCE
DATA**

L0231A
 ISSUE DATE: 3-7-05

FRAME		VOLTS		ENCLOSURE		WYE CONN EQ CKT PER PHASE (AT BASE RATING, 25°C)	
RL2162		AMPS	49.26	MAX SAFE SPEED	5000		
HP	40	DUTY	CONT	IM (AMPS)	15.52	R1	.177
BASE SPEED	1750	S.F.	1.0	P.F. @NL / FL	.089/.872	R2	.113
PHASE/HZ	3/60	AMB.°C / INSUL	40/H	WK² (Lb-Ft²)	1.99	X1	.748
						X2	.717
						XM	17.6

**CORRELATED DATA
LOAD PERFORMANCE (CONSTANT V/HZ RANGE)**




TYPICAL DATA, DATA VALID FOR NAMEPLATE SPEED RANGE ONLY



DRAWN BY: B. GRANT
 CHECKED BY: B. GRANT
 APPROVED BY: T. EVON
 DATE: 3-7-05


**AC MOTOR
PERFORMANCE
DATA**

L0231A
 ISSUE DATE: 3-7-05



INDUSTRIAL ALTERNATING CURRENT MOTORS
RPM AC

STEEL, CAST IRON, MILL AND TERMINAL BOARD CONDUIT BOX DIMENSIONS
NEMA FRAMES RL210 thru RL280 and IEC FRAMES RDL132 thru RDL180
NEMA FRAMES FL180 thru FL280 and IEC FRAMES FDL112 thru FDL180



FRAME	TYPE	TERMINAL STRIP	AMPS	C/BOX	Y	TA	T	AA
FL180	STEEL	N	40	706320003A	5.00	1.62	3.00	1.12
FL180	STEEL	Y/N	75	706320003A	6.12	2.35	4.38	1.75/2.00
FL180	STEEL	N	208	706320007A	6.62	2.00	7.00	2.50/3.00
FL180	CAST IRON	Y/N	208	706320004C	6.75	2.50	4.38	1.0/1.75
FL180 & FDL11	MILL	Y	100	706310056A	7.75	2.30	4.40	PG29/PG16

FL210 & RL210	STEEL	N	61	075452000B	6.34	2.00	4.12	1.75
FL210 & RL210	STEEL	N	121	075452001A	7.69	2.38	5.25	1.94
FL210 & RL210	STEEL	N	306	706320016A	9.00	4.12	8.44	4.59
FL210 & RL210	CAST IRON	N	110	075460052B	7.25	2.50	5.25	1.5 TAP
FL210 & RL210	MILL	Y	100	706310229A	7.75	2.30	4.40	PG29/PG16
FL210 & RL210	MILL	Y	160	706310056A	9.00	3.06	5.40	PG36/PG16
FL210 & RL210	MILL	Y/N	235	706310056B	11.42	4.00	6.72	2.50

FL250 & RL250	STEEL	N	61	075452000B	6.34	2.00	4.12	1.75
FL250 & RL250	STEEL	N	121	075452001A	7.69	2.38	5.25	1.94
FL250 & RL250	STEEL	N	306	706320016A	9.00	4.12	8.44	4.59
FL250 & RL250	CAST IRON	N	110	075460052B	7.25	2.50	5.25	1.5 TAP
FL250 & RL250	CAST IRON	N	210	706320013A	10.50	4.88	9.00	4.0 TAP
FL250 & RL250	MILL	Y	100	706310229A	7.75	2.30	4.40	PG29/PG16
FL250 & RL250	MILL	Y	160	706310056B	9.00	3.06	5.40	PG36/PG16
FL250 & RL250	MILL	Y/N	235	706310057A	11.42	4.00	6.72	2.50
FL250 & RL250	MILL	Y	235	706310063B	14.39	7.43	12.15	BLANK

FL280 & RL280	STEEL	N	160	706320029A	7.25	3.50	7.06	2.50
FL280 & RL280	STEEL	N	306	706320016A	9.00	4.12	8.44	4.59
FL280 & RL280	STEEL	N	500	702658001C	14.62	7.56	12.70	5.00
FL280 & RL280	CAST IRON	N	140	706320012B	9.25	4.81	8.56	3.0 TAP
FL280 & RL280	CAST IRON	N	210	706320013A	10.50	4.88	9.00	4.0 TAP
FL280 & RL280	CAST IRON	N	510	706320014D	15.00	7.56	12.81	5.0 TAP
FL280 & RL280	MILL	Y	100	706310056A	7.75	2.30	4.40	PG29/PG16
FL280 & RL280	MILL	Y	160	706310056B	9.00	3.06	5.40	PG36/PG16
FL280 & RL280	MILL	Y/N	235	706310057A	11.42	4.00	6.72	2.50
FL280 & RL280	MILL	Y	400	706310063B	14.39	7.43	12.15	BLANK

FRAME SIZE	XAB	XX	XY	PART NUMBER	FRAME SIZE	XAB	XX	XY	PART NUMBER
FL210/RL210/FL112	7.38	4.25	4.25	602007-26-A	FL210/RL210/FL112	10.88	8.00	8.00	706310-3-B
FL250/RL250/FL160	8.44	4.25	4.25	602007-26-A	FL250/RL250/FL160	11.88	8.00	8.00	706310-3-B
FL280/RL280/FL280/180	9.12	4.25	4.25	602007-26-A	FL280/RL280/FL280/180	12.62	8.00	8.00	706310-3-B

(1) 1/4" CONDUIT.
(2) 1/4" PIPE TAP.
(3) CUSTOMER TO PROVIDE HOLE PER CONDUIT.
(4) 2" DIA. OR 1" DIA. DIA. OR 1" DIA. DIA.

TERMINAL BOX CAN BE ROTATED FOR LEAD OUTLET AT TOP, SIDES OR BOTTOM.
TERMINAL BOX LOCATED ON OPPOSITE SIDE WHEN F-2, V-1, V-4, V-5, V-7.
OR C-1 MOUNTING IS SPECIFIED. BOX LOCATED ON TOP WHEN SPECIFIED.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.


REV. DESC: ADD 706310-637 & 639 BOX	VERSION: 06	TDR: 000001180260
REV. LTR: F	REVISED: 11:08:56 10/26/2021	BY: RCGRWM
FILE: \\RGG\00003\692		
MTL: -		

BALDOR - RELIANCE®

DIM SHT NEMA RL210-RL280 FL180-FL280 IEC RDL132-RDL180

SH 1 of 1

422927-001



NOTE:
DATA TO BE SIZED
SO THAT IT FITS INTO
MATERIAL DECAL
DIMENSIONS. MAKE
LETTERS & NUMBERS
AS LARGE AS POSSIBLE.

MATERIAL: CERAMATIC DGF-P4
 PERMA GRIP ADHESIVE

ALL LETTERS, NUMBERS
AND LINES TO BE BLACK
ON WHITE BACKGROUND.

422927-001

REV. DESC: CHANGE BACKGROUND COLOR FROM GOLD TO WHITE		
REV. LTR: B	VERSION: 02	TDR: 000000788708
FILE: \RGG\00000\203	REVISED: 08:09:29 03/04/2013	
MTL: -	BY: RGGWT	

BALDOR

EXTERNAL CONNECTION LABEL

SH 1 of 1