

# ABB BALDOR RELIANCE III

---

## Customer information packet

### IDM3661T-5

3HP, 1755RPM, 3PH, 60HZ, 184TC, 0632M, TEBC, F1

Class - None

Division - Not Applicable

**Specifications**

|                                |                           |
|--------------------------------|---------------------------|
| Enclosure                      | TEBC                      |
| Frame                          | 184TC                     |
| Frame Material                 | Iron                      |
| Frequency                      | 60.00 Hz                  |
| Haz Area Class and Group       | None                      |
| Haz Area Division              | Not Applicable            |
| Motor Letter Type              | Three Phase               |
| Output @ Frequency             | 3.000 HP @ 60 HZ          |
| Phase                          | 3                         |
| Synchronous Speed @ Frequency  | 1800 RPM @ 60 HZ          |
| Voltage @ Frequency            | 575.0 V @ 60 HZ           |
| Agency Approvals               | UR<br>CSA                 |
| Ambient Temperature            | 40 °C                     |
| Auxiliary Box                  | NO AUXILLARY BOX          |
| Auxiliary Box Lead Termination | None                      |
| Base Indicator                 | Rigid                     |
| Bearing Grease Type            | Polyrex EM (-20F +300F)   |
| Blower                         | 115V 1-Phase EXT          |
| Current @ Voltage              | 3.300 A @ 575.0 V         |
| Design Code                    | B                         |
| Drip Cover                     | No Drip Cover             |
| Duty Rating                    | CONT                      |
| Efficiency @ 100% Load         | 89.5 %                    |
| Electrically Isolated Bearing  | Not Electrically Isolated |
| Feedback Device                | NO FEEDBACK               |
| Front Face Code                | Encoder/Feedback Device   |
| Front Shaft Indicator          | None                      |
| Heater Indicator               | No Heater                 |
| High Voltage Full Load Amps    | 3.3 a                     |
| Insulation Class               | H                         |
| Inverter Code                  | Inverter Duty             |

**Part Detail**

|              |            |
|--------------|------------|
| Revision     | J          |
| Type         | AC         |
| Mech. spec.  | 06F552     |
| Base         |            |
| Status       | PRD/A      |
| Elec. spec.  | 06WGX319   |
| Layout       | 06LYF552   |
| Eff. date    | 09-30-2025 |
| CD Diagram   | CD0006     |
| Poles        | 04         |
| Leads        | 3#16       |
| Proprietary  | False      |
| Created date | 10-10-2011 |

|                                      |                                       |
|--------------------------------------|---------------------------------------|
| <b>KVA Code</b>                      | <b>J</b>                              |
| <b>Lifting Lugs</b>                  | <b>Standard Lifting Lugs</b>          |
| <b>Locked Bearing Indicator</b>      | <b>Locked Bearing</b>                 |
| <b>Max Speed</b>                     | <b>6000 rpm</b>                       |
| <b>Motor Lead Exit</b>               | <b>Ko Box</b>                         |
| <b>Motor Lead Quantity/Wire Size</b> | <b>3 @ 16 AWG</b>                     |
| <b>Motor Lead Termination</b>        | <b>Flying Leads</b>                   |
| <b>Motor Standards</b>               | <b>NEMA</b>                           |
| <b>Motor Type</b>                    | <b>0632M</b>                          |
| <b>Mounting Arrangement</b>          | <b>F1</b>                             |
| <b>Number of Poles</b>               | <b>4</b>                              |
| <b>Overall Length</b>                | <b>21.71 IN</b>                       |
| <b>Power Factor</b>                  | <b>77</b>                             |
| <b>Product Family</b>                | <b>General Purpose</b>                |
| <b>Pulley End Bearing Type</b>       | <b>Ball</b>                           |
| <b>Pulley Face Code</b>              | <b>C-Face</b>                         |
| <b>Pulley Shaft Indicator</b>        | <b>Standard</b>                       |
| <b>Rodent Screen</b>                 | <b>None</b>                           |
| <b>Service Factor</b>                | <b>1.00</b>                           |
| <b>Shaft Diameter</b>                | <b>1.125 IN</b>                       |
| <b>Shaft Extension Location</b>      | <b>Pulley End</b>                     |
| <b>Shaft Ground Indicator</b>        | <b>No Shaft Grounding</b>             |
| <b>Shaft Rotation</b>                | <b>Reversible: Connected Standard</b> |
| <b>Shaft Slinger Indicator</b>       | <b>No Slinger</b>                     |
| <b>Speed</b>                         | <b>1755 rpm</b>                       |
| <b>Speed Code</b>                    | <b>Single Speed</b>                   |
| <b>Starting Method</b>               | <b>Direct on line</b>                 |
| <b>Thermal Device - Bearing</b>      | <b>None</b>                           |
| <b>Thermal Device - Winding</b>      | <b>Normally Closed Thermostat</b>     |
| <b>Vibration Sensor Indicator</b>    | <b>No Vibration Sensor</b>            |
| <b>Winding Thermal 1</b>             | <b>None</b>                           |
| <b>Winding Thermal 2</b>             | <b>None</b>                           |

**Nameplate**

| NP4009L        |              |   |      |            |      |       |  |      |    |     |      |     |
|----------------|--------------|---|------|------------|------|-------|--|------|----|-----|------|-----|
| CAT.NO.        | IDM3661T-5   |   |      |            |      |       |  |      |    |     |      |     |
| SPEC.          | 06F552X319G1 |   |      |            |      |       |  |      |    |     |      |     |
| FRAME          | 184TC        |   |      | H.P.       | 3 TE |       |  |      |    |     |      |     |
| VOLTS          | 575          |   |      |            |      |       |  |      |    |     |      |     |
| MAG. CUR.      | 1.7          |   |      | F.L. AMPS  |      |       |  | 3.3  |    |     |      |     |
| R.P.M.         | 1755         |   |      | R.P.M. MAX |      |       |  | 6000 |    |     |      |     |
| HZ.            | 60           |   | PH.  | 3          |      | CLASS |  | H    |    |     |      |     |
| SER.F.         | 1.00         |   | DES. | B          |      | SL HZ |  |      |    | 1.5 |      |     |
| NEMA NOM. EFF. | 89.5         |   | WK2  | 0.3        |      |       |  |      |    |     |      |     |
| BLOWER         |              | V | 115  |            | PH   | 1     |  | HZ   | 60 |     | AMPS | .26 |
| RATING         | 40C AMB-CONT |   |      |            |      |       |  |      |    |     |      |     |
| DE             | 6206         |   | ODE  | 6205       |      |       |  |      |    |     |      |     |
| CC             | 010A         |   | SN   |            |      |       |  |      |    |     |      |     |
|                | 1000:1 CT/VT |   |      |            |      |       |  |      |    |     |      |     |

**Parts List**

| Part number | Description                              | Quantity |
|-------------|------------------------------------------|----------|
| SA232419    | SA 06F552X319G1                          | 1.000 ea |
| RA219425    | RA 06F552X319G1                          | 1.000 ea |
| HW3201A05   | 3/8-16 EYEBOLT                           | 1.000 ea |
| 06CB3000    | BALDOR CONDUIT BOX CAST                  | 1.000 ea |
| 06GS1000    | GASKET,CONDUIT BOX                       | 1.000 ea |
| 51XW2520A12 | SCREW, HEX SER SLT HD, ZN, 1/4-20 X .75  | 2.000 ea |
| 11XW1032G06 | 10-32 X .38, TAPTITE II, HEX WSHR SLTD U | 1.000 ea |
| HW3001B01   | BRASS CUP WASHER, FOR #10 SCREW          | 1.000 ea |
| 36EP1101B41 | FR TEBC 205 BRG W/ GRSR & THRU-SHAFT ENC | 1.000 ea |
| HW4500A01   | 1641B(ALEMITE)400 UNIV, GREASE FITT      | 1.000 ea |
| HW5100A05   | WVY WSHR F/205 & 304 BRGS                | 1.000 ea |
| 36PE1300A01 | PU ENDPLATE, MACH                        | 1.000 ea |
| HW4500A01   | 1641B(ALEMITE)400 UNIV, GREASE FITT      | 1.000 ea |
| 10XN2520A26 | 1/4-20X 1 5/8 HEX HD                     | 4.000 ea |
| HW1001A25   | LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I | 4.000 ea |
| HA3101A34   | THRUBOLT- 1/4-20 X 10.375                | 4.000 ea |
| 10XN2520A08 | 1/4-20X1/2 HEX HEAD CAP                  | 1.000 ea |
| HA3218A05   | M/FE STANDOFF UNIC#SX1043.25-20 .38 HEX  | 3.000 ea |
| 10XN2520A06 | 1/4 20X3/8 HX HD CAP                     | 3.000 ea |
| HW1001A25   | LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I | 3.000 ea |
| 06CB3500    | BALDOR CONDUIT BOX LID                   | 1.000 ea |
| 06GS1001    | BALDOR CONDUIT BOX GASKET                | 1.000 ea |
| 51XW2520A12 | .25-20 X .75, TAPTITE II, HEX WSHR SLTD  | 2.000 ea |
| HA1005A03SP | SLINGER, OD 1.750, ID .938, 205 BRG      | 1.000 ea |
| HW2501E16   | KEY, 1/4 SQ X 1.750                      | 1.000 ea |
| HA7000A02   | KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA  | 1.000 ea |
| MJ5004A05   | #242-21 LOCTITE GENERAL PURPOSE MED. STR | 0.005 ea |
| 85XU0407S04 | 4X1/4 U DRIVE PIN STAINLESS              | 2.000 ea |
| LB1624      | COMBINED WARNING LABEL, ISO/ANSI PICTOGR | 1.000 ea |
| LB1009N     | LABEL,ROTATION DIRECTION (ON ROLLS)      | 1.000 ea |
| MJ1000A02   | GREASE, POLYREX EM EXXON                 | 0.050 lb |

|             |                                         |          |
|-------------|-----------------------------------------|----------|
| 06FH5001A02 | BLOWER ASSY. 06FH4001, EF0001           | 1.000 ea |
| MG1050G01   | CELEROL MEDIUM CHARCOAL METALLIC GRAY   | 0.028 ga |
| LC0035B01   | 1PH, SV, FIX, 2 LEAD                    | 1.000 ea |
| LC0006      | CONNECTION LABEL                        | 1.000 ea |
| NP4009L     | SS INV UL CSA-EEV CC NEMA PREM          | 1.000 ea |
| G0PA1000    | PKG GRP, PRINT PK1026A06                | 1.000 ea |
| MN416A01    | TAG-INSTAL-MAINT no wire (2500 bx)11/25 | 1.000 ea |



**AC Induction Motor Performance Data**  
 Record # 36484  
 Typical performance - not guaranteed values

|                          |                    |                        |
|--------------------------|--------------------|------------------------|
| <b>Winding:</b> 06WGX319 | <b>Type:</b> 0632M | <b>Enclosure:</b> TEBC |
|--------------------------|--------------------|------------------------|

| Nameplate Data    |              |          |    | General Characteristics at 575 V, 60 Hz:<br>Single Volt Motor |            |
|-------------------|--------------|----------|----|---------------------------------------------------------------|------------|
| Rated Output (HP) | 3            |          |    | Full Load Torque                                              | 9.05 LB-FT |
| Volts             | 575          |          |    | Start Configuration                                           | DOL        |
| Full Load Amps    | 3.3          |          |    | Break Down Torque                                             | 33 LB-FT   |
| R.P.M.            | 1755         |          |    | Pull-Up Torque                                                | 18.2 LB-FT |
| Hz                | 60           | Phase    | 3  | Locked-rotor Torque                                           | 20.3 LB-FT |
| NEMA Design Code  | B            | KVA Code | J  | Starting Current                                              | 23.8 Amps  |
| Service Factor    | 1            |          |    | No-load Current                                               | 1.7 Amps   |
| NEMA Nom. Eff.    | 89.5         | P.F.     | 77 | Line-line Res. @ 25°C.                                        | 6.22 Ohms  |
| Rating - Duty     | 40C AMB-CONT |          |    | Temp. Rise @ Rated Load                                       | 35°C       |
| S.F. Amps         |              |          |    | Temp. Rise @ S.F. Load                                        |            |


Load Characteristics at 575 Volts, 60 Hz, 3 HP

| % of Rated Load | 25   | 50   | 75   | 100  | 125  | 150  | S.F. |
|-----------------|------|------|------|------|------|------|------|
| Power Factor    | 38   | 59   | 71   | 77   | 81   | 83   |      |
| Efficiency      | 83.1 | 88.4 | 89.8 | 89.6 | 89.1 | 87.7 |      |
| Speed           | 1790 | 1779 | 1769 | 1757 | 1744 | 1730 |      |
| Line Amperes    | 1.86 | 2.22 | 2.71 | 3.27 | 3.92 | 4.69 |      |


Baldor Electric Company Fort Smith, Arkansas



|            |            |                          |      |                                       |       |                                                   |       |    |         |
|------------|------------|--------------------------|------|---------------------------------------|-------|---------------------------------------------------|-------|----|---------|
| Catalog    | IDM3661T-5 | NP VOLTS                 | 575  | ENCLOSURE                             | TEBC  | WYE CONN EQ CKT OHMS PER PHASE (BASE RATING, 20C) |       |    |         |
| FRAME      | 184TC      | NP AMPS                  | 3.3  | Base Volts                            | 575   | R1                                                | 3.040 | X1 | 8.588   |
| HP         | 3 HP       | DUTY                     | Cont | Base AMPS                             | 3.27  | R2                                                | 2.150 | X2 | 7.189   |
| BASE SPEED | 1800       | MAX SAFE RPM             | 6000 | Slip Hz                               | 1.43  |                                                   |       | XM | 187.435 |
| PHASE/HZ   | 3/60       | AMB <sup>0</sup> C/INSUL | 40/H | WK <sup>2</sup> (lb-ft <sup>2</sup> ) | 0.298 |                                                   |       |    |         |



Remarks: Calculated Data



**BALDOR**  
A MEMBER OF THE ABB GROUP

DR BY ENR  
CK BY  
APP BY ENR  
DATE 2/27/2013

A-C MOTOR  
PERFORMANCE CURVES

**06F552X319G1**

ISSUE DATE 2/27/2013



CD0006


**NOTES:**

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10: 24: 49 02/19/2019

BY: ENBRIRO

MTL: —


**BALDOR - RELIANCE®**

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1