

ABB BALDOR RELIANCE III

Customer information packet

IDM4117T

64M 6P TEBC HOR 326T INV DUTY T'STATS

Class - None

Division - Not Applicable

Specifications

Enclosure	TEBC
Frame	326T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	30.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	BLOWER
Current @ Voltage	39.000 A @ 460.0 V 78.000 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	39.0 a
Insulation Class	H

Part Detail

Revision	E
Type	AC
Mech. spec.	12T107
Base	
Status	PRD/A
Elec. spec.	12WGY812
Layout	12LYT107
Eff. date	08-18-2025
CD Diagram	CD0005
Poles	06
Leads	9#8
Proprietary	False
Created date	03-19-2019

Inverter Code	Inverter Duty
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	3900 rpm
Motor Lead Quantity/Wire Size	9 @ 8 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1264M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	36.92 IN
Power Factor	78
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.00
Shaft Diameter	2.125 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1180 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1163L									
CAT NO	IDM4117T								
SPEC.	12T107Y812G1								
FRAME	326T		HP	30	TE				
VOLTS	230/460								
MAG CUR	34.4/17.2			FLA	78/39				
RPM	1180			RPM MAX	3900				
HZ	60		PH	3		CLASS	H		
SER.F.	1.00		DES	A		SL HZ	1		
NEMA-NOM-EFF	93		WK2	12.2					
BLWR V		PH		HZ		A			
RATING	40C AMB-CONT								
DE BRG	6312		ODE BRG	6311					
CC	010A	SN							
	1000:1 CT, 1000:1 VT								

Parts List

Part number	Description	Quantity
SA371437	SA 12T107Y812G1	1.000 ea
RA361123	RA 12T107Y812G1	1.000 ea
10CB3001	CONDUIT BOX CAST W/2.500 LEAD HOLE	1.000 ea
09GS1000	GASKET-CONDUIT BOX, 1/16 THICK LEXIDE	1.000 ea
10XN3118K12	5/16-18 X .75 GRADE 5, ZINC PLATED	4.000 ea
HW1001A31	LOCKWASHER 5/16, ZINC PLT.591 OD, .319 I	4.000 ea
WD1000B25	GND LUG, BURNDY L125HP OR T&B L125HP-BB	1.000 ea
19XW3118G08	.31-18X.50,HEX WSHR HD,TAPTITE 2,GREEN	1.000 ea
12EP1107A55	FR ENDPLATE, W/THRU SHAFT ENCODER DESIGN	1.000 ea
10XN5013K32	1/2-13 X 2.00" HEX HD GRD 5 (20051)	4.000 ea
HW1001A50	LOCKWASHER 1/2, ZINC PLT,.879 OD, .509 I	4.000 ea
HA1005A26	SLINGER, OD 3.00, ID 1.75, 309 BRG	1.000 ea
10XN2520K12	1/4-20 X.75 GRD 5	1.000 ea
HW1001A25	LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I	1.000 ea
HW5100A13	W4627-047 WVY WSHR	1.000 ea
10XN3118K40	5/16-18 X 2.25" HEX HD, GRADE 5	2.000 ea
HW1001A31	LOCKWASHER 5/16, ZINC PLT.591 OD, .319 I	2.000 ea
10XN3118K40	5/16-18 X 2.75" HEX HD, GRADE 5	4.000 ea
HW1001A31	LOCKWASHER 5/16, ZINC PLT.591 OD, .319 I	4.000 ea
12EP1106A01	PU ENDPLATE, MACH	1.000 ea
10XN5013K28	1/2-13 X 1.75 HEX HEAD MACH SCREW,GRAD	4.000 ea
HW1001A50	LOCKWASHER 1/2, ZINC PLT,.879 OD, .509 I	4.000 ea
HA1005A06	SLINGER, OD 3.62, ID 2.15	1.000 ea
10CB3500SP	CONDUIT BOX LID, CAST	1.000 ea
10GS1000	GASKET, CONDUIT BOX LID	1.000 ea
51XW2520A12	.25-20 X .75, TAPTITE II, HEX WSHR SLTD	4.000 ea
HW2501H33	KEY, 1/2 SQ X 3.875	1.000 ea
HW4500A21	1618BALEMITE FITTING 825 UNIVERSAL	1.000 ea
HA4017A01	1/8 X 4 GREASE EXT (F/S)	1.000 ea
HA4051A00	PLASTIC CAP FOR GREASE FITTING	1.000 ea
HW4500A17	317400 ALEMITE GREASE RELIEF	1.000 ea

HA4054	SHORT T-DRAIN FITTING, .125" N.P.T.	1.000 ea
MJ1000A02	GREASE, POLYREX EM EXXON	0.200 lb
HW4500A03	GREASE FITTING, .125 NPT 1610(ALEMITE) 8	1.000 ea
HW4500A17	317400 ALEMITE GREASE RELIEF	1.000 ea
HA4051A00	PLASTIC CAP FOR GREASE FITTING	1.000 ea
HA4054	SHORT T-DRAIN FITTING, .125" N.P.T.	1.000 ea
WD4101A08	STIMPSON #D3557,1.188 DIA. HOLE PLUG	1.000 ea
BLWM12-F	312 BLOWER ASSY. (12FH4010 & EF5102)	1.000 ea
LB1624	COMBINED WARNING LABEL, ISO/ANSI PICTOGR	1.000 ea
MG1050G01	CELEROL MEDIUM CHARCOAL METALLIC GRAY	0.125 ga
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
LC0005E01	SPL CONN.DIA./WARN.LABEL(LC0005/LB1119)	1.000 ea
NP1163L	ALUM INV UL CSA CC	1.000 ea
10PA1010	PACKAGING GROUP, PRINT PK1151A06	1.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
PE-0000013	ZRTG PE ASSEMBLY	1.000 ea

NP VOLTS	230/460	MAX SAFE RPM	3900	WYE CONN EQ CKT OHMS PER PHASE (BASE RATING, 20C)			
NP AMPS	78/39	Base Volt	460	R1	0.118	X1	0.692
HP	30HP	NL AMPS	17.2	R2	0.086	X2	0.688
BASE SPEED	1180	Slips (Hz)	0.85			XM	14.900
PHASE/HZ	3/60	WK ² (lb-ft ²)	12.2				

Rated Full Load Data

	RPM	HP	Torque	Volts	Freq-Hz	Amps
Base Speed	1183	30.0	133.0	460	60	38.7
Max Speed	1774	30.0	88.7	460	90	36.7
Min Speed	0	0.0	133.0	20.98	0.85	38.7

Load Performance at Base Speed

	RPM	HP	Torque	Volts	Freq-Hz	Amps
No Load	1199	0.0	0.0	460	60	17.2
1/4	1197	7.6	33.3	460	60	19.2
1/2	1192	15.1	66.5	460	60	24.1
3/4	1188	22.6	100.0	460	60	31.0
Full Load	1183	30.0	133.0	460	60	38.7
O/L	1165	59.9	270.0	460	60	76.6

Blower Data	Volts	Ph/HZ	FL Amps	LR Amps	Frame	CFM

Remarks: Calculated Data
Vector PWM Inverter Duty



DR BY BR
CK BY
APP BY BR
DATE 3/28/2017

A-C MOTOR
PERFORMANCE
CURVES
12WGY812


NP VOLTS 230/460
NP AMPS 78/39
HP 30HP
BASE SPEED 1180
PHASE/HZ 3/60

MAX SAFE RPM 3900
Base Volt 460
NL AMPS 17.2
Slips (Hz) 0.85
WK2 (lb-ft2) 12.2

WYE CONN EQ CKT OHMS PER PHASE (BASE RATING, 20C)

R1	0.118	X1	0.692
R2	0.086	X2	0.688
		XM	14.900

Vector PWM Inverter Duty
Variable Speed AC Motor Curves



Calculated Data

Data Valid For Nameplate Speed Range only




DR BY BR
CK BY
APP BY BR
DATE 3/28/2017

A-C MOTOR
PERFORMANCE
CURVES

12WGY812

NP VOLTS	230/460	MAX SAFE RPM	3900	WYE CONN EQ CKT OHMS PER PHASE (BASE RATING, 20C)			
NP AMPS	78/39	Base Volt	460	R1	0.118	X1	0.692
HP	30HP	NL AMPS	17.2	R2	0.086	X2	0.688
BASE SPEED	1180	Slips (Hz)	0.85			XM	14.900
PHASE/HZ	3/60	WK2 (lb-ft2)	12.2				

Vector PWM Inverter Duty
Variable Speed AC Motor Curves




Calculated Data

Data Valid For Nameplate Speed Range only






DR BY BR
CK BY
APP BY BR
DATE 3/28/2017

A-C MOTOR
PERFORMANCE
CURVES
12WGY812



CD0005



- NOTES:
- 1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
 - 4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: E	BY: JLP	REVISED: 01/19/99 10:15	TDR: 0171435
S00000		FILE: AAA00005140	MDL: -
		MTL: -	

BALDOR ELECTRIC Co.

3PH, DV, 9 LEADS

CD0005