

ABB BALDOR RELIANCE III

Customer information packet

IDNM3661T

3HP, 1760RPM, 3PH, 60HZ, 184TC, 0636M, TENV, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	184TC
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.300 A @ 460.0 V 8.600 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Encoder/Feedback Device
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	4.3 a

Part Detail

Revision	G
Type	AC
Mech. spec.	06F551
Base	
Status	PRD/A
Elec. spec.	06WGX370
Layout	06LYF551
Eff. date	06-05-2026
CD Diagram	CD0005
Poles	04
Leads	9#16
Proprietary	False
Created date	04-03-2017

Insulation Class	H
Inverter Code	Inverter Duty
KVA Code	L
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	6000 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0636M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	17.21 IN
Power Factor	73
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1760 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP4009L									
CAT.NO.	IDNM3661T								
SPEC.	06F551X370G2								
FRAME	184TC		H.P.	3 TE					
VOLTS	230/460								
MAG. CUR.	4.8/2.4			F.L. AMPS			8.6/4.3		
R.P.M.	1760		R.P.M. MAX			6000			
HZ.	60		PH.	3	CLASS		H		
SER.F.	1.00		DES.	A	SL HZ		1.2		
NEMA NOM. EFF.	89.5		WK2	0.372					
BLOWER		V		PH		HZ		AMPS	
RATING	40C AMB-CONT								
DE	6206		ODE	6205					
CC	010A	SN							
	1000:1 CT/VT								

Parts List

Part number	Description	Quantity
SA336769	SA 06F551X370G2	1.000 ea
RA325021	RA 06F551X370G2	1.000 ea
HW3201A05	3/8-16 EYEBOLT	1.000 ea
06CB3000	BALDOR CONDUIT BOX CAST	1.000 ea
06GS1000	GASKET,CONDUIT BOX	1.000 ea
51XW2520A12	SCREW, HEX SER SLT HD, ZN, 1/4-20 X .75	2.000 ea
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 ea
HW3001B01	BRASS CUP WASHER, FOR #10 SCREW	1.000 ea
36EP1101B70	FR TENV 205 BRG W/ GRSR & THRU-SHAFT ENC	1.000 ea
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 ea
HW5100A05	WVY WSHR F/205 & 304 BRGS	1.000 ea
36PE1300A01	PU ENDPLATE, MACH	1.000 ea
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 ea
10XN2520A26	1/4-20X 1 5/8 HEX HD	4.000 ea
HW1001A25	LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I	4.000 ea
HA3101A34	THRUBOLT- 1/4-20 X 10.375	4.000 ea
35FH4801G	THRU-SHAFT ENCODER COVER INV/VECTOR F1 &	1.000 ea
WD4129	1.50 X 1.50 GRAY SNAP IN PLUG PROMOULD #	2.000 ea
10XN2520A08	1/4-20X1/2 HEX HEAD CAP	4.000 ea
10XN2520A08	1/4-20X1/2 HEX HEAD CAP	1.000 ea
06CB3500	BALDOR CONDUIT BOX LID	1.000 ea
06GS1001	BALDOR CONDUIT BOX GASKET	1.000 ea
51XW2520A12	.25-20 X .75, TAPTITE II, HEX WSHR SLTD	2.000 ea
HW2501E16	KEY, 1/4 SQ X 1.750	1.000 ea
HA7000A02	KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA	1.000 ea
MJ5004A05	#242-21 LOCTITE GENERAL PURPOSE MED. STR	0.005 ea
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
LB1624	COMBINED WARNING LABEL, ISO/ANSI PICTOGR	1.000 ea
MJ1000A02	GREASE, POLYREX EM EXXON	0.050 lb
MG1050G01	CELEROL MEDIUM CHARCOAL METALLIC GRAY	0.028 ga
LC0145B01	CONNECTION LABEL	1.000 ea

NP4009L	SS INV UL CSA-EEV CC NEMA PREM	1.000 ea
36PA1001	PKG GRP, PRINT PK1017A07	1.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea

NP VOLTS	230/460	Base Volt	460	WYE CONN EQ CKT OHMS PER PHASE (BASE RATING, 20C)			
NP AMPS	8.6/4.3	NL AMPS	2.45	R1	1.890	X1	5.040
HP	3	Slip (HZ)	1.17	R2	1.340	X2	4.290
BASE SPEED	1765	WK ² (lb-ft ²)	0.335			XM	113.000
PHASE/HZ	3/60						

Rated Full Load Data

	RPM	HP	Torque	Volts	Freq-Hz	Amps
Base Speed	1765	3.0	9.0	460	60	4.3
Max Speed	3528	3.0	4.5	460	120	3.8
CT Min Speed	1.765	0.003	9.0	0.46	0.06	4.3

Load Performance at Base Speed

	RPM	HP	Torque	Volts	Freq-Hz	Amps
No Load	1799	0.0	0.0	460	60	2.5
1/4	1791	0.8	2.3	460	60	2.7
1/2	1783	1.5	4.5	460	60	3.0
3/4	1774	2.3	6.7	460	60	3.6
Full Load	1765	3.0	9.0	460	60	4.3
O/L	1765	3.0	9.0	460	60	4.3

Blower Data

Volts	Ph/Hz	FL Amps	LR Amps	Frame	CFM

Remarks: Calculated Data

BALDOR • RELIANCE

DR BY USJIJON
CK BY CD
APP BY USJIJON
DATE 11/1/2024
**A-C MOTOR
PERFORMANCE
CURVES**
06WGX370

Record: 66036


NP VOLTS 230/460
NP AMPS 8.6/4.3
HP 3
BASE SPEED 1765
PHASE/HZ 3/60

Base Volt 460
NL AMPS 2.45
Slip (HZ) 1.17
WK² (lb-ft²) 0.335

WYE CONN EQ CKT OHMS PER PHASE (BASE RATING, 20C)

R1	1.890	X1	5.040
R2	1.340	X2	4.290
		XM	113.000

Variable Speed AC Motor Curves



Calculated Data

Data Valid For Nameplate Speed Range only

BALDOR • RELIANCE

DR BY USJIJON
CK BY CD
APP BY USJIJON
DATE 11/1/2024


**A-C MOTOR
PERFORMANCE
CURVES**

06WGX370

Record: 66036

NP VOLTS	230/460	0	0	WYE CONN EQ CKT OHMS PER PHASE (BASE RATING, 20C)			
NP AMPS	8.6/4.3	Base Volt	460	R1	1.890	X1	5.040
HP	3	NL AMPS	2.45	R2	1.340	X2	4.290
BASE SPEED	1765	Slip (HZ)	1.17			XM	113.000
PHASE/HZ	3/60	WK2 (lb-ft2)	0.335				

Vector PWM Inverter Duty
Variable Speed AC Motor Curves



Calculated Data

Data Valid For Nameplate Speed Range only

BALDOR • RELIANCE

DR BY USJIJON
 CK BY CD
 APP BY USJIJON
 DATE 11/1/2024

**A-C MOTOR
PERFORMANCE
CURVES**

06WGX370

Record: 66036

