ABB BALDOR RELIANCE

Customer information packet

IDVSM4410T-4

125HP, 1790-2685RPM, 3PH, 60-90HZ, 444T, A440
Class - None
Division - Not Applicable

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
10/5/2026 10:46:28 PM

Specifications

Enclosure	TEFC
Frame	444T
Frame Material	Iron
Frequency	60.00 Hz
	90.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	125.000 HP @ 90 HZ
	125.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
	460.0 V @ 90 HZ
Agency Approvals	CCSA US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Constant Torque Speed Range	1000:1
Current @ Voltage	140.000 A @ 460.0 V
	150.000 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Heater Indicator	No Heater
High Voltage Full Load Amps	140.0 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	M
Lifting Lugs	Standard Lifting Lugs

Part Detail

Revision	L
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A44WG0911
Layout	617435-164
Eff. date	09-25-2025
CD Diagram	416820-036
Poles	04
Leads	3#1/0
Proprietary	False
Created date	08-23-2012

Max Speed	3600 rpm
Motor Lead Quantity/Wire Size	3 @ 1/0 AWG
Motor Standards	NEMA
Motor Type	A44062M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	44.75 IN
Product Family	Other
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.00
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1790 rpm
	2685 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat

Nameplate

000613007HV

CAT NO	IDVSM4410T-4		**SPEC NO.**	P44G4008								
SER.NO.			**FRAME**	444T								
	HP	**RPM**	**VOLTS**	**AMPS**	**HZ**	**TYPE**	P					
BASE	125	1790	460	150	60	**SF**	1.00					
MAX	125	2685	460	140	90	**INSUL.CLASS**	F					
DRIVE END BEARING	90BC03J30X		**CONSTANT TORQUE**		**DUTY**	CONT	**AMB**	40				
OPP D.E. BEARING	6318C3VL0241		1000:1	**ENCL**	TEFC	**PHASE**	3					
DESIGN NO.	A44WG0911-R003		**FLUX AMPS**	62.1		**VPWM INVERTER READY**						
MAX SPEED/RPM	3600		**OVERTEMP PROT**	2	**WK2**	40.0	**POLES**	4	**WEIGHT**			

Parts List

Part number	Description	Quantity
SA254356	SA P44G4008	1.000 ea
RA241164	RA P44G4008	1.000 ea
421948051	LABEL, MYLAR	1.000 ea
000613006PU	N/P (RELEASE QTY 10,000) UL CSA LABEL	1.000 ea
000692000VD	LABEL WARNING	1.000 ea
000613007HV	N/P BALDOR VSMASTER, CURUS	1.000 ea
412118006A	DRAIN	2.000 ea
089490099A	G28 BRKT 089490098WCA KB	1.000 ea
415072001B	CLAMP	1.000 ea
083199082A	G28 Fan cover machining	1.000 ea
034180014DA	KEY 1/4X1/4X1-3/4 L	1.000 ea
702618004T	FAN KB 182/70 (112) 440	1.000 ea
004824015A	GREASE POLYREX EM	1.160 lb
032018020FK	HHCS 3/4-10X2-1/2 PLTD.	4.000 ea
032018008CK	HHCS 3/8-16X1L PLATED	4.000 ea
032018030DK	HHCS 1/2-13X3-3/4 PLTD.	3.000 ea
032018030DK	HHCS 1/2-13X3-3/4 PLTD.	3.000 ea
415096002A	CPLG 1/8 HEX TYPE	1.000 ea
410700004A	WSHR	1.000 ea
034017014AB	LCKW 3/8 STD. PLATED	4.000 ea
034530064AB	P/NIP 1/8 X 8" L Pipe Nipple	1.000 ea
089490099A	G28 BRKT 089490098WCA KB	1.000 ea
032018020FK	HHCS 3/4-10X2-1/2 PLTD.	4.000 ea
702658001A	CONDUIT BOX, E440	1.000 ea
702658002A	+C/BOX CVR, PAINTED 440	1.000 ea
415915007G	GASK, LAC	1.000 ft
406056008A	GASKET, TERBD 440	1.000 ea
418153001A	GASK 440	1.000 ea
032018008DK	HHCS 1/2-13X1 PLATED	4.000 ea
033512006LB	HHTTS 1/4-20X3/4 PLTD.	8.000 ea
406099000A	PLUG - FAN COVER 320-440	1.000 ea

415000115H	T/LUG #2AWG-4/0AWG	1.000 ea
032018005DL	1/2-13 X 5/8 SILICON BRONZE HHCS	1.000 ea
033775004EA	DRSCR #6-1/4 304 S.S.	2.000 ea
034180054KA	7/8 SQ X 6.75 KEY	1.000 ea
035000001A	ALFTG 1/8" 1610-BL	1.000 ea
034690002AB	PPLG 1/4" PLTD.	1.000 ea
034690005AB	PPLG 3/4 PLATED	2.000 ea
418151014G	RETAIN RING	1.000 ea
032018004BK	HHCS 5/16-18X1/2 PLATED	3.000 ea
035000001A	ALFTG 1/8" 1610-BL	1.000 ea
415096002A	CPLG 1/8 HEX TYPE	1.000 ea
032620016LA	SOCKET SET SCREW-449	3.000 ea
702623013A	THERMAL BARRIER -- G28 -- BRACKET MTD	1.000 ea
034017013AB	LCKW 5/16 STD. PLATED	3.000 ea
034690002AB	PPLG 1/4" PLTD.	1.000 ea
034530044AB	P/NIP 1/8X5-1/2L GALV.	1.000 ea
032620016LA	SOCKET SET SCREW-449	3.000 ea
000692000FF	N/P	1.000 ea
PK5004A09	BASE 48 X 39-1/4 WITH STACKED 2X4 RUUNER	1.000 ea
MG1025N19	WILKO 778.50 BLUE GREEN - 55 GAL DRUMS	0.438 ga

REL S.O.	-	VOLTS	460	ENCLOSURE	TEFC	WYE CONN EQ CKT OHMS PER PHASE			
FRAME	444T	AMPS	150	MAX SAFE RPM	3600	(AT BASE RATING, 25 °C)			
HP	125	DUTY	CONT	IM (AMPS)	62.1	R1	.0136	X1	.134
BASE SPEED	1790	S.F.	1.00	P.F.@NL/FL	7.2/82.1	R2	.00939	X2	.109
PHASE/HERTZ	3/60	AMB °C/INSUL	40/F	WK^2 (Lb-Ft^2)	40.99			XM	3.58

RATED FULL LOAD DATA

	RPM	HP	TORQUE LB-FT	FUND VOLTS	FREQ-HZ	AMPS
BASE SPEED	1790	125	367	460	60	150
MAX SPEED	2684	125	244	460	90	140
MIN SPEED	0	0	367	7.80	.342	150

LOAD PERFORMANCE AT BASE SPEED

	RPM	HP	TORQUE LB-FT	FUND VOLTS	FREQ-HZ	AMPS
NO LOAD	1800	0	0	460	60	62.1
1/4	1797	31.3	92	460	60	80.4
1/2	1795	62.6	183	460	60	99.1
3/4	1792	93.8	275	460	60	124
FULL LOAD	1790	125	367	460	60	150
O/L	1779	249	734	460	60	274

BLOWER DATA	VOLTS	PH/HZ	FL AMPS	LR AMPS	FRAME	CFM

REMARKS: TYPICAL DATA
VECTOR PWM INVERTER DUTY

BALDOR

DR. BY	M. ORDERS
CK. BY	J. TSAO
APP. BY	J. TSAO
DATE	06/15/04

A-C MOTOR PERFORMANCE DATA

A44WG0911-R003

ISSUE DATE 12/21/10

REL S.O.	–	VOLTS	460	ENCLOSURE	TEFC	WYE CONN EQ CKT OHMS PER PHASE (AT BASE RATING, 25 °C)	
FRAME	444T	AMPS	150	MAX SAFE RPM	3600		
HP	125	DUTY	CONT	IM (AMPS)	62.1	R1 .0136	X1 .134
BASE SPEED	1790	S.F.	1.00	P.F.@NL/FL	7.2/82.1	R2 .00939	X2 .109
PHASE/HERTZ	3/60	AMB °C/INSUL	40/F	WK² (Lb-Ft²)	40.99		XM 3.58



REMARKS: TYPICAL DATA
DATA VALID FOR NAMEPLATE SPEED RANGE ONLY

BALDOR

DR. BY	M. ORDERS
CK. BY	J. TSAO
APP. BY	J. TSAO
DATE	06/15/04

A–C MOTOR PERFORMANCE CURVES

A44WG0911-R003
SH 1 OF 2
ISSUE DATE 12/21/10

REL S.O.	-	VOLTS	460	ENCLOSURE	TEFC	WYE CONN EQ CKT OHMS PER PHASE	
FRAME	444T	AMPS	150	MAX SAFE RPM	3600	(AT BASE RATING, 25 °C)	
HP	125	DUTY	CONT	IM (AMPS)	62.1	R1 .0136	X1 .134
BASE SPEED	1790	S.F.	1.00	P.F.@NL/FL	7.2/82.1	R2 .00939	X2 .109
PHASE/HERTZ	3/60	AMB °C/INSUL	40/F	WK² (Lb-Ft²)	40.99		XM 3.58



REMARKS: TYPICAL DATA

DATA VALID FOR NAMEPLATE SPEED RANGE ONLY

BALDOR

DR. BY	M. ORDERS
CK. BY	J. TSAO
APP. BY	J. TSAO
DATE	06/15/04

A-C MOTOR PERFORMANCE CURVES

A44WG0911-R003

SH 2 OF 2

ISSUE DATE 12/21/10

DUTY MASTER ALTERNATING CURRENT MOTORS

617435-164

ENCLOSURE: TOTALLY ENCLOSED

SQUIRREL-CAGE INDUCTION

MOUNTING: FOOT, F-1 SIDE

G444T/G445T FRAME MOUNTING HOLES

COOLING: FAN COOLED









DIMENSIONS ARE IN INCHES.
MOTOR WEIGHTS (LBS) = 2130 ±15% DEPENDING ON RATING.
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT MOTOR PERFORMANCE IS SUITABLE IN THE APPLICATION.

1 OBSTRUCTIONS MUST NOT ENCROACH ON AIR INLET.

IF MOUNTING CLEARANCE DETAILS ARE REQUIRED, CONSULT FACTORY.
MAX PERMISSIBLE SHAFT RUNOUT WHEN MEASURED AT END OF STANDARD SHAFT EXTENSION IS .003" T.I.R.

SHEET NUMBER 1 OF 2

617435-164

REV. DESC: ADD METRIC DS			
REV: B	VERSION: 02	REVISED: 01:13:13 06/10/2021	TDR: 000001169193
MODEL NO. 617435-164			REF:
BY: USJEDIL	Material:		C

BALDOR

G445/444T TEFC F1 FOOT SIDE/CEN STEEL CONDUIT BOX

617435-164

DUTY MASTER ALTERNATING CURRENT MOTORS

617435-164

ENCLOSURE: TOTALLY ENCLOSED

SQUIRREL-CAGE INDUCTION

MOUNTING: FOOT, F-1 SIDE

G444T/G445T FRAME MOUNTING HOLES

COOLING: FAN COOLED









DIMENSIONS ARE IN MILLIMETERS.
MOTOR WEIGHTS (LBS) = 966 ±15% DEPENDING ON RATING.
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT MOTOR PERFORMANCE IS SUITABLE IN THE APPLICATION.

1 OBSTRUCTIONS MUST NOT ENCROACH ON AIR INLET.

IF MOUNTING CLEARANCE DETAILS ARE REQUIRED, CONSULT FACTORY.
MAX PERMISSIBLE SHAFT RUNOUT WHEN MEASURED AT END OF STANDARD SHAFT EXTENSION IS .08 T.I.R.

SHEET NUMBER 2 OF 2

617435-164

REV. DESC: ADD METRIC DS			
REV: B	VERSION: 02	REVISED: 01:13:13 06/10/2021	TDR: 000001169193
MODEL NO. 617435-164			REF:
BY: USJEDIL	Material:		C

BALDOR

G445/444T TEFC F1 FOOT SIDE/CEN STEEL CONDUIT BOX

617435-164

416820–036

A–C MOTOR
CONNECTION DIAGRAM
STANDARD 3 LEAD CONNECTED



(N.P. 1575–BA)

416820–036

REV. DESC: LOADED TO BUS, C/R 335225			BALDOR
REV. LTR: –	VERSION: 00	TDR: 000000538207	
FILE: \MGA\00000\682		REVISED: 11:54:06 04/30/2010	CONN DIAG – STANDARD 3 LEAD
MTL: –		BY: RAGRA	SH 1 of 1