ABB BALDOR RELIANCE

Customer information packet

JEWDM3550

1.5HP, 3450RPM, 3PH, 60HZ, 56J, 3526M, TEFC, F1
Class - None
Division - Not Applicable

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
10/5/2026 9:54:25 PM

Specifications

Enclosure	TEFC
Frame	56J
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	1.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	208.0 V @ 60 HZ
	230.0 V @ 60 HZ
	460.0 V @ 60 HZ
Agency Approvals	CSA EEV
	CSA
	UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	2.000 A @ 460.0 V
	4.000 A @ 230.0 V
	4.100 A @ 208.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	84.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard

Part Detail

Revision	N
Type	AC
Mech. spec.	35E2235
Base	
Status	PRD/A
Elec. spec.	35WGM774
Layout	35LYE2235
Eff. date	09-17-2025
CD Diagram	CD0005
Poles	02
Leads	9#18
Proprietary	False
Created date	07-02-2015

Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	2.0 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	P
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3526M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	13.72 IN
Power Factor	84
Product Family	Wash Down
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Ext Thread
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.30
Shaft Diameter	0.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None

Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1669L								
CAT.NO.	JEWDM3550							
SPEC.	35E2235M774G2							
HP	1.5							
VOLTS	208-230/460							
AMP	4.1-4/2							
RPM	3450							
FRAME	56J	**HZ**	60			**PH**	3	
SER.F.	1.30	**CODE**	P	**DES**	B	**CLASS**	F	
NEMA-NOM-EFF	84	**PF**	84					
RATING	40C AMB-CONT							
CC	010A							
DE	6205	**ODE**	6203					
ENCL	TEFC	**SN**						
BLANK	SFA 5.1-4.8/2.4							

Parts List

Part number	Description	Quantity
SA303593	SA 35E2235M774G2	1.000 ea
RA290724	RA 35E2235M774G2	1.000 ea
NS2512A01	INSULATOR, CONDUIT BOX X	1.000 ea
35CB3008A01G	SPL CONDUIT BOX, MACHINED GRAY	1.000 ea
35GS1022A03	GASKET BOX .125 THK WHITE NEOPRENE	1.000 ea
51XB1016A07	10-16 X 7/16 HXWSSLD SERTYB	2.000 ea
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 ea
35EP3122B00W	MASTER ODE,203 BRG,.683SH,.125NPT DRNS,F	1.000 ea
HW4072A01	BLACK DRAIN PLUG FOR .125 NPT	3.000 ea
HW5100A03	WAVY WASHER (W1543-017)	1.000 ea
HW4600B39SP	V-RING SLINGER 0.550 X 0.790 X .18 VITON	1.000 ea
12XN1032S20	10-32 X 1-1/4 HEX M.S. , STAINLESS STEEL	2.000 ea
35EP3307E00W	MASTER DE,205 BRG,1.623SH,.125NPT DRNS,C	1.000 ea
HW4072A01	BLACK DRAIN PLUG FOR .125 NPT	3.000 ea
HW4600B49	SEAL 0.938 X 1.624 X 0.250 SINGLE LIP DB	1.000 ea
HW4600B46	V-RING SLINGER 0.875 X 1.420 X .24 VITON	1.000 ea
35FH4005A55	IEC FH NO GRSR,3 MTG HOLE NO DIMPLES,	1.000 ea
11XW1032S06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	3.000 ea
WD4100A10	465 NIAGARA PLUG (SO ELEC),FOR 1.093 DIA	1.000 ea
35CB4522	35 LIPPED CB LID PRIMED	1.000 ea
35GS1030A02	35 GS FOR CB LID - WHITE NEOPRENE	1.000 ea
59XW0832S07	TAPTITE II,HEX WSHR UNSLTD SER,410 S.S.,	4.000 ea
LB1164	LABEL,WARNING AND DRAIN	1.000 ea
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
HA5027A02	HA4054 T-DRAIN X2 BAGGED WITH LABEL	1.000 ea
RM1010A12	.437 I.D. 1" VINYL CAP (SHORT) MOCAP	1.000 ea
MJ1000A02	GREASE, POLYREX EM EXXON	0.050 lb
34FN3002B01	EXTERNAL FAN, PLASTIC, .637/.639 HUB W/	1.000 ea
MJ5001A27	32220KN GRAY SEALER *MIN BUY 4 QTS=1GAL	0.001 qt
MG1025W01	WILKOFAST, 781.01, SIGNAL WHITE #9003	0.017 ga
MG1025Z02	ACTIVATOR WILKOFAST 060.02HF	0.010 ga

HA3100S07	THRUBOLT 10-32 X 8.375 SS	4.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
LC0005	CONN.DIA.,TY M,9-LD,DUAL VOLT,REVERSING	1.000 ea
NP1669L	SS WD SUPER-E UL PREM REV MTG	1.000 ea
36PA1000	PKG GRP, PRINT PK1016A08	1.000 ea
PK3083	STYROFOAM PACKING CRADLE	1.000 ea
PK3088	MICROFOAM, 8"X"8 PERF. SHEETS	1.000 ea
FE-0000001	ZRTG FE ASSEMBLY	1.000 ea
PE-0000002	ZRTG PE ASSEMBLY	1.000 ea

AC Induction Motor Performance Data
Record # 51670
Typical performance - not guaranteed values

Winding: 35WGM774-R070	**Type:** 3526M	**Enclosure:** TEFC

Nameplate Data			**460 V, 60 Hz: High Voltage Connection**	
Rated Output (HP)		1.5	**Full Load Torque**	2.22 LB-FT
Volts		208-230/460	**Start Configuration**	direct on line
Full Load Amps		4.1-4/2	**Breakdown Torque**	14.2 LB-FT
R.P.M.		3450	**Pull-up Torque**	6.33 LB-FT
Hz	60 **Phase**	3	**Locked-rotor Torque**	11.2 LB-FT
NEMA Design Code	B **KVA Code**	P	**Starting Current**	25.9 A
Service Factor (S.F.)		1.3	**No-load Current**	0.912 A
NEMA Nom. Eff.	84 **Power Factor**	84	**Line-line Res. @ 25ºC**	6.88 Ω
Rating - Duty		40C AMB-CONT	**Temp. Rise @ Rated Load**	34°C
S.F. Amps		5.1-4.8/2.4	**Temp. Rise @ S.F. Load**	43°C
			Locked-rotor Power Factor	49.9
			Rotor inertia	0.0719 LB-FT2

Load Characteristics 460 V, 60 Hz, 1.5 HP

% of Rated Load	**25**	**50**	**75**	**100**	**125**	**150**	**S.F.**
Power Factor	48	67	78	84	87	89	87
Efficiency	67.2	79.7	83.2	85.1	85.4	85	85.3
Speed	3578	3559	3539	3518	3496	3470	3491
Line amperes	1.04	1.29	1.61	1.96	2.34	2.76	2.42

ABB Motors and Mechanical Inc.

WINDING # 35WGM774

1.5 HP 3 PH 60 HZ 3450 RPM 460 V 3526M

Typical performance - not guaranteed values.

TORQUES(LB-FT): PO=14.2 PU=6.33 LR=11.2 LRA=25.9




35LYE2235
510-520 = 12.72
521-528 = 13.72
529-535 = 14.60
536-546 = 15.97
2.56
(4) .125" NPT HOLES
3 W/PLUGS
@ 3, 9, & 1:00
(FRONT END)
CHECK WITH
GAGE T-6338
1.91
1.85
.72
.66
.13
.16
NAMEPLATE
Ø7.19
SLINGER
(EA. END)
PLUG
SLOT
.09 WIDE X
.12 DEEP
.03 X 45°
Ø6.49
Ø4.500
4.497
Ø.6253
.6243
.44-20 UNF-2A
RH THDS
(4) .125" NPT HOLES
3 W/PLUGS
@ 3, 9, & 11:00
(PULLEY END)
3.76
Ø6.61
5.77
45°
45°
LEAD HOLE
.50 NPT
4 HOLES
.38-16 TAP ON
Ø5.88 B.C.
4.69
OMIT LOCK-WASHERS &
APPLY SEALER UNDER
BEARING RETAINER SCREW HEADS
& HOUSING BEFORE PRESSING IN SEAL
PULLEY END DETAIL
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION
REV. DESC: HOW SEAL OPP DIRECT TO MATCH SI
REV: E
VERSION: 05
REVISED: 09:01:35 02/25/2019
TDR: 000001100583
MODEL NO. 35LYE2235
REF: -
BY: ENWINB0
B
BALDOR - RELIANCE®
STD VERT 56J TEFC 35M WD (S/P9) W/ FULL LENGTH SS SHAFT
SH 1 of 1
35LYE2235

CD0005





NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0005

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			BALDOR ELECTRIC Co.
REV. LTR: E	BY: JLP	REVISED: 01/19/99 10:15	TDR: 0171435
CD0005		FILE: AAA00005140	MDL: –
		MTL: –	3PH, DV, 9 LEADS