

ABB BALDOR RELIANCE III

Customer information packet

JML1511T

10HP, 3450RPM, 1PH, 60HZ, 215JM, 3740L, OPEN, F

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	215JM
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Induction Run
Output @ Frequency	10.000 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	48.000 A @ 208.0 V 46.000 A @ 230.0 V
Design Code	L
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	83.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	46.0 a
Insulation Class	F

Part Detail

Revision	V
Type	AC
Mech. spec.	37K266
Base	
Status	PRD/A
Elec. spec.	37WGX047
Layout	37LYK266
Eff. date	05-13-2024
CD Diagram	CD0017A01
Poles	02
Leads	2#8 A PH,2#14 B PH
Proprietary	False
Created date	03-08-2007

Inverter Code	Not Inverter
KVA Code	G
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	2 @ 8 AWG, A PH
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3740L
Mounting Arrangement	F1
Number of Poles	2
Overall Length	19.31 IN
Power Factor	86
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	Included
Service Factor	1.15
Shaft Diameter	1.000 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L									
CAT.NO.	JML1511T								
SPEC.	37K266X047G1								
HP	10								
VOLTS	230								
AMP	46								
RPM	3450								
FRAME	215JM		HZ	60			PH	1	
SER.F.	1.15		CODE	G	DES	L	CLASS	F	
NEMA-NOM-EFF	83		PF	86					
RATING	40C AMB-CONT								
CC									
DE	6309		ODE	6206					
ENCL	OPEN		SN						

Parts List

Part number	Description	Quantity
SA155065	SA 37K266X047G1	1.000 ea
RA143722	RA 37K266X047G1	1.000 ea
HA6361A01	LIFTING LUG FOR 37, 39 & 40 FRAME ZINC	2.000 ea
37CB3006	37 CB CASTING W/1.38 LEAD HOLE @ 6:00	1.000 ea
51XW2520A12	.25-20 X .75, TAPTITE II, HEX WSHR SLTD	2.000 ea
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 ea
37EP3203D00	MASTER,ODE,206 BRG,GREASER,RELIEF	1.000 ea
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 ea
HW4500A17	317400 ALEMITE GREASE RELIEF	1.000 ea
HA1104A01	RODENT SCREEN 37 FRAME 206 BRG FRONT END	1.000 ea
HW1000A10	#10 FLAT WASHER (SAE)	4.000 ea
SP1008A01	BAFFLE, MODEL 36 & 37	1.000 ea
13XF0832A08	8-32 X.50 PAN HD,SLTD, TYPE F SCREW, ZIN	2.000 ea
51XW2520A10	.25-20 X .62, TAPTITE II, HEX WSHR SLTD	2.000 ea
HW5100A06	W2420-025 WVY WSHR (WB)	1.000 ea
37EP3401A46	PUEP OPEN 309 BRG W/BAFFLE, GRS, REL, MF	1.000 ea
37AD2000A02	BAFFLE PLATE, STAMPED PLATED	1.000 ea
60XW0632A06	6-32 X 3/8 TORX HEAD SCREW TAPTITE II	4.000 ea
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 ea
HW4500A17	317400 ALEMITE GREASE RELIEF	1.000 ea
HA1222	RODENT SCREEN - 37 C-FACE MOTORS	4.000 ea
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	4.000 ea
HW1000A10	#10 FLAT WASHER (SAE)	4.000 ea
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	4.000 ea
10XN2520A36	1/4-20X 2 1/4 HEX HD X	4.000 ea
HW1001A25	LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I	4.000 ea
XY3118A12	5/16-18 HEX NUT DIRECTIONAL SERRATION	4.000 ea
HW4600B67	V-RING SLINGER 1.770 X 2.170 X .28 VITON	1.000 ea
37CB4516	LIPPED LID FOR 37 FRAME NEC KOBX	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	4.000 ea
HW2501D13	KEY, 3/16 SQ X 1.375	1.000 ea

HA7000A01	KEY RETAINER 7/8" DIA SHAFT	1.000 ea
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
MJ1000A02	GREASE, POLYREX EM EXXON	0.050 lb
MG1050G01	CELEROL MEDIUM CHARCOAL METALLIC GRAY	0.028 ga
SP5172A01	37 TYPE L TORQ STAT SWITCH LEAD ASSEMBLY	1.000 ea
37CB5007A01	CAPACITOR BOX KIT, 37CB3802, 3 EC1216C0	1.000 ea
HA3104A35	THRUBOLT .31-18 X 13.687	4.000 ea
LC0017	CONN LABEL-1 PHASE-SINGLE VOLT-REV ROTNO	1.000 ea
LB1624	COMBINED WARNING LABEL, ISO/ANSI PICTOGR	1.000 ea
NP1256L	ALUM UL CC INDUSTRIAL MOTOR A60	1.000 ea
37PA1074	PALLET PACK GRP, PRINT BOX PK1026A06	1.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
FE-0000004	ZRTG FE ASSEMBLY	1.000 ea

AC Induction Motor Performance Data

Record # 11971

Typical performance - not guaranteed values

Winding: 37WGX047-R001			Type: 3740L		Enclosure: OPEN		
Nameplate Data			230 V, 60 Hz: Single Voltage Motor				
Rated Output (HP)		10	Full Load Torque		15 LB-FT		
Volts		230	Start Configuration		direct on line		
Full Load Amps		46	Breakdown Torque		46.4 LB-FT		
R.P.M.		3450	Pull-up Torque		27.6 LB-FT		
Hz	60	Phase	1	Locked-rotor Torque		30.6 LB-FT	
NEMA Design Code		L	KVA Code	G	Starting Current		280 A
Service Factor (S.F.)		1.15		No-load Current		19.3 A	
NEMA Nom. Eff.		83	Power Factor	86	Line-line Res. @ 25°C		0.163 Ω A Ph 0.728 Ω B Ph
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		100°C	
S.F. Amps				Temp. Rise @ S.F. Load		115°C	

Load Characteristics 230 V, 60 Hz, 10 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	56	72	82	86	88	87	87
Efficiency	63	79.3	81.1	83.7	82.8	80.7	83.2
Speed	3587	3570	3552	3536	3512	3482	3522
Line amperes	23.5	29	37.2	45.5	55.6	68.6	51.6


ABB Motors and Mechanical Inc.


WINDING # 37WG047

Typical performance - not guaranteed values.

10 HP 1 PH 60 HZ 3450 RPM 230 V 3740L

TORQUES (LB-FT) : PO=46.4 PU=27.6 LR=30.6 LRA=280





CD0017A01

