ABB BALDOR RELIANCE

# Customer information packet

## L3613T

1.5HP, 1140RPM, 1PH, 60HZ, 184T, 3634LC, TEFC
Class - None
Division - Not Applicable

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
11/1/2026 6:59:51 PM

## Specifications

| | |
|---|---|
| **Enclosure** | TEFC |
| **Frame** | 184T |
| **Frame Material** | Steel |
| **Frequency** | 60.00 Hz |
| **Haz Area Class and Group** | None |
| **Haz Area Division** | Not Applicable |
| **Motor Letter Type** | Cap Start, Cap Run |
| **Output @ Frequency** | 1.500 HP @ 60 HZ |
| **Phase** | 1 |
| **Synchronous Speed @ Frequency** | 1200 RPM @ 60 HZ |
| **Voltage @ Frequency** | 115.0 V @ 60 HZ |
| | 230.0 V @ 60 HZ |
| **Agency Approvals** | C UR US |
| **Ambient Temperature** | 40 °C |
| **Auxiliary Box** | NO AUXILLARY BOX |
| **Auxiliary Box Lead Termination** | None |
| **Base Indicator** | Rigid |
| **Bearing Grease Type** | Polyrex EM (-20F +300F) |
| **Blower** | None |
| **Current @ Voltage** | 16.400 A @ 115.0 V |
| | 8.200 A @ 230.0 V |
| | 8.600 A @ 208.0 V |
| **Design Code** | L |
| **Drip Cover** | No Drip Cover |
| **Duty Rating** | CONT |
| **Efficiency @ 100% Load** | 73.0 % |
| **Electrically Isolated Bearing** | Not Electrically Isolated |
| **Feedback Device** | NO FEEDBACK |
| **Front Face Code** | Standard |
| **Front Shaft Indicator** | None |
| **Heater Indicator** | No Heater |
| **High Voltage Full Load Amps** | 8.2 a |

## Part Detail

| | |
|---|---|
| **Revision** | AZ |
| **Type** | AC |
| **Mech. spec.** | 36E004 |
| **Base** | |
| **Status** | PRD/A |
| **Elec. spec.** | 36WGW839 |
| **Layout** | 36LYE004 |
| **Eff. date** | 07-17-2025 |
| **CD Diagram** | CD0055 |
| **Poles** | 06 |
| **Leads** | 6#16 |
| **Proprietary** | False |
| **Created date** | 01-01-0001 |

| | |
|---|---|
| **Insulation Class** | F |
| **Inverter Code** | Not Inverter |
| **KVA Code** | J |
| **Lifting Lugs** | Standard Lifting Lugs |
| **Locked Bearing Indicator** | No Locked Bearing |
| **Motor Lead Exit** | Ko Box |
| **Motor Lead Quantity/Wire Size** | 6 @ 16 AWG |
| **Motor Lead Termination** | Flying Leads |
| **Motor Standards** | NEMA |
| **Motor Type** | 3634LC |
| **Mounting Arrangement** | F1 |
| **Number of Poles** | 6 |
| **Overall Length** | 16.56 IN |
| **Power Factor** | 81 |
| **Product Family** | General Purpose |
| **Pulley End Bearing Type** | Ball |
| **Pulley Face Code** | Standard |
| **Pulley Shaft Indicator** | Standard |
| **Rodent Screen** | None |
| **Service Factor** | 1.15 |
| **Shaft Diameter** | 1.125 IN |
| **Shaft Extension Location** | Pulley End |
| **Shaft Ground Indicator** | No Shaft Grounding |
| **Shaft Rotation** | Reversible |
| **Shaft Slinger Indicator** | No Slinger |
| **Speed** | 1140 rpm |
| **Speed Code** | Single Speed |
| **Starting Method** | Direct on line |
| **Thermal Device - Bearing** | None |
| **Thermal Device - Winding** | None |
| **Vibration Sensor Indicator** | No Vibration Sensor |
| **Winding Thermal 1** | None |
| **Winding Thermal 2** | None |

**Nameplate**

| NP1256L | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| **CAT.NO.** | L3613T | | | | | | | |
| **SPEC.** | 36E04W839 | | | | | | | |
| **HP** | 1.5 | | | | | | | |
| **VOLTS** | 115/230 | | | | | | | |
| **AMP** | 16.4/8.2 | | | | | | | |
| **RPM** | 1140 | | | | | | | |
| **FRAME** | 184T | **HZ** | 60 | | | **PH** | 1 | |
| **SER.F.** | 1.15 | **CODE** | J | **DES** | L | **CLASS** | F | |
| **NEMA-NOM-EFF** | 73 | **PF** | 81 | | | | | |
| **RATING** | 40C AMB-CONT | | | | | | | |
| **CC** | | | | | | | | |
| **DE** | 6206 | **ODE** | 6205 | | | | | |
| **ENCL** | TEFC | **SN** | | | | | | |

**Parts List**

| Part number | Description | Quantity |
|---|---|---|
| SA034452 | SA 36E04W839 | 1.000 ea |
| RA030480 | RA 36E04W839 | 1.000 ea |
| OC3060C09SP | CAPACITOR 60 MFD 240 VAC | 1.000 ea |
| EC1645A06SP | ELEC CAP, 645-774 MFD, 125V, 2.06D X 4. | 1.000 ea |
| 36CB3004 | 36 CB CASTING W/1.09 DIA LEAD HOLE @ 6:0 | 1.000 ea |
| 36GS1000SP | GASKET-CONDUIT BOX, .06 THICK #SV-330 LE | 1.000 ea |
| 51XB1016A08 | 10-16X 1/2HXWSSLD SERTYB | 2.000 ea |
| 11XW1032G06 | 10-32 X .38, TAPTITE II, HEX WSHR SLTD U | 1.000 ea |
| HW3001B01 | BRASS CUP WASHER, FOR #10 SCREW | 1.000 ea |
| 36EP3104A01 | FREP MACH W/GRSR, RAISED FH PADS | 1.000 ea |
| HW4500A01 | 1641B(ALEMITE)400 UNIV, GREASE FITT | 1.000 ea |
| 13XF0832A08 | 8-32 X.50 PAN HD,SLTD, TYPE F SCREW, ZIN | 2.000 ea |
| 36GS3000 | GASKET, CAPACITOR COVER LEXIDE | 1.000 ea |
| 51XW2520A10 | .25-20 X .62, TAPTITE II, HEX WSHR SLTD | 2.000 ea |
| HW5100A05 | WVY WSHR F/205 & 304 BRGS | 1.000 ea |
| 36EP3100A01SP | PUEP ASSEMBLY FOR ROUTING PURPOSES | 1.000 ea |
| HW4500A01 | 1641B(ALEMITE)400 UNIV, GREASE FITT | 1.000 ea |
| XY2520A12 | 1/4-20 HEX NUT, DIRECTIONAL SERRATIONS | 4.000 ea |
| 51XB1214A16 | 12-14X1.00 HXWSSLD SERTYB | 1.000 ea |
| 51XW1032A06 | 10-32 X .38, TAPTITE II, HEX WSHR SLTD S | 3.000 ea |
| 36CB4516 | 750LIPPED CB LID - GALVANNEAL | 1.000 ea |
| 37GS1001SP | GASKET, CONDUIT BOX LID, .06 THICK LEXID | 1.000 ea |
| 51XW0832A07 | 8-32 X .44, TAPTITE II, HEX WSHR SLTD SE | 4.000 ea |
| HW2501E16 | KEY, 1/4 SQ X 1.750 | 1.000 ea |
| HA7000A02 | KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA | 1.000 ea |
| 85XU0407S04 | 4X1/4 U DRIVE PIN STAINLESS | 2.000 ea |
| HA6362ZP | LIFTING LUG FOR 36 FRAME MOTORS. | 2.000 ea |
| WD1000A15 | 3-520132-2 AMP FLAG (4M/RL NON-CANC/NON- | 2.000 ea |
| 36CB3800SP | CAPACITOR COVER, CAST | 1.000 ea |
| HA7010A01 | CAPACITOR RETENTION CLAMP, 6.562 LONG | 1.000 ea |
| MJ1000A02 | GREASE, POLYREX EM EXXON | 0.050 lb |

| | | |
|---|---|---|
| 36FN3000A01SP | EXFN, PLASTIC, 7.00 OD, .912 ID | 1.000 ea |
| MG1050G01 | CELEROL MEDIUM CHARCOAL METALLIC GRAY | 0.022 ga |
| HA3101A45 | THRUBOLT- 1/4-20 X 11.126 | 4.000 ea |
| 36FH4009A124 | IEC FH W/GRSR,GRILL,NO DIMPLES,PRIMER | 1.000 ea |
| SP5172A05 | 37 TYPE LC TORQ STAT SW LEAD ASSEMBLY | 1.000 ea |
| LC0001A01 | CONN LABEL / WARNING LABEL (LC0001 / LB1 | 1.000 ea |
| NP1256L | ALUM UL CC INDUSTRIAL MOTOR A60 | 1.000 ea |
| 36PA1001 | PKG GRP, PRINT PK1017A07 | 1.000 ea |
| MN416A01 | TAG-INSTAL-MAINT no wire (2500 bx)11/25 | 1.000 ea |
| LB1624 | COMBINED WARNING LABEL, ISO/ANSI PICTOGR | 1.000 ea |
| FE-0000001 | ZRTG FE ASSEMBLY | 1.000 ea |

**Accessories**

| Part number | Description | Multiplier |
|---|---|---|
| 36-3301 | C FACE KIT | A8 |
| 36EP1304A62SP | FLANGE MTD ENDPLATE 182-4TD -ENCL (LESS | A8 |

**AC Induction Motor Performance Data**
Record # 44641
Typical performance - not guaranteed values

| **Winding:** 36WGW839-R001 | **Type:** 3634LC | **Enclosure:** TEFC |
|---|---|---|

| **Nameplate Data** | | | **230 V, 60 Hz: High Voltage Connection** | |
|---|---|---|---|---|
| **Rated Output (HP)** | | 1.5 | **Full Load Torque** | 6.8 LB-FT |
| **Volts** | | 115/230 | **Start Configuration** | direct on line |
| **Full Load Amps** | | 16.4/8.2 | **Breakdown Torque** | 16 LB-FT |
| **R.P.M.** | | 1140 | **Pull-up Torque** | 11 LB-FT |
| **Hz** | 60 **Phase** | 1 | **Locked-rotor Torque** | 15 LB-FT |
| **NEMA Design Code** | L **KVA Code** | J | **Starting Current** | 84 A |
| **Service Factor (S.F.)** | | 1.15 | **No-load Current** | 4.1 A |
| **NEMA Nom. Eff.** | 73 **Power Factor** | 81 | **Line-line Res. @ 25ºC** | 0.403 Ω A Ph<br>1.01 Ω B Ph |
| **Rating - Duty** | | 40C AMB-CONT | **Temp. Rise @ Rated Load** | 76°C |
| **S.F. Amps** | | | **Temp. Rise @ S.F. Load** | 90°C |
| | | | **Rotor inertia** | 0.319 LB-FT2 |

**Load Characteristics 230 V, 60 Hz, 1.5 HP**

| **% of Rated Load** | **25** | **50** | **75** | **100** | **125** | **150** | **S.F.** |
|---|---|---|---|---|---|---|---|
| **Power Factor** | 53 | 68 | 76 | 81 | 81 | 80 | 81 |
| **Efficiency** | 51.4 | 66.5 | 72.4 | 74.3 | 73.8 | 70.7 | 74 |
| **Speed** | 1188 | 1179 | 1168 | 1156 | 1140 | 1117 | 1146 |
| **Line amperes** | 4.6 | 5.5 | 6.5 | 8.2 | 10 | 12.5 | 9.2 |


ABB Motors and Mechanical Inc.

WINDING # 36WGW839

1.5 HP 1 PH 60 HZ 1140 RPM 230 V 3634LC

Typical performance - not guaranteed values.

TORQUES(LB-FT): PO=16 PU=11 LR=15 LRA=84



**AC Induction Motor Performance Data**
Record # 44642
Typical performance - not guaranteed values


| **Winding:** 36WGW839-R001 | **Type:** 3634LC | **Enclosure:** TEFC |
|---|---|---|


| **Nameplate Data** | | | |
|---|---|---|---|
| **Rated Output (HP)** | | | 1.5 |
| **Volts** | | | 115/230 |
| **Full Load Amps** | | | 16.4/8.2 |
| **R.P.M.** | | | 1140 |
| **Hz** | 60 | **Phase** | 1 |
| **NEMA Design Code** | L | **KVA Code** | J |
| **Service Factor (S.F.)** | | | 1.15 |
| **NEMA Nom. Eff.** | 73 | **Power Factor** | 81 |
| **Rating - Duty** | | | 40C AMB-CONT |
| **S.F. Amps** | | | |

| **115 V, 60 Hz: Low Voltage Connection** | |
|---|---|
| **Full Load Torque** | 6.8 LB-FT |
| **Start Configuration** | direct on line |
| **Breakdown Torque** | 16 LB-FT |
| **Pull-up Torque** | 11 LB-FT |
| **Locked-rotor Torque** | 15 LB-FT |
| **Starting Current** | 84 A |
| **No-load Current** | 8.2 A |
| **Line-line Res. @ 25ºC** | 0.403 Ω A Ph<br>1.01 Ω B Ph |
| **Temp. Rise @ Rated Load** | 76°C |
| **Temp. Rise @ S.F. Load** | 90°C |
| **Rotor inertia** | 0.319 LB-FT2 |


**Load Characteristics 115 V, 60 Hz, 1.5 HP**

| **% of Rated Load** | **25** | **50** | **75** | **100** | **125** | **150** | **S.F.** |
|---|---|---|---|---|---|---|---|
| **Power Factor** | 53 | 68 | 76 | 81 | 81 | 80 | 81 |
| **Efficiency** | 51.4 | 66.5 | 72.4 | 74.3 | 73.8 | 70.7 | 74 |
| **Speed** | 1188 | 1179 | 1168 | 1156 | 1140 | 1117 | 1146 |
| **Line amperes** | 9.2 | 10.9 | 13.3 | 16.2 | 19.9 | 24.9 | 18.4 |


ABB Motors and Mechanical Inc.
WINDING # 36WGW839
1.5 HP 1 PH 60 HZ 1140 RPM 115 V 3634LC
Typical performance - not guaranteed values.
TORQUES(LB-FT): PO=16 PU=11 LR=15 LRA=84
TORQUE
RPM
WATTS
AMPS
EFF
PF
%EFF
%PF
TORQUE (LB-FT)
RPM
WATTS
AMPS
PERCENT OF RATED OUTPUT (1.5 HP)
11/1/2026 ACPERF, record # 44642


36LYE004
614-634 = 16.56
635-646 = 18.04
GREASE FITTING (EA. END)
3.56
2.75
.25 KEY 1.75 LONG
Ø8.60
NAMEPLATE
Ø 1.1250 1.1245
4.27
4.50
.50
5.50
2.75
6.50
6 HOLES .41 DIA.
7.88
6.87
2.71
LIFTING LUG (1 EA. END)
8.45
4.50 +.00 -.06
LEAD HOLE Ø1.09
3.75
3.75
5.75
4.31
8.63
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION
REV. DESC: ADD LIFTING LUG CALLOUT
REV: L
VERSION: 05
REVISED: 09:07:41 01/08/2025
TDR: 000001247732
MODEL NO. 36LYE004
REF: -
BY: USMAHAD
B
BALDOR - RELIANCE®
STD HORZ 182-4T TEFC 36L-LC
36LYE004

CD0055




| | LINE A | LINE B | JOIN |
|---|---|---|---|
| HIGH STD | 1 | 4,5 | 2,3,8 |
| HIGH OPP | 1 | 4,8 | 2,3,5 |
| LOW STD | 1,3,8 | 2,4,5 | – |
| LOW OPP | 1,3,5 | 2,4,8 | – |

NOTES:

1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
2. OPTIONAL THERMOSTAT IS PROVIDED WHEN SPECIFIED.
3. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0055

| | | | |
|---|---|---|---|
| REV. DESC: REVISE TO SHOW OPTIONAL COLORS | | | BALDOR ELECTRIC Co. |
| REV. LTR: D | BY: JLP | REVISED: 04/08/99 1:17 | TDR: 0178636 |
| CD0055 | | FILE: AAA00007414 | MDL: – |
| | | MTL: – | TYPE LC, DV, REV, 6 LEADS |