

ABB BALDOR RELIANCE III

Customer information packet

SUM21504

15HP, 1765RPM, 3PH, 60HZ, 210TY, TENV, V1

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	210TY
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Phase	3
Agency Approvals	CCSA US
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Cable Length	25 FOOT
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Heater Indicator	No Heater
Insulation Class	F
Inverter Code	Not Inverter
IP Rating	IP68
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Motor Type	01
Mounting Arrangement	V1
Number of Poles	4
Product Family	Pump - Centrifugal
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.00
Shaft Diameter	1.437 IN
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed Code	Single Speed

Part Detail

Revision	B
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	86078
Layout	619738-019
Eff. date	12-10-2024
CD Diagram	
Poles	///
Leads	
Proprietary	False
Created date	07-11-2024

Starting Method	Direct on line
Thermal Device - Winding	Normally Closed Thermostat

Nameplate

000613007MS										
CAT.NO.	SUM21504			SPEC NO.	S21-CWS0-0303					
SER.NO.					FRAME SIZE	210TY				
CONSTANT HP RPM	HP	RPM	VOLTS		AMPS		HZ		S.F.	
	15	1765	230/460		38/19		6-60		1.00	
	15	1765	230/460		38/19		60		1.15	
	@			HZ	CODE	H				
	TYPE	P	INSUL.CLASS		F	TORQUE	10:1_VT			DESIGN
D.E. BRG.	60BC02JPP30A			ENCL	TENV	DUTY	15MIN		PH	3
O.D.E. BRG.	30BC02JPG30A			MOTOR WEIGHT			AMB		40	
	FINAL CONN VOLTAGE = 230 *15									
	MIN IN AIR									

000692000MB	
SUITABLE FOR OPERATION ON PWM	
INVERTER EQUIPPED WITH IGBT	
DEVICES AND CAPABLE OF	
CARRIER	
FREQUENCY OF 2 KHZ MINIMUM	

000613007MS

CAT.NO.	SUM21504		SPEC NO.		S21-CWS0-0303			
SER.NO.				FRAME SIZE	210TY			
	HP	RPM	VOLTS	AMPS	HZ	S.F.		
	15	1765	230/460	38/19	6-60	1.00		
	15	1765	230/460	38/19	60	1.15		
CONSTANT HP RPM		@		HZ	CODE	H		
TYPE	P	INSUL.CLASS		F	TORQUE	10:1_VT	DESIGN	B
D.E. BRG.	60BC02JPP30A		ENCL	TENV	DUTY	15MIN	PH	3
O.D.E. BRG.	30BC02JPG30A		MOTOR WEIGHT			AMB	40	
	FINAL CONN VOLTAGE = 230 *15							
	MIN IN AIR							

Parts List

Part number	Description	Quantity
SA427800	SA S21-CWS0-0303	1.000 ea
RA419948	RA S21-CWS0-0303	1.000 ea
000692000WC	WARNING FLAMMABLE VAPORS MAY BE PRESENT	2.000 ea
000692000EJ	NAME PLATE	1.000 ea
000613007MS	NP, MEDIUM AC,INVERTER DUTY CSA,STD INDU	1.000 ea
000901001AA	LABEL WARNING	1.000 ea
000692000MB	BALDOR RELIANCE MOTOR DATA NAMEPLATE	1.000 ea
000613007MS	NP, MEDIUM AC,INVERTER DUTY CSA,STD INDU	1.000 ea
034692002AE	HCSPP 1/4" 304 S.S.	1.000 ea
088206510A	BRKT,ODE,210SUB 88206-1WB	1.000 ea
004824015A	GREASE POLYREX EM	0.100 lb
032018012DG	HHCS 1/2-13X1-1/2 316S.S	4.000 ea
421900144FU	406673000BF	1.000 ea
004824018AF	SHELL ROTELLA OIL 10W	4.569 lb
413480001R	RESISTOR ASSEMBLY-BLANKET	1.000 ea
413412006S	LEAD WIRE ASSY	1.000 ea
413412004A	SUBM MOISTURE PROBE	2.000 ea
421900144FU	406673000BF	1.000 ea
088208001AA	MTG PLATE EX210Y SUBMERSIBLE 088208001WB	1.000 ea
032130010DC	HSHCS 1/2-13X1-1/4 304SS	4.000 ea
421900144FU	406673000BF	1.000 ea
088207510A	BRKT,DE,210SUB 88207-1WA	1.000 ea
032018012DG	HHCS 1/2-13X1-1/2 316S.S	4.000 ea
032018008BG	HHCS 5/16-18X1 316 SS	3.000 ea
064262012C	SEAL	1.000 ea
047174005D	SNAP RING	1.000 ea
034692003AE	PPLG 3/8" 304 S.S.	2.000 ea
047174005C	SNAP RING	1.000 ea
064262012D	SEAL - Mech Ceramic Seal	1.000 ea
032080003JB	HWHMS 10-24X3/8L PLTED	4.000 ea
032080003LB	HWHMS 1/4-20X3/8L PLTED	6.000 ea

415031017B	NUT W/WASHER 1/4-20 C.P	6.000 ea
047024003E	TERMINAL LUG	9.000 ea
415031017A	NUT W/WASHER 10-24 C.PLT	4.000 ea
700385014DA	CCA #4 25' 210/250	1.000 ea
421900092FU	ORING	1.000 ea
032018010CG	HHCS 3/8-16X1-1/4L 316SS	4.000 ea
032018006BM	HHCS 5/16-18X3/4 PLTGRN.	1.000 ea
032018006BM	HHCS 5/16-18X3/4 PLTGRN.	1.000 ea
034036013AB	LCKW 5/16 EXT.TOOTH LCKW	1.000 ea
047024003AH	T/LUG AMP 34112	4.000 ea
609181014D	HEAT SHRINK TUBING 3/4	10.000 ea
004824007K	SPECIAL PAINT	0.100 ea
033775004EA	DRSCR #6-1/4 304 S.S.	8.000 ea
034180009FD	KEY 3/8X3/8X1-1/8 303 SS	1.000 ea
B3630-9	SUBM THERMOSTAT TAG	1.000 ea
B-3664002	TAG, (NON REGREASABLE)	1.000 ea

AC induction motor performance data

Record #86078 - Typical performance - not guaranteed values

Winding	07WGA0018
Type	0746M
Enclosure	XPNV

Nameplate data

Rated Output	15		
Volts	230/460		
Full Load Amps	38/19		
R.P.M.	1765		
Hz	60	Phase	3
KVA Code	H		
S.F.	1.15		
NEMA Nom. Eff.	90.1	Power Factor	82
Duty	15 MIN		
S.F. Amps			

460 V, 60 Hz:

High Voltage Connection

Full Load Torque	44.66 LB-FT
Start Configuration	direct on line
Breakdown Torque	115 LB-FT
Pull-up Torque	45 LB-FT
Locked-rotor Torque	63.2 LB-FT
Starting Current	121 A
No-load Current	7.16
Line-line Res. @ 25°C	0.904 Ω
Temp. Rise @ Rated Load	35°C
Temp. Rise @ S.F. Load	43°C
Locked-rotor Power Factor	37.5
Rotor inertia	1.13 lb-ft²

Load Characteristics 460 V, 60 Hz, 15 HP

% of Rated Load	NL	25	50	75	100	125	150	SF
Power Factor	5	47	69	78	82	84	84	83
Efficiency	0	88.9	91.4	91.9	90.9	89.9	88	90.3
Speed	1799	1792	1783	1775	1765	1754	1741	1758
Line amperes	7.16	8.37	11.13	14.65	18.74	23.33	28.59	21.5

SPEED TORQUE / SPEED CURRENT CURVES



07WGA0018

15HP 460V 60HZ





