ABB BALDOR RELIANCE

Customer information packet

SUM70504-8

5HP, 1755RPM, 3PH, 60HZ, 180TY, XPNV, V1
Class - CLI GP C,D
Division - Not Applicable

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
10/31/2026 10:13:05 PM

Specifications

Enclosure	XPNV
Frame	180TY
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP C,D
Haz Area Division	Not Applicable
Phase	3
Agency Approvals	CCSA US
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Haz Area Temp Code	T3C
Heater Indicator	No Heater
Insulation Class	F
Inverter Code	Not Inverter
IP Rating	IP68
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	V1
Number of Poles	4
Product Family	Pump - Centrifugal
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.15
Shaft Diameter	1.250 IN
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Starting Method	Direct on line
Thermal Device - Winding	Normally Closed Thermostat

Part Detail

Revision	C
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	86084
Layout	619738-001
Eff. date	12-10-2024
CD Diagram	
Poles	///
Leads	
Proprietary	False
Created date	12-15-2021

Nameplate

000613007MS											
CAT.NO.	SUM70504-8			**SPEC NO.**	S18-CWS0-0025						
SER.NO.				**FRAME SIZE**	180TY						
	HP	**RPM**	**VOLTS**	**AMPS**	**HZ**	**S.F.**					
	5	1755	200/400	15.6/7.8	6-60	1.00					
	5	1755	200/400	15.6/7.8	60	1.15					
CONSTANT HP RPM		**@**		**HZ**	**CODE**	J					
TYPE	P	**INSUL.CLASS**	F	**TORQUE**	10:1_VT		**DESIGN**	B			
D.E. BRG.	50BC02JPP30A		**ENCL**	TENV	**DUTY**	15 MIN	**PH**	3			
O.D.E. BRG.	25BC02JPG30A		**MOTOR WEIGHT**		**AMB**	40					
	FINAL CONN VOLTAGE = 200										
	*15MIN IN AIR ;SUB. IN SEWAGE										
	/ WATER ONLY										

000613007RC		
CLASS I GROUP	C D X	**NO.**
CLASS II GROUP	X X X	
OPERATING TEMP CODE	T3C	

000692000MB
SUITABLE FOR OPERATION ON PWM
INVERTER EQUIPPED WITH IGBT
DEVICES AND CAPABLE OF
CARRIER
FREQUENCY OF 2 KHZ MINIMUM

000613007MS

CAT.NO.	SUM70504-8			**SPEC NO.**	S18-CWS0-0025							
SER.NO.				**FRAME SIZE**	180TY							
	HP	**RPM**	**VOLTS**	**AMPS**	**HZ**	**S.F.**						
	5	1755	200/400	15.6/7.8	6-60	1.00						
	5	1755	200/400	15.6/7.8	60	1.15						
CONSTANT HP RPM		**@**		**HZ**	**CODE**	J						
TYPE	P	**INSUL.CLASS**	F	**TORQUE**	10:1_VT			**DESIGN**	B			
D.E. BRG.	50BC02JPP30A			**ENCL**	TENV	**DUTY**	15 MIN		**PH**	3		
O.D.E. BRG.	25BC02JPG30A			**MOTOR WEIGHT**			**AMB**	40				
	FINAL CONN VOLTAGE = 200											
	*15MIN IN AIR ;SUB. IN SEWAGE											
	/ WATER ONLY											

Parts List

Part number	Description	Quantity
SA399779	SA S18-CWS0-0025	1.000 ea
RA390881	RA S18-CWS0-0025	1.000 ea
000692000EJ	NAME PLATE	1.000 ea
000692000WC	WARNING FLAMMABLE VAPORS MAY BE PRESENT	2.000 ea
000613007MS	NP, MEDIUM AC,INVERTER DUTY CSA,STD INDU	1.000 ea
000901001AA	LABEL WARNING	1.000 ea
000613007RC	C UL US NAMEPLATE FOR HAZARDOUS LOC	1.000 ea
000692000MB	BALDOR RELIANCE MOTOR DATA NAMEPLATE	1.000 ea
000613007MS	NP, MEDIUM AC,INVERTER DUTY CSA,STD INDU	1.000 ea
034692002AE	HCSPP 1/4" 304 S.S.	1.000 ea
088203001AB	BRKT,ODE,180SUB 88203-1WB	1.000 ea
004824015A	GREASE POLYREX EM	0.100 lb
032018010CG	HHCS 3/8-16X1-1/4L 316SS	4.000 ea
421900124FU	ORING	1.000 ea
004824018AF	SHELL ROTELLA OIL 10W	1.500 lb
603760001AA	LABYRINTH	1.000 ea
413480001R	RESISTOR ASSEMBLY-BLANKET	1.000 ea
413412006R	LEAD WIRE ASSY	1.000 ea
413412004A	SUBM MOISTURE PROBE	2.000 ea
421900124FU	ORING	1.000 ea
088205001AA	SUB PLT 180 88205-1WC	1.000 ea
032130008CC	HSHCS 3/8-16 X 1.00" L	4.000 ea
032620020JD	HSSS 10-24X5/8L 304S.S.	1.000 ea
421900124FU	ORING	1.000 ea
088204001AA	BRKT,DE,180SUB 88204-1WA	1.000 ea
032018010CG	HHCS 3/8-16X1-1/4L 316SS	4.000 ea
032018006AG	HHCS 1/4-20X3/4L 316 SS	3.000 ea
064262012B	SEAL	1.000 ea
047174005C	SNAP RING	1.000 ea
034692003AE	PPLG 3/8" 304 S.S.	2.000 ea
047174005B	SNAP RING	1.000 ea

064262012C	SEAL	1.000 ea
032080003JB	HWHMS 10-24X3/8L PLTED	4.000 ea
032080003LB	HWHMS 1/4-20X3/8L PLTED	4.000 ea
415031017A	NUT W/WASHER 10-24 C.PLT	4.000 ea
415031017B	NUT W/WASHER1/4-20 C.P	4.000 ea
032677003BG	5/16-18 X 3/8 DHFHBHCS	2.000 ea
047024003B	T/LUG AMP 33218	9.000 ea
603766501A	MACH,CAST,EX180Y,EX1,7BY	1.000 ea
421900072FU	ORING	1.000 ea
032018008BG	HHCS 5/16-18X1 316 SS	4.000 ea
032018006BM	HHCS 5/16-18X3/4 PLTGRN.	1.000 ea
032018006BM	HHCS 5/16-18X3/4 PLTGRN.	1.000 ea
034036013AB	LCKW 5/16 EXT.TOOTH LCKW	1.000 ea
034017013AC	LCKW 5/16" 316 S.S.	2.000 ea
047024003AH	T/LUG AMP 34112	4.000 ea
609181014D	HEAT SHRINK TUBING 3/4	8.000 ea
802386001R	PAIGE INTERNAL MOTOR POWER PLUG	1.000 ea
802386002R	PAIGE INTERNAL MOTOR CONTROL PLUG	1.000 ea
613425013E	12" SAFETY CABLE	2.000 ea
613425013S	FERRULE, SAFETY CABLE	2.000 ea
004824007K	SPECIAL PAINT	0.100 ea
033775004EA	DRSCR #6-1/4 304 S.S.	8.000 ea
034180009DD	KEY 1/4X1/4X1-1/8L	1.000 ea
B3630-9	SUBM THERMOSTAT TAG	1.000 ea
B-3664002	TAG, (NON REGREASABLE)	1.000 ea

AC induction motor performance data

Record #86084 - Typical performance - not guaranteed values

Winding	06WGA0015
Type	0640M
Enclosure	TENV

Nameplate data

Rated Output			5
Volts			200/400
Full Load Amps			15.6/7.8
R.P.M.			1755
Hz	60	Phase	3
KVA Code			J
S.F.			1.15
NEMA Nom. Eff.	89.5	Power Factor	76
Duty			15 MIN
S.F. Amps			

400 V, 60 Hz:
High Voltage Connection

Full Load Torque	15.01 LB-FT
Start Configuration	direct on line
Breakdown Torque	51.89 LB-FT
Pull-up Torque	26.04 LB-FT
Locked-rotor Torque	30.75 LB-FT
Starting Current	53.22 A
No-load Current	3.99
Line-line Res. @ 25°C	1.98 Ω
Temp. Rise @ Rated Load	56°C
Temp. Rise @ S.F. Load	69°C
Locked-rotor Power Factor	41.1
Rotor inertia	0.372 lb-ft²

Load Characteristics 400 V, 60 Hz, 5 HP


% of Rated Load	NL	25	50	75	100	125	150	SF
Power Factor	5	38	58	69	76	80	83	78
Efficiency	0	81.6	88.8	90.2	90.4	88.7	83.9	89.4
Speed	1799	1790	1779	1769	1757	1744	1727	1749
Line amperes	3.99	4.4	5.23	6.43	7.82	9.44	11.6	8.79


DUTY MASTER ALTERNATING CURRENT MOTORS


SQUIRREL-CAGE INDUCTION
ENCLOSURE: TOTALLY ENCLOSED


SUBMERSIBLE

619738-001









SECTION A–A

NOTES:
1. FACE RUNOUT AND ECCENTRICITY .008 MAX T.I.R.
2. PROTECTIVE CONDUIT FURNISHED BY CUSTOMER
3. WEIGHT (LBS): 200±15%
4. PROVIDED WITH CABLE ONNECTOR TO LENGTH OF CABLE AS REQUESTED BY CUSTOMER

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION


REV. DESC: INITIAL RELEASE			
REV: -	VERSION: 00	REVISED: 04:18:07 04/23/2019	TDR: 000001101861
MODEL NO. 619738-001			REF: -
BY: RGGJAO			B


BALDOR

DIM SHT 180TY SUBMERSIBLE WITH CABLE CONNECTORS

619738-001

CD0005





NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0005

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			BALDOR ELECTRIC Co.
REV. LTR: E	BY: JLP	REVISED: 01/19/99 10:15	TDR: 0171435
CD0005		FILE: AAA00005140	MDL: –
		MTL: –	3PH, DV, 9 LEADS