

ABB BALDOR RELIANCE III

Customer information packet

SUM73006-4

30HP, RPM, 3PH, 60HZ, 320TY, XPNV, V1

Class - CLI GP C,D

Division - Not Applicable

Specifications

Enclosure	XPNV
Frame	320TY
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP C,D
Haz Area Division	Not Applicable
Phase	3
Agency Approvals	C UR US CCSA US
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Cable Length	25 FOOT
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Haz Area Temp Code	T3C
Heater Indicator	No Heater
Insulation Class	F
Inverter Code	Not Inverter
IP Rating	IP68
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	V1
Number of Poles	6
Product Family	Pump - Centrifugal
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.15
Shaft Diameter	2.499 IN
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Starting Method	Direct on line

Part Detail

Revision	E
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	85958
Layout	619738-007
Eff. date	12-10-2024
CD Diagram	416820-036
Poles	///
Leads	
Proprietary	False
Created date	05-06-2021

Thermal Device - Winding

Normally Closed Thermostat

Nameplate

000613007MS										
CAT.NO.	SUM73006-4			SPEC NO.	S32-CWS0-0007					
SER.NO.					FRAME SIZE	320TY				
CONSTANT HP RPM	HP	RPM	VOLTS		AMPS		HZ		S.F.	
	30	1180	460		41		6-60		1.00	
	30	1180	460		41		60		1.15	
	@			HZ	CODE	G				
	TYPE	P	INSUL.CLASS		F	TORQUE	10:1_VT			DESIGN
D.E. BRG.	85BJ33J30X			ENCL	TENV	DUTY		15 MIN	PH	3
O.D.E. BRG.	50BC03JPG30A			MOTOR WEIGHT			AMB		40	
	*15 MIN IN AIR ;SUB. IN									
	SEWAGE / WATER ONLY									

000613007RC			
CLASS I GROUP	C D X	NO.	
CLASS II GROUP	X X X		
OPERATING TEMP CODE	T3C		

000692000MB	
SUITABLE FOR OPERATION ON PWM	
INVERTER EQUIPPED WITH IGBT	
DEVICES AND CAPABLE OF	
CARRIER	
FREQUENCY OF 2 KHZ MINIMUM	

000613007MS

CAT.NO.	SUM73006-4			SPEC NO.		S32-CWS0-0007				
	SER.NO.			FRAME SIZE		320TY				
	HP	RPM	VOLTS		AMPS	HZ		S.F.		
	30	1180	460		41	6-60		1.00		
	30	1180	460		41	60		1.15		
	CONSTANT HP RPM		@	HZ	CODE	G				
	TYPE	P	INSUL.CLASS		F	TORQUE	10:1_VT		DESIGN	B
	D.E. BRG.	85BJ33J30X			ENCL	TENV	DUTY	15 MIN	PH	3
	O.D.E. BRG.	50BC03JPG30A			MOTOR WEIGHT		AMB		40	
	*15 MIN IN AIR ;SUB. IN									
SEWAGE / WATER ONLY										

Parts List

Part number	Description	Quantity
SA393326	SA S32-CWS0-0007	1.000 ea
RA383965	RA S32-CWS0-0007	1.000 ea
424476003WL	WIRING DIAGRAM MEDIUMA	1.000 ea
424476003WL	WIRING DIAGRAM MEDIUMA	1.000 ea
000901001AA	LABEL WARNING	1.000 ea
000692000EJ	NAME PLATE	1.000 ea
000692000WC	WARNING FLAMMABLE VAPORS MAY BE PRESENT	2.000 ea
000613007MS	NP, MEDIUM AC,INVERTER DUTY CSA,STD INDU	1.000 ea
000901001AA	LABEL WARNING	1.000 ea
000613007RC	C UL US NAMEPLATE FOR HAZARDOUS LOC	1.000 ea
000692000MB	BALDOR RELIANCE MOTOR DATA NAMEPLATE	1.000 ea
000613007MS	NP, MEDIUM AC,INVERTER DUTY CSA,STD INDU	1.000 ea
034692002AE	HCSPP 1/4" 304 S.S.	1.000 ea
802075601A	BRKT,ODE,320SUB	1.000 ea
004824015A	GREASE POLYREX EM	0.400 lb
032018016EG	HHCS 5/8-11X2 316S.S.	6.000 ea
421900216FU	ORING	1.000 ea
004824018AF	SHELL ROTELLA OIL 10W	5.483 lb
603762053B	SLINGER BLKT	1.000 ea
413480001R	RESISTOR ASSEMBLY-BLANKET	1.000 ea
413412006Y	LEAD WIRE ASSY	1.000 ea
413412004C	SUBM MOISTURE PROBE	2.000 ea
421900192FU	ORING	1.000 ea
802077002A	MTGPLT 320 802077001WCA	1.000 ea
032130016DD	HSXCS 1/2-13X2L 316 S.S.	6.000 ea
032620020JD	HSSS 10-24X5/8L 304S.S.	2.000 ea
421900216FU	ORING	1.000 ea
802076601A	BRKT,DE,320SUB	1.000 ea
032018016EG	HHCS 5/8-11X2 316S.S.	6.000 ea
032018010CG	HHCS 3/8-16X1-1/4L 316SS	3.000 ea
064262018F	SEAL 320 SUBMERSIBLE	1.000 ea

034141300AC	RETAINING RING	1.000 ea
034692003AE	PPLG 3/8" 304 S.S.	2.000 ea
034141275AC	RETAINING RING	1.000 ea
064262018G	SEAL SUBMERSIBLE	1.000 ea
032080003LB	HWHMS 1/4-20X3/8L PLTED	3.000 ea
032080003JB	HWHMS 10-24X3/8L PLTED	4.000 ea
415031017B	NUT W/WASHER1/4-20 C.P	3.000 ea
415031017A	NUT W/WASHER 10-24 C.PLT	4.000 ea
047024003J	TERMINAL LUG	3.000 ea
700385014AC	CCA #6 25' 320/360	1.000 ea
421900124FU	ORING	1.000 ea
032018016EG	HHCS 5/8-11X2 316S.S.	4.000 ea
032018006BM	HHCS 5/16-18X3/4 PLTGRN.	1.000 ea
032018006BM	HHCS 5/16-18X3/4 PLTGRN.	1.000 ea
034036013AB	LCKW 5/16 EXT.TOOTH LCKW	1.000 ea
047024003AH	T/LUG AMP 34112	4.000 ea
609181014D	HEAT SHRINK TUBING 3/4	7.000 ea
004824007K	SPECIAL PAINT	0.100 ea
033775004EA	DRSCR #6-1/4 304 S.S.	10.000 ea
034180024GD	KEY 1/2X1/2X3L 303 S.S.	1.000 ea
B3630-9	SUBM THERMOSTAT TAG	1.000 ea
B-3664002	TAG, (NON REGREASABLE)	1.000 ea

AC induction motor performance data

Record #85958 - Typical performance - not guaranteed values

Winding	12WGA0158
Type	1240M
Enclosure	XPNV

Nameplate data

Rated Output	30		
Volts	460		
Full Load Amps	82/41		
R.P.M.	1175		
Hz	60	Phase	3
KVA Code	G		
S.F.	1.15		
NEMA Nom. Eff.	91	Power Factor	75
Duty	15 MIN		
S.F. Amps			

460 V, 60 Hz:

High Voltage Connection

Full Load Torque	133 LB-FT
Start Configuration	direct on line
Breakdown Torque	294 LB-FT
Pull-up Torque	134 LB-FT
Locked-rotor Torque	175 LB-FT
Starting Current	214 A
No-load Current	19.44
Line-line Res. @ 25°C	0.326 Ω
Temp. Rise @ Rated Load	21°C
Temp. Rise @ S.F. Load	26°C
Locked-rotor Power Factor	30
Rotor inertia	7.66 lb-ft ²

Load Characteristics 460 V, 60 Hz, 30 HP


% of Rated Load	NL	25	50	75	100	125	150	SF
Power Factor	5	38	59	69	75	77	78	76
Efficiency	0	85.6	90.5	92	91.1	90	85.6	90.4
Speed	1199	1194	1190	1185	1179	1173	1165	1175
Line amperes	19.44	21.44	26.28	33.09	41.01	50.22	63.06	46.5


SPEED TORQUE / SPEED CURRENT CURVES



12WGA0158


30HP 460V 60HZ





416820-036

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 3 LEAD CONNECTED



(N.P. 1575-BA)




416820-036

REV. DESC: LOADED TO BUS, C/R 335225		
REV. LTR: -	VERSION: 00	TDR: 000000538207
FILE: \MGA\00000\682		REVISED: 11: 54: 06 04/30/2010
MTL: -		BY: RAGRA

BALDOR

CONN DIAG - STANDARD 3 LEAD
SH 1 of 1

CD0006


NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10:24:49 02/19/2019

BY: ENBRIRO

MTL: —


BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1