

ABB BALDOR RELIANCE III

Customer information packet

UCLE570

5-7 AIR OVERHP, 3450RPM, 1PH, 60HZ, 182TZ, 36

Class - None

Division - Not Applicable

Specifications

Enclosure	TEAO
Frame	182TZ
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Cap Run
Output @ Frequency	7.000 HP @ 60 HZ 5.000 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	20.500 A @ 230.0 V
Design Code	L
Drip Cover	No Drip Cover
Duty Rating	CONT
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	20.5 a
Insulation Class	H
Inverter Code	Not Inverter

Part Detail

Revision	Q
Type	AC
Mech. spec.	36Q214
Base	
Status	PRD/A
Elec. spec.	36WGX572
Layout	36LYQ214
Eff. date	01-02-2025
CD Diagram	CD0208
Poles	02
Leads	2#10 A PH SEE NOTES,2#16 B PH Y
Proprietary	False
Created date	03-06-2014

KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Pipe Or Pipe Adaptor
Motor Lead Quantity/Wire Size	2 @ 10 AWG, A PH
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3646LC
Mounting Arrangement	F1
Number of Poles	2
Overall Length	16.88 IN
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1279L									
CAT.NO.	UCLE570								
SPEC.	36Q214X572G1								
HP	5-7 AIR OVER								
VOLTS	230								
AMP	20.5-27.7								
RPM	3450								
FRAME	182TZ		HZ	60		PH		1	
SER.F.	1.00		CODE	K	DES	L		CL	H
NEMA-NOM-EFF			PF						
RATING	40C AMB-CONT								
CC									
DE	6206		ODE	6205					
ENCL	TEAO		SN						

NP1263L									
CAT.NO.	UCLE570								
SPEC.	36Q214X572G1								
HP	5-7 AIR OVER								
VOLTS	230								
AMP	20.5-27.7								
RPM	3450								
FRAME	182TZ		HZ	60		PH	1		
SER.F.	1.00	CODE	K	DES	L	CL	H		
NEMA-NOM-EFF		PF							
RATING	40C AMB-CONT								
CC									
DE	6206	ODE	6205						
ENCL	TEAO	SN							

Parts List

Part number	Description	Quantity
SA277495	SA 36Q214X572G1	1.000 ea
RA264044	RA 36Q214X572G1	1.000 ea
OC3060F10SP	CYL OIL CAP 60MFD/370V	1.000 ea
EC1216C06SP	ELEC CAP, 216-259 MFD, 250V, 2.06D X 4.	2.000 ea
HA6021A01SP	ADAPTOR, MACH	1.000 ea
36GS5000	GASKET CONDUIT ADAPTOR	1.000 ea
51XB1016A07	10-16 X 7/16 HXWSSLD SERTYB	2.000 ea
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 ea
HW3001B01	BRASS CUP WASHER, FOR #10 SCREW	1.000 ea
36EP3104A46	FREP TENV 36L/M 205 BRG NO GRSR, W/GND	1.000 ea
13XF0832A08	8-32 X.50 PAN HD,SLTD, TYPE F SCREW, ZIN	2.000 ea
51XB1016A05	10-16X5/16HX WA SL SR TYB (F/S)	4.000 ea
HW5100A05	WVY WSHR F/205 & 304 BRGS	1.000 ea
36EP3100B94	PU ENDPLATE, MACH	1.000 ea
HW4600H12	SEAL 1.156 X 1.874 X 0.250 SINGLE LIP DB	1.000 ea
10XN2520A20	1/4-20X 1 1/4 HEX HD X	2.000 ea
XY2520A12	1/4-20 HEX NUT, DIRECTIONAL SERRATIONS	4.000 ea
HW4600B36SP	V-RING SLINGER 1.188 X 1.380 X .24 VITON	1.000 ea
HW2501E18	KEY, 1/4 SQ X 2.000	1.000 ea
HA7000A02	KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA	1.000 ea
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
MJ5001A27	32220KN GRAY SEALER *MIN BUY 4 QTS=1GAL	0.001 qt
HW3200A01	3/8-16X3/4 EYEBOLT WELDED F/S	1.000 ea
MJ1000A02	GREASE, POLYREX EM EXXON	0.050 lb
MG1025C02	WILKOFASST SG, 787.105, TAN	0.022 ga
LD5000A642	LEAD ASSY, ML1400DF14 W/#10 RING 36"	1.000 ea
SP5172A13	37 TYPE L TORQ STAT SWITCH LEAD ASSEMBLY	1.000 ea
WD1000A15	3-520132-2 AMP FLAG (4M/RL NON-CANC/NON-	6.000 ea
35CB4802A02SP	CAPACITOR COVER, STAMPED X	2.000 ea
35GS3001A02	GASKET, CA.COVER, 5.38 LONG .06 CS301	2.000 ea
HA3101A28	THRUBOLT 1/4-20 X 12.500 OHIO ROD	4.000 ea

MP1002A24	6" X 16" .65 MIL. CLEAR PLASTIC BAG	1.000 ea
LC0208	CONNECTION LABEL	1.000 ea
NP1279L	ALUM FARM DUTY UL CSA CC	1.000 ea
LB1624	COMBINED WARNING LABEL, ISO/ANSI PICTOGR	1.000 ea
NP1263L	AUX, GP, ALUM, CC, LASER ETCHED	1.000 ea
36PA1001	PKG GRP, PRINT PK1017A07	1.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
PE-0000002	ZRTG PE ASSEMBLY	1.000 ea
FE-0000001	ZRTG FE ASSEMBLY	1.000 ea

Accessories

Part number	Description	Multiplier
36-3303FD	C FACE KIT FARM DUTY 182-4C, ENCL 6206	A8
36EP1304A62SP	FLANGE MTD ENDPLATE 182-4TD -ENCL (LESS	A8

AC Induction Motor Performance Data

Record # 36968

Typical performance - not guaranteed values

Winding: 36WGX572-R004			Type: 3646LC		Enclosure: TEAO	
Nameplate Data			230 V, 60 Hz: Single Voltage Motor			
Rated Output (HP)		5-7 AIR OVER	Full Load Torque		10.8 LB-FT	
Volts		230	Start Configuration		direct on line	
Full Load Amps		20.5-27.7	Breakdown Torque		37.3 LB-FT	
R.P.M.		3450	Pull-up Torque		20 LB-FT	
Hz	60 Phase	1	Locked-rotor Torque		24.1 LB-FT	
NEMA Design Code		L KVA Code	Starting Current		239 A	
Service Factor (S.F.)		1	No-load Current		6 A	
NEMA Nom. Eff.		0 Power Factor	Line-line Res. @ 25°C		0.197 Ω A Ph 0.838 Ω B Ph	
Rating - Duty		40C AMB-CONT	Temp. Rise @ Rated Load			

Load Characteristics 230 V, 60 Hz, 7 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	95	99	98	99	96	93
Efficiency	67.4	78.3	87.1	83.1	84.6	84.9
Speed	3577	3557	3536	3513	3487	3460
Line amperes	9.39	15.4	20.7	28.4	35.8	43.7


ABB Motors and Mechanical Inc.


WINDING # 36WGX572

Typical performance - not guaranteed values.


7 HP 1 PH 60 HZ 3450 RPM 230 V 3646LC

TORQUES (LB-FT): PO=37.3 PU=20 LR=24.1 LRA=239





CD0208



REV. DESC: REVISE TO MATCH LC0208

REV. LTR: D

BY: JLP

REVISED: 01/09/01 5:10

TDR: 0228770

802000

FILE: AAA00026902

REF: -

MTL: -

BALDOR ELECTRIC Co.

TYPE LC, SV, REV, SEP MTD OIL CAP(S), 5 LEADS

CD0208