

ABB BALDOR RELIANCE III

Customer information packet

VAOM3527

1 AIR OVERHP, 865RPM, 3PH, 60HZ, 56C, 3546M, T

Class - None

Division - Not Applicable

Specifications

Enclosure	TEAO
Frame	56C
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	1.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	900 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ 208.0 V @ 60 HZ
Agency Approvals	C UR US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.400 A @ 230.0 V 4.200 A @ 208.0 V 2.200 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	75.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	2.2 a

Part Detail

Revision	D
Type	AC
Mech. spec.	35E2256
Base	
Status	PRD/A
Elec. spec.	35WGG675
Layout	35LYE2256
Eff. date	04-10-2026
CD Diagram	CD0005
Poles	08
Leads	9#18
Proprietary	False
Created date	09-26-2024

Insulation Class	F
Inverter Code	Not Inverter
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	None
Motor Standards	NEMA
Motor Type	3546M
Mounting Arrangement	F1
Number of Poles	8
Overall Length	14.93 IN
Power Factor	55
Product Family	General Purpose
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	865 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L											
CAT.NO.	VAOM3527										
SPEC.	35E2256G675G1										
HP	1 AIR OVER										
VOLTS	208-230/460										
AMP	4.2-4.4/2.2										
RPM	865										
FRAME	56C		HZ	60			PH	3			
SER.F.	1.00		CODE	K	DES	B	CLASS	F			
NEMA-NOM-EFF	75.5		PF	55							
RATING	40C AMB-CONT										
CC											
DE	6205		ODE	6203							
ENCL	TEAO		SN								

Parts List

Part number	Description	Quantity
SA430892	SA 35E2256G675G1	1.000 ea
RA423112	RA 35E2256G675G1	1.000 ea
11XW0832G06	#8-32 X 3/8, TAPTITE II, HEX WSHR SLTD	1.000 ea
51XT1032A08	10-32X7/16 TY23 HXHD SLTD	2.000 ea
35EP3102B59	FREP ENCL, .50 NPT LEAD HOLE, MACH'D SW	1.000 ea
HW4003A01	T&B PLG-1-RD, 1/2 NPT PLUG ALUM	1.000 ea
HW5100A03	WAVY WASHER (W1543-017)	1.000 ea
35EP3307F00	MASTER DE,205 BRG,.998SH,#26 DRN	1.000 ea
51XN1032A20	10-32 X 1 1/4 HX WS SL SR	2.000 ea
35CB4500	TERMINAL BOX LID STAMPED	1.000 ea
35GS1002	GASKET,1/16 THICK LEXIDE	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 ea
HW2501D13	KEY, 3/16 SQ X 1.375	1.000 ea
HA7000A04	KEY RETAINER 0.625 DIA SHAFTS	1.000 ea
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
MJ1000A02	GREASE, POLYREX EM EXXON	0.050 lb
WD1000A16	2-520128-2 AMP FLAG TERMINAL(4M/RL)	9.000 ea
MG1050G01	CELEROL MEDIUM CHARCOAL METALLIC GRAY	0.017 ga
HA3100A24	THRUBOLT 10-32 X 10.625	4.000 ea
SP5079A01	MODEL 35 3PH TERM PANEL CONN 9LD DUAL VO	1.000 ea
LB1624	COMBINED WARNING LABEL, ISO/ANSI PICTOGR	1.000 ea
LC0005	CONN.DIA.,TY M,9-LD,DUAL VOLT,REVERSING	1.000 ea
NP1256L	ALUM UL CC INDUSTRIAL MOTOR A60	1.000 ea
36PA1000	PKG GRP, PRINT PK1016A08	1.000 ea
PK3082	STYROFOAM CRADLE	1.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
PE-0000001	ZRTG PE ASSEMBLY	1.000 ea



