ABB BALDOR RELIANCE

Customer information packet

VP3575D

1.1/1.5HP, 1750RPM, DC, D90D, 3536P, TEFC, F2
Class - None
Division -

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
10/31/2026 4:53:15 AM

Specifications

Armature Voltage	180 V
Base Speed	1750 rpm
Enclosure	TEFC
Frame	D90D
Frame Material	Steel
Haz Area Class and Group	None
Output Power	1.500 HP
Agency Approvals	CE
	CSA
	UR
Ambient Temperature	40 °C
Armature Current	7.7 a
Armature Inertia	30.342 lb-ft2
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Drip Cover	No Drip Cover
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Frame Prefix	D
Heater Indicator	No Heater
Lifting Lugs	No Lifting Lugs
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	2 @ 14 AWG, A
Motor Lead Termination	Flying Leads
Motor Standards	IEC
Mounting Arrangement	B35
Overall Length	17.88 IN
Product Family	General Purpose
Pulley End Bearing Type	Sealed Bearing
RoHS Status	ROHS COMPLIANT
Service Factor	1.00
Shaft Diameter	0.945 IN

Part Detail

Revision	AJ
Type	DC
Mech. spec.	35P466
Base	
Status	PRD/A
Elec. spec.	35WGZ164
Layout	35LYP466
Eff. date	09-29-2026
CD Diagram	CD0194
Poles	00
Leads	2#14 A Y
Proprietary	False
Created date	01-01-0001

Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger

Nameplate

NP1049L					
CAT.NO.	VP3575D				
SPEC.	35P466Z164				
KW/HP	1.1/1.5 TE		**I.P.**	54	
RPM	1750 TE 1/MIN IC411 31KG				
IEC FRAME	D90D	**TYPE**	3536P		
ARM V	180		**ARM A**	7.7	
FLD V			**FLD A**		
INSUL	F	**AMB.**	40		
DUTY	CONT		**SUPPLY**	K	
BRG/DE	6206	**BRG/ODE**	6205		
BRUSHES	2/BP5000T15				
			BLANK		
SER.					
BLANK	IEC60034-1;-5				
APRV-CE		**APRV-CSA**		**APRV-UL**	

Parts List

Part number	Description	Quantity
SA005529	SA 35P466Z164	1.000 ea
AA003178	AA 35P466Z164	1.000 ea
35EP3110A04	STD FR EP TEFC F2 MTG FOR EXT T'BOLT 35P	1.000 ea
HW5100A05	WVY WSHR F/205 & 304 BRGS	1.000 ea
HW5010A45	WALDES TRUARC #5100-118 (SNAP)RING 1.188	1.000 ea
35EP2500A02	PU ENDPLATE 35DC-PM IEC 165 FLG D80 & D9	1.000 ea
10XN2520A24	1/4-20X 1 1/2 HEX HD X	2.000 ea
HW4600H12	SEAL 1.156 X 1.874 X 0.250 SINGLE LIP DB	1.000 ea
BP5201A14SP	BRUSH HOLDER ASSY	1.000 ea
80XN1032J03	10-32 X 3/16 SET SCREW, HEX SOC, CUP PT	2.000 ea
MJ5004A05	#242-21 LOCTITE GENERAL PURPOSE MED. STR	0.001 ea
35FN3002A05SP	EXFN, PLASTIC, 6.376 OD, .638 ID	1.000 ea
51XB1214A16	12-14X1.00 HXWSSLD SERTYB	1.000 ea
35FH5001A10SP	FAN COVER ASS'Y TEFC HORZ	1.000 ea
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 ea
WD4102A01	SR-6L-1 HEYCO STRN RELIEF OR 23MPO6L10 M	1.000 ea
WD4100A17	PLUG STIMPSON D4036	1.000 ea
35CB4506	CONDUIT BOX LID, STAMPED	1.000 ea
35GS1010	CONDUIT BOX LID, GASKET	1.000 ea
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 ea
HW2505A14	KEY, 8 X 7 MM 1.50 INCHES	1.000 ea
HA7000A12	KEY RETAINER 0.945-1.00 DIA SHAFTS	1.000 ea
MJ5001A27	32220KN GRAY SEALER *MIN BUY 4 QTS=1GAL	0.001 qt
HW3001B02	BRASS CUP WASHER W/GROUND SYMBOL TAB,	1.000 ea
59XW2520A07	.25-20X7/16HEX SER WSHR HD TAPTIE-II T	4.000 ea
MG1050G01	CELEROL MEDIUM CHARCOAL METALLIC GRAY	0.017 ga
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 ea
HA3101A46	THRUBOLT 1/4-20 X 10.00	4.000 ea
BP5000T15	CARBON BRUSH-35P,180VOLTS	2.000 ea
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 ea
LB1624	COMBINED WARNING LABEL, ISO/ANSI PICTOGR	1.000 ea

LC0194	CONNECTION LABEL	1.000 ea
MN416A01	TAG-INSTAL-MAINT no wire (2500 bx)11/25	1.000 ea
NP1049L	NP STD LASER ENGRAVED IEC DC MOTORS, UL	1.000 ea
35PA1007	PKG GRP, PRINT PK1034A07	1.000 ea
PK6503	STRUCTURAL WOOD PSC 1X6X8	1.000 ea

Accessories

Part number	Description	Multiplier
TK3500	TACHO MOUTING KIT TK3500	A8

DC Motor Performance Data
Record # 388
Typical performance - not guaranteed values

Winding: 35WGZ164-R001	**Type:** 3536P	**Enclosure:** TEFC

Nameplate Data	
Rated Output (HP)	1.5
R.P.M.	1750
Armature Volts	180
Armature Amps	7.7
Field Volts	
Field Amps	
Rating - Duty	40C AMB-CONT
Power Supply Code	K

General Characteristics	
Armature Resistance @ 25ºC	0.965 Ω
Voltage Constant	97.47 v/krpm
Armature Inductance	12.959 mH
Armature Inertia	30.342 LI²

Load Characteristics at 180 Armature Volts

Load Point	**1**	**2**	**3**	**4**	**5**	**6**	**7**
Armature Amps	0.5	3.6	5.4	7	8.5	10.2	12
R.P.M.	1819	1762	1727	1701	1682	1661	1632
Torque (LB-FT)	0	2.25	3.375	4.5	5.625	6.75	7.875


ABB Motors and Mechanical Inc.


WINDING # 35WGZ164

1.5 HP DC 1750 RPM 180 V 3536P


ENCL: TEFC DUTY: CONT CL: F

Typical performance - not guaranteed values.




35LYP466
524 = 15.98[406]
536 = 17.85 [453]
548 = 18.85 [479]
3.66[93]
.79[20]
1.97[50]
.420[11]
.138[4]
8 X 7 MM KEY
1.50 [38] LONG
Ø7.78[198]
Ø5.118[130.0]
5.115[129.9]
.9452[24.01]
.9447[23.99]
.75[19]
3.00[76]
3.75[95]
4.50[114]
BRUSH
LOCATION
2 PLCS @ 180°
Ø6.63[168]
4 HOLES
.472 [12] DIA.
Ø6.50 [165] B.C.
LEAD HOLE
PG-16 TAP
45°
45°
3.38[86]
4.26[108]
3.50 +.00 -.06 [89 0 -2]
2.44[62]
2.44[62]
6.50[165]
APPLY SEALER TO
HOUSING BEFORE
PRESSING SEAL IN.
SEAL MUST BE PRESSED
IN W/LIP OUT.
M8 X 1.25 TAP
.62 DEEP (MIN)
DRIVE END DETAIL
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION
REV. DESC: CONVERT PLT TO SWD DWG
REV: M
VERSION: 02
REVISED: 08:05:36 12/04/2024
TDR: 000001245542
MODEL NO. 35LYP466
REF: -
BY: USALMAZ
B
BALDOR - RELIANCE®
STD HORZ 35PM TEFC IEC D90D-B5/B3 F2 2 POLE MOTOR
35LYP466

CD0194



NOTES:

1. CCW ROTATION AS SHOWN FACING COMMUTATOR END. TO REVERSE MOTOR ROTATION OR TACHOMETER OUTPUT POLARITY INTERCHANGE LEADS A1(RED) & A2(BLACK)

2. LEAD COLORS FOR REFERENCE ONLY & NOT SPECIFIED BY THIS DRAWING. LEAD COLORS SPECIFIED BY LAYOUT DRAWING & BILL OF MATERIAL ONLY.

CD0194

MATL: –				BALDOR ELECTRIC Co.
REV: E	ADDED NOTE "LEAD COLORS FOR REFERENCE ONLY &....			
CD0194	SCALE: –	BY: CK	REVISED: 07/28/95	CD TYPE P DC PERMANENT MAGNET MOTORS AND TACHOMETERS
	FILE: AAA00004503		TDR: 0078737	