

ABB BALDOR RELIANCE III

Customer information packet

ZDPM18030C-BV

30HP, 1800RPM, 3PH, 60HZ, 1852C, TEBC, FOOT,

Specifications

Enclosure	TEAO
Frame	FL1852C
Frame Material	Aluminum
Frequency	60.00 Hz
Output @ Frequency	30.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Current @ Voltage	32.300 A @ 460.0 V
Duty Rating	CONT
Feedback Device	TACHOMETER
Frame Prefix	FL
Heater Indicator	No Heater
High Voltage Full Load Amps	32.3 a
Insulation Class	H
Motor Standards	NEMA
Mounting Arrangement	F3
Overall Length	28.05 IN
Product Family	General Industrial
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Service Factor	1.00
Shaft Diameter	1.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	1800 rpm
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat

Part Detail

Revision	E
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	PM3756A
Layout	617235-315
Eff. date	10-24-2019
CD Diagram	422927-001
Poles	04
Leads	
Proprietary	False
Created date	04-09-2015

Nameplate

000613006NS									
	DUTY	HP	RPM	AMPS	VOLTS	HZ			
	CONT	30	1800		32.3	460	60		
	CONT	30	3000		30.6	460	100		
CAT.NO.	ZDPM18030C-BV		SPEC. NO.		P18M0505				
SER.NO			FR	FL 1852C		INSUL	H		
PH.	3	MAX SAFE SPEED		7200		AMB.	40	MIN. AMB.	-25
DESIGN NO.	PM3756A		TYPE		ENCL.		TEAO-BC		
S.F.	1.0		D.E. BRG.		45BC02JPP30A				
ENCL MOD			O.D.E. BRG.		35BC02JPP30A				

000692000VY

MEAS OPEN CIRCUIT VOLTAGE

IS VOLTS AT RPM.

Parts List

Part number	Description	Quantity
WS286790	WS P18M0505	1.000 ea
RA282998	RA P18M0505	1.000 ea
000692000FP	NP, WARNING LIFT INSTRUCTIONS	1.000 ea
033775004EA	DRSCR #6-1/4 304 S.S.	8.000 ea
000613006NS	RPM AC WITH CERTIFIED LOGO	1.000 ea
000692000NH	LABEL DIRECTION AIR FL	1.000 ea
000692000VY	PERMANENT MAGNET MOTOR NAMEPLATE	1.000 ea
411716004A	219P039 - 219P039 - LA	1.000 ea
418056062A	NP AC BLOWER DATA	1.000 ea
422927001	C/D LABEL	1.000 ea
032003200CB	FL1852 THRU BOLT	4.000 ea
033102012AG	HXNUT LEAD CONN 1/4-20 GR5 ZP	4.000 ea
034017012AB	LCKW 1/4 STD. PLATED 034017012AF	4.000 ea
036000050JB	M8-1,25 X 50 MHHCS	2.000 ea
400638001D	WAVEN (Customer number 43699)	1.000 ea
411693051B	LUG, LIFTING	2.000 ea
HA4054	SHORT T-DRAIN FITTING, .125" N.P.T.	1.000 ea
HA4054	SHORT T-DRAIN FITTING, .125" N.P.T.	1.000 ea
807580002BAA	BRKT,DE,FL181 807580-1WCC	1.000 ea
807580003AAB	BRKT,ODE180AC 807580-1WCC	1.000 ea
036000012HB	HHCS M6X12MM LONG PLATED	2.000 ea
036000040JB	HHCS,DE BRKT (M8-1.25X40MM PLTD.) AA	4.000 ea
418010006A	CAST,MPLATE,180-280,EX1,7BY	1.000 ea
036000012HB	HHCS M6X12MM LONG PLATED	3.000 ea
036620009AB	M8 EXTERNAL LK WASHER	1.000 ea
036310010FB	RHMS TERM/BLK MTG	2.000 ea
418057461B	PLATE, ENCODER	1.000 ea
418057461B	PLATE, ENCODER	1.000 ea
418057373A	SCREW SHEET METAL	4.000 ea
036320008CB	M2.5 SCREW	4.000 ea
036500006AB	M4-0.7 METRIC HEX NUT	2.000 ea


065530000B	GASK	1.000 ea
075451000A	COVER, CONDUIT BOX	1.000 ea
406673002C	.75 CAP PLUG	2.000 ea
415000103G	TLUG	1.000 ea
422962051BW	STUB SHAFT	1.000 ea
800123015A	RESOLVER	1.000 ea
417733001A	GSK C/ BOX BASE	2.000 ea
418018074A	GROUND LABEL G100 METRIC 160 D.C.	1.000 ea
418057445B	SCREW	4.000 ea
418057260A	SCREW PHILLIPS PAN HD	4.000 ea
418057373A	SCREW SHEET METAL	3.000 ea
613450001G	BLMTR EBM	1.000 ea
706320003A	CONDUIT BOX	1.000 ea
807505050B	SHROUD, FAN/BLOWER	1.000 ea
807505051A	GRILL, FAN COVER	1.000 ea
418057243A	GROOVE PIN	1.000 ea
807504052D	FL180 FRAME	1.000 ea
000640000P	TAG WINDING THERMOST	1.000 ea
004824007K	SPECIAL PAINT	0.100 ea
034180022FA	KEY 3/8X3/8X2-3/4 L	1.000 ea
LB1549	LABEL, BLANK 1.375 X 2.250 IMPRINTABLE	1.000 ea
004824007AB	PAINT,XT	0.100 ea

S.O. 0	VOLTS 460	TYPE IPM	STATOR RES. @ 25 °C .3489
FRAME FL1852	AMPS 32	ENCLOSURE TEBC	OHMS (BETWEEN LINES)
HP 30	DUTY CONT	MAX SAFE RPM 7200	
BASE SPEED 1800	S.F. 1.0	WK ² (Lb-Ft ²) .96	
PHASE/HERTZ 3/60	AMB °C/INSUL 40/H	MAX INSTANTANEOUS OVERLOAD AMPS 96	

VARIABLE SPEED PERFORMANCE

HP	AMPS (rms)	RPM	GAMMA*	POWER FACT.	EFF.	VOLTS (L-L) (rms)	Em (L-N) (rms)	Lq (mH)	Ld (mH)
OpenCkt**	N/A	1800	5.0	N/A	N/A	N/A	185	N/A	N/A
OpenCkt, hot	N/A	1800	5.0	N/A	N/A	N/A	160	N/A	N/A
6.10	8.0	1800	30.7	96.5	93.0	367	160	58.3	8.90
13.8	16.0	1800	39.6	95.3	94.2	413	160	42.6	8.70
21.7	24.0	1800	44.0	94.0	94.7	436	160	34.2	8.50
30.0	32.0	1800	48.5	92.9	94.7	459	160	30.5	8.30

Remarks: TYPICAL DATA
 CONSTANT TORQUE 0-1800 RPM, CONSTANT POWER 1800-3000 RPM
 200% OVERLOAD BELOW BASE SPEED TAPERED TO 100% AT 3000 RPM



*Gamma is the current angle relative to counter emf, defined to be positive when current leads counter emf.

Equivalently, Gamma is positive when Id is negative.

**Data at 25°C - all other data at rated temperature

BALDOR


DR. BY	CD
CK. BY	RM
APP. BY	RM
DATE	4/23/10

IPM MOTOR	
PERFORMANCE	PM3756A
DATA	ISSUE DATE 4/23/10

S.O. 0	VOLTS 460	TYPE IPM	STATOR RES. @ 25 °C .3489
FRAME FL1852	AMPS 32	ENCLOSURE TEBC	OHMS (BETWEEN LINES)
HP 30	DUTY CONT	MAX SAFE RPM 7200	
BASE SPEED 1800	S.F. 1.0	WK ² (Lb-Ft ²) .96	
PHASE/HERTZ 3/60	AMB °C/INSUL 40/H	MAX INSTANTANEOUS OVERLOAD AMPS 96	

Lq, Ld, & Torque vs. RMS Phase Amps

CONSTANT TORQUE 0-1800 RPM, CONSTANT POWER 1800-3000 RPM
200% OVERLOAD BELOW BASE SPEED TAPERED TO 100% AT 3000 RPM



REMARKS: TYPICAL DATA


BALDOR

DR. BY	CD
CK. BY	RM
APP. BY	RM
DATE	4/23/10

**IPM MOTOR
PERFORMANCE
DATA**


PM3756A

ISSUE DATE 4/23/10



INDUSTRIAL ALTERNATING CURRENT MOTORS
RPM AC

STEEL, CAST IRON, MILL AND TERMINAL BOARD CONDUIT BOX DIMENSIONS
NEMA FRAMES RL210 thru RL280 and IEC FRAMES RDL132 thru RDL180
NEMA FRAMES FL180 thru FL280 and IEC FRAMES FDL112 thru FDL180



FRAME	TYPE	TERMINAL STRIP	AMPS	C/BOX	Y	TA	T	AA
FL180	STEEL	N	40	706320003A	5.00	1.62	3.00	1.12
FL180	STEEL	Y/N	75	706320003A	6.12	2.36	4.38	1.75/2.00
FL180	STEEL	N	208	706320007A	6.62	2.00	7.00	2.50/3.00
FL180	CAST IRON	Y/N	208	706320004C	6.75	2.36	4.38	1.75/2.00
FL180 & FDL11	MILL	Y	100	706310056A	7.75	2.30	4.40	PG29/PG16

FL210 & RL210	STEEL	N	61	075452000B	6.34	2.00	4.12	1.75
FL210 & RL210	STEEL	N	121	075452001A	7.69	2.36	5.25	1.94
FL210 & RL210	STEEL	N	306	706320016A	9.00	4.12	8.44	4.89
FL210 & RL210	CAST IRON	N	110	075460062B	7.25	2.50	5.25	1.5 TAP
FL210 & RL210	MILL	Y	100	706310229A	7.75	2.30	4.40	PG29/PG16
FL210 & RL210	MILL	Y	160	706310056A	9.00	3.06	5.40	PG36/PG16
FL210 & RL210	MILL	Y/N	235	706310056B	11.42	4.00	6.72	2.50

FL250 & RL250	STEEL	N	61	075452000B	6.34	2.00	4.12	1.75
FL250 & RL250	STEEL	N	121	075452001A	7.69	2.36	5.25	1.94
FL250 & RL250	STEEL	N	306	706320016A	9.00	4.12	8.44	4.89
FL250 & RL250	CAST IRON	N	110	075460062B	7.25	2.50	5.25	1.5 TAP
FL250 & RL250	CAST IRON	N	210	706320013A	10.50	4.88	9.00	4.0 TAP
FL250 & RL250	MILL	Y	100	706310229A	7.75	2.30	4.40	PG29/PG16
FL250 & RL250	MILL	Y	160	706310056B	9.00	3.06	5.40	PG36/PG16
FL250 & RL250	MILL	Y/N	235	706310057A	11.42	4.00	6.72	2.50
FL250 & RL250	MILL	Y	235	706310063B	14.39	7.43	12.15	BLANK

FL280 & RL280	STEEL	N	160	706320029A	7.25	3.50	7.06	2.50
FL280 & RL280	STEEL	N	306	706320016A	9.00	4.12	8.44	4.89
FL280 & RL280	STEEL	N	500	702658001C	14.62	7.56	12.70	5.00
FL280 & RL280	CAST IRON	N	140	706320012B	9.25	4.81	8.56	3.0 TAP
FL280 & RL280	CAST IRON	N	210	706320013A	10.50	4.88	9.00	4.0 TAP
FL280 & RL280	CAST IRON	N	510	706320014D	15.00	7.56	12.81	5.0 TAP
FL280 & RL280	MILL	Y	100	706310056A	7.75	2.30	4.40	PG29/PG16
FL280 & RL280	MILL	Y	160	706310056B	9.00	3.06	5.40	PG36/PG16
FL280 & RL280	MILL	Y/N	235	706310057A	11.42	4.00	6.72	2.50
FL280 & RL280	MILL	Y	400	706310063B	14.39	7.43	12.15	BLANK

FRAME SIZE	XAB	XX	XY	PART NUMBER	FRAME SIZE	XAB	XX	XY	PART NUMBER
FL210/RL210/FL112	7.38	4.25	4.25	602007--26-A	FL210/RL210/FL112	10.88	8.00	8.00	706310-3-B
FL250/RL250/FL160	8.44	4.25	4.25	602007--26-A	FL250/RL250/FL160	11.88	8.00	8.00	706310-3-B
FL280/RL280/FL280/180	9.12	4.25	4.25	602007--26-A	FL280/RL280/FL280/180	12.62	8.00	8.00	706310-3-B

(1) 1" MIN. CONDUIT.
(2) 1/2" MIN. PIPE TAP.
(3) CUSTOMER TO PROVIDE HOLE PER CONDUIT.
(4) 2" DIA. DIA. OR 1" DIA. DIA. DIA.

TERMINAL BOX CAN BE ROTATED FOR LEAD OUTLET AT TOP, SIDES OR BOTTOM.
TERMINAL BOX LOCATED ON OPPOSITE SIDE WHEN F-2, V-1, V-4, V-5, V-7,
OR C-1 MOUNTING IS SPECIFIED. BOX LOCATED ON TOP WHEN SPECIFIED.


CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: ADD 706310-637 & 639 BOX	TDR: 000001180260
REV. LTR: F	VERSION: 06
FILE: \RGG\00003\692	REVISED: 11:08:56 10/26/2021
MTL: -	BY: RCGRWM

BALDOR - RELIANCE®

DIM SHT NEMA RL210-RL280 FL180-FL280 IEC RDL132-RDL180

422927-001



NOTE:
DATA TO BE SIZED
SO THAT IT FITS INTO
MATERIAL DECAL
DIMENSIONS. MAKE
LETTERS & NUMBERS
AS LARGE AS POSSIBLE.

MATERIAL: CERAMATIC DGF-P4
PERMA GRIP ADHESIVE

ALL LETTERS, NUMBERS
AND LINES TO BE BLACK
ON WHITE BACKGROUND.

422927-001

REV. DESC: CHANGE BACKGROUND COLOR FROM GOLD TO WHITE		
REV. LTR: B	VERSION: 02	TDR: 000000788708
FILE: \RGG\00000\203	REVISED: 08:09:29 03/04/2013	
MTL: -	BY: RGGWT	

BALDOR

EXTERNAL CONNECTION LABEL

SH 1 of 1